Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Fix All Crystal

Reference nr: 230212

Unique identification code of the product-type

Fix All Crystal

Intended use or uses of the construction product

Sealants for facade for interior application
Sealants used for sanitary applications

Name and contact address of the manufacturer as required pursuant to Article 11(5)

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

Authorised Representative

Not relevant

System(s) of assessment and verification of consistency of performance of the construction product, as set out in Annex V

System 3: for reaction to fire
System 3: for essential characteristics

Construction product in accordance with applicable harmonised specifications

EN 15651-1:2012: Type F-INT
EN 15651-3:2012: Type XS1

The notified body

The notified body IFT Rosenheim GmbH, NB 0757 has carried out Determination of the Product Type under system 3.

Soudal NV
Everdongenlaan 18 - 20, B-2300 Turnhout
+32 (0)14.42.42.31
www.soudal.com info@soudal.com

SOUDAL

Declared Performance: EN 15651-1:2012

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-1:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Tensile properties at maintained extension after water immersion	NF	
Elongation at break	≥ 25%	
Durability	Pass	

Conditioning: Method A
Test Substrate: aluminium, mortar

Declared Performance: EN 15651-3:2012

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-3:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Tensile properties at maintained extension after water immersion	NF	
Microbiological growth	0	
Durability	Pass	

Conditioning: Method A
Test Substrate: aluminium, glass

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by

Ing. W. Dierckx
Senior Technical Product Manager
Soudal NV- Belgium

Soudal NV
Everdongenlaan 18 - 20, B-2300 Turnhout
+32 (0)14.42.42.31
www.soudal.com info@soudal.com

SOUDAL

CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

Fix All Crystal

CE

NB 0757

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

14

Reference nr: 230212

EN 15651-1:2012
EN 15651-3:2012
Sealants for facade for interior application
Sealants used for sanitary applications

Fix All Crystal

EN 15651-1:2012: Type F-INT
EN 15651-3:2012: Type XS1

Conditioning: Method A
Test Substrate: aluminium, mortar, glass

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	E	EN 15651-1:2012 EN 15651-3:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Tensile properties at maintained extension after water immersion	NF	
Elongation at break	≥ 25%	
Microbiological growth	0	
Durability	Pass	

Soudal NV
Everdongenlaan 18 - 20, B-2300 Turnhout
+32 (0)14.42.42.31
www.soudal.com info@soudal.com

Unique identification code of the product-type
Fix All Crystal

Intended use or uses of the construction product
Sealants for facade for interior application
Sealants used for sanitary applications

Name and contact address of the manufacturer as required pursuant to Article 11(5)
Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

Authorised representative
Soudal (UK) Ltd, Soudal House, Unit 1, Centurion Way, Centurion Park, Tamworth B77 5PNSoudal House, Unit 1, Centurion Way, Centurion Park, Tamworth B77 5PN.

System(s) of assessment and verification of consistency of performance of the construction product, as set out in Annex V
System 3: for reaction to fire
System 3: for essential characteristics

Construction product in accordance with applicable designated standards
BS EN 15651-1:2012: Type F-INT
BS EN 15651-3:2012: Type XS1

Approved Body
4ward Testing, AB 2538, has carried out Determination of the Product Type under system 3.

Soudal NV
Everdongenlaan 18 - 20, B-2300 Turnhout
+32 (0)14.42.42.31
www.soudal.com info@soudal.com

Declared Performance: BS EN 15651-1:2012

Essential Characteristics	Performance	Designated Technical Specification
Reaction to fire	E	BS EN 15651-1:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Elongation at break	NPD	
Durability	Pass	

Conditioning: Method A
Test substrate: aluminium, mortar

Declared Performance: BS EN 15651-3:2012

Essential Characteristics	Performance	Designated Technical Specification
Resistance to flow	≤ 3 mm	BS EN 15651-3:2012
Loss of volume	NPD	
Water and air tightness		
Microbiological growth	NPD	
Durability	Pass	

Conditioning: Method A
Test substrate: aluminium, glass

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for on behalf of the manufacturer by

Ing. W. Dierckx
Senior Technical Product Manager
Soudal NV- Belgium

Soudal NV
Everdongenlaan 18 - 20, B-2300 Turnhout
+32 (0)14.42.42.31
www.soudal.com info@soudal.com

UKCA marking

In accordance with the CPR Regulation (EU) N° 305/2011

Fix All Crystal

UK CA

AB 2538

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium
21
UK Reference nr DOP: 230212UK

BS EN 15651-1:2012
BS EN 15651-3:2012

Sealants for facade for interior application
Sealants used for sanitary applications

Fix All Crystal

BS EN 15651-1:2012: Type F-INT
BS EN 15651-3:2012: Type XS1

Conditioning: Method A
Test substrate: aluminium, mortar

Essential Characteristics	Performance	Designated Technical Specification
Reaction to fire	E	BS EN 15651-1:2012 BS EN 15651-3:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	NPD	
Elongation at break	NPD	
Microbiological growth	NPD	
Durability	Pass	

Soudal NV
Everdongenlaan 18 - 20, B-2300 Turnhout
+32 (0)14.42.42.31
www.soudal.com info@soudal.com