

Sikaflex[®] EBT+ Colours

DECLARATION OF PERFORMANCE No. 39862285

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	39862285
2	INTENDED USE/S	Sealant for non-structural joints in floors. PW EXT-INT CC
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	AVCP 3
6a	HARMONISED STANDARD:	EN15651-4:2012
	Notified body/ies:	1213

Declaration of Performance

Sikaflex[®] EBT+ Colours
39862285
2024/11, ver. 01
1003, 1009

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class E	3	EN15651-4: 2012
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness			
Tensile properties at maintained extension.	NF at 100 % elongation		
Loss of volume	≤10 %	3	
Tensile properties at maintained extension after water immersion.	NF at 100 % elongation	3	
Tear Resistance	NF at 50 % elongation		
Adhesion/cohesion properties at maintained extension after 28 days water immersion.	NF at 100 % elongation, Change of secant modulus: ≤50 %	3	
Adhesion/cohesion properties at maintained extension after 28 days salt water immersion.	NF at 100 % elongation	3	
Tensile properties at maintained extension for non structural sealants used in joints in cold climate areas (-30 °C)	NF at 100 % elongation	3	
Durability	Pass	3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Paul Thomas
 Function: Technical Product Coordinator
 At Leeds on 21 November 2024

Name : Alex West
 Function: Product Manager
 At Leeds on 21 November 2024




End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Sikaflex® PRO-3 Purform
 39862285
 2024/11 , ver. 01
 1003, 1009





24

Sika Services AG, Zurich, Switzerland

DoP No. 39862285

EN15651-4:2012

Notified Body: 1213

Sealant for non-structural joints in floors.
PW EXT-INT CC

Reaction to fire	Class E
Release of chemicals dangerous to the environment and health	NPD
Water tightness and air tightness	
Tensile properties at maintained extension.	NF at 100 % elongation
Loss of volume	≤10 %
Tensile properties at maintained extension after water immersion.	NF at 100 % elongation
Tear Resistance	NF at 50 % elongation
Adhesion/cohesion properties at maintained extension after 28 days water immersion.	NF at 100 % elongation, Change of secant modulus: ≤50 %
Adhesion/cohesion properties at maintained extension after 28 days salt water immersion.	NF at 100 % elongation
Tensile properties at maintained extension for non structural sealants used in joints in cold climate areas (-30 °C)	NF at 100 % elongation
Durability	Pass

Declarations see sika.co.uk

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Declaration of Performance

Sikaflex® PRO-3 Purform
39862285
2024/11, ver. 01
1003, 1009

Declaration of Performance

Sikaflex® PRO-3 Purform

39862285

2024/11 , ver. 01

1003, 1009

