



Declaration of performance according to Construction Product Regulation (EU 305/2011)

No. **10015823 / OEM-TST-2200-8-2670-WMO-9016**

1. Unique identification code of the product-type:

**29357 / 2-Column 1992mm x 394mm White**

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

in heating systems in buildings

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):

Zehnder GmbH  
Almweg 34  
DE-77933 Lahr

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

None

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

6. a) In case of the declaration of performance concerning a construction product under system 3 covered by a harmonised standard:

WSPLab, Kapuzinerweg 7, DE-70374 Stuttgart (N.B. 1428)

has assessed and evaluated the product under system 3 and issued the following report:

07.50.ZEH.052

(description of the third party tasks as set out in Annex V)

(certificate of constancy of performance, certificate of conformity of the factory production control, test/calculation reports – as relevant)

6. b) In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant



7. Declared performance

Harmonized technical specification according to EN 442-1:2014

Essential characteristics	Performance
Reaction to fire	A1
Release of dangerous substances	None
Maximal operating pressure (MOP)	1000 kPa
Pressure tightness	no leakage at 1,30 x MOP
Resistance to pressure	no breakage at 1,69 x MOP
Surface temperature	maximum 110 °C
Rated thermal output	Φ30 = 572 W
Rated thermal output	Φ50 = 1103 W
Thermal output in different operating conditions (characteristic curve)	$\Phi = 0,91 \times \Delta T^{1,28}$
Resistance against corrosion	no corrosion after 100 h humidity test
Resistance against minor impact	Class 0

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Lahr, 03.03.2023  
Version 03-2018

Zehnder GmbH  
  
Clemens Ganter  
General Manager