

INSTALLATION GUIDELINES

Note: Always use a professional installer when fitting our products

BEFORE YOU BEGIN

- ⚠ **WARNING:** Risk of personal injury. Metal surfaces are sharp and can cause severe cuts. Use gloves and handle sink edges carefully.
- Observe all local plumbing and building codes.
- Shut off the hot and cold water supplies.
- All information in this guide is based on the latest product information available at the time of publication.

RECOMMENDED TOOLS AND MATERIALS

- Pencil and Marker
- Measuring Tape
- Drill
- Scissors
- Sealant
- Safety Glasses
- Keyhole/Compass or jigsaw
- Putty Knife



Undermount Sink Installation

1. Cut the Sink Mounting Holes

- ⚠ **CAUTION: Risk of product damage.** To avoid damage to the sink, do not cut, drill, or sand the kitchen worktop while it is positioned over the sink.
- Before cutting, measure the sink's actual dimensions to ensure correct.
- Drill a pilot hole inside the cut-out line.
- Using a jigsaw or keyhole saw, cut along the inside of the template if provided.





2. Install the Mounting Brackets (if required)

- Equally space the required number of mounting brackets and locate the mounting holes on the underside of the kitchen worktop 1-3/8" (3.5cm) from the edge of the kitchen worktop opening.
- The type of fastener needed is dependant upon the kitchen worktop material and should be recommended by the kitchen worktop supplier.
- Loosely install the mounting brackets to the kitchen worktop.
- Turn the brackets parallel to the opening to allow for easy installation of the sink.



3. Apply the Sealant





- Clean all residue from the top rim of the sink.
- Clean the underside of the kitchen worktop around the cut-out area and make sure the surface is smooth and free of defects.
- Apply a generous bead of silicone or latex sealant to the rim of the sink near the inside edge.



4. Finish the Installation

- Position and align the sink with the opening in the kitchen worktop. The corner of the sink should be flush with the inside edge of the kitchen worktop.
- Rotate the mounting brackets over the sink rim.
- Tighten each bracket until snug while maintaining proper alignment.
- Wipe away any excess sealant with a dry cloth.
- Allow the sealant to set for a minimum of 30 minutes. Follow the instructions provided with the sealant.

INSET SINK INSTALLATION



Suggested Clip Placement
(Approximately 8 clips is normally sufficient)

- Where a sealant strip is pre fitted to the underside of the sink please pay close attention to the seal near the corner of the sink. Often, due to tension on the strip, additional silicone sealant should be applied on the corners (and elsewhere if required) to ensure a fully waterproof seal.

CARE AND CLEANING

Stainless Steel

Rinse your stainless steel sink thoroughly after each use, and use a dabbing action to dry with a clean, soft cloth. Clean your sink once a week with Bar Keepers Friend or Shiny Sinks.

Always apply stainless steel cleaner/polish with a nonabrasive cloth or sponge, working with, not across the grain. Do not use steel wool, wire brushes or abrasive pads to clean your sink.

If you use cleaners containing bleach, be sure to rinse the surface immediately after you clean it to avoid corrosion or staining. Do not allow cleaners to remain in contact with the sink surface for long periods of time.



Kitchen sink made of:
stainless steel

Carysil Products Ltd.
Crossley Stud Farm,
Buxton Road, Congleton,
CW12 2PN
EN 13310:2015

Cleanability: Pass
Load resistance: N/A
Durability: Pass

Carysil Products Ltd. Crossley Stud Farm, Buxton Road, Congleton, CW12 2PN