



**SAFETY DATA SHEET**  
POLYURETHANE VARNISH - GLOSS

Page: 1

Compilation date: 18/08/2017

Revision No: 1

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** POLYURETHANE VARNISH - GLOSS

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** PC9a: Coatings and paints, thinners, paint removers. Professional Use. Consumer Use.

**1.3. Details of the supplier of the safety data sheet**

**Company name:** J.V. Barrett & Co Ltd

St Ivel way

Warmley

Bristol

BS30 8TY

United Kingdom

**Tel:** 01179600060

**Fax:** 01179352437

**Email:** [sales@barrettine.co.uk](mailto:sales@barrettine.co.uk)

**1.4. Emergency telephone number**

**Emergency tel:** +44 (0) 1179 672222 (Office hours only 8am - 5pm Mon- Thurs. 8 am - 4.30 pm Fri.)

+44 (0) 1270 502891 (Out of hours emergency number)

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** Aquatic Chronic 3: H412; Flam. Liq. 3: H226; STOT SE 3: H336; STOT RE 1: H372; -: EUH066; -: EUH208; Skin Sens. 1A: H317

**Most important adverse effects:** Repeated exposure may cause skin dryness or cracking. Contains 2-butanone oxime, colbalt containing polymer. May produce an allergic reaction. Flammable liquid and vapour. May cause an allergic skin reaction. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains 2-butanone oxime, colbalt containing polymer. May produce an allergic

[cont...]

# SAFETY DATA SHEET

## POLYURETHANE VARNISH - GLOSS

Page: 2

reaction.

H226: Flammable liquid and vapour.

H317: May cause an allergic skin reaction.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

**Hazard pictograms:** GHS02: Flame

GHS07: Exclamation mark



**Signal words:** Warning

**Precautionary statements:** P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P260: Do not breathe vapours/spray.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER/doctor if you feel unwell.

P403+235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

P233: Keep container tightly closed.

P501: Dispose of contents/container to special waste collection point.

### 2.3. Other hazards

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS - REACH registered number(s): 01-2119463258-33-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
--------	-----	-----------	--------------------	---------

[cont...]

# SAFETY DATA SHEET

## POLYURETHANE VARNISH - GLOSS

Page: 3

919-857-5	-	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	10-30%
-----------	---	---	---	--------

HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%). - REACH registered number (s): 01-2119458049-33

-	919-446-0	-	Flam. Liq. 3: H226; STOT SE 3: H336; STOT RE 1: H372; Asp. Tox. 1: H304; Aquatic Chronic 2: H411	10-30%
---	-----------	---	--	--------

XYLENE - REACH registered number(s): 01-2119488216-32-XXXX

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	-----------	---	---	-------

2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT - REACH registered number(s): 01-2119979088-21-XXXX

245-018-1	22464-99-9	-	Repr. 2: H361	<1%
-----------	------------	---	---------------	-----

2-BUTANONE OXIME - REACH registered number(s): 01-2119539477-28-XXXX

202-496-6	96-29-7	-	Carc. 2: H351; Acute Tox. 4: H312; Eye Dam. 1: H318; Skin Sens. 1: H317	<1%
-----------	---------	---	---	-----

### Section 4: First aid measures

#### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

[cont...]

# SAFETY DATA SHEET

## POLYURETHANE VARNISH - GLOSS

Page: 4

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS. Refer to section 13 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

### 7.3. Specific end use(s)

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

[cont...]

# SAFETY DATA SHEET

## POLYURETHANE VARNISH - GLOSS

Page: 5

**Hazardous ingredients:**

**XYLENE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m <sup>3</sup>	441 mg/m <sup>3</sup>	-	-

**DNEL/PNEC Values**

**Hazardous ingredients:**

**HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS**

Type	Exposure	Value	Population	Effect
DNEL	Dermal (repeated dose)	208 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation (repeated dose)	871 mg/m <sup>3</sup> /8H	Workers	Systemic
DNEL	Dermal (effects on fertility)	125 mg/kg bw/day	Consumers	Systemic
DNEL	Inhalation (repeated dose)	185 mg/m <sup>3</sup> /24H	Consumers	Systemic
DNEL	Oral	125 mg/kg bw/day	Consumers	Systemic

**HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%).**

Type	Exposure	Value	Population	Effect
DNEL	Dermal (repeated dose)	44 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation (repeated dose)	330 mg/m <sup>3</sup> /8h	Workers	Systemic
DNEL	Dermal (repeated dose)	26 mg/kg bw/day	General Population	Systemic
DNEL	Inhalation (repeated dose)	76 mg/m <sup>3</sup> /24h	General Population	Systemic
DNEL	Oral (repeated dose)	26 mg/kg bw/day	General Population	Systemic

**2-BUTANONE OXIME**

Type	Exposure	Value	Population	Effect
DNEL	Inhalation (repeated dose)	9 mg/m <sup>3</sup>	Workers	Systemic
DNEL	Inhalation (repeated dose)	2.7 mg/m <sup>3</sup>	General Population	Systemic
DNEL	Inhalation (repeated dose)	3.33 mg/m <sup>3</sup>	Workers	Local
DNEL	Inhalation (repeated dose)	2 mg/m <sup>3</sup>	General Population	Local
DNEL	Dermal (repeated dose)	1.3 mg/kg bw/day	Workers	Systemic
DNEL	Dermal (repeated dose)	780 µg/kg bw/day	General Population	Systemic
DNEL	Dermal	2.5 mg/kg bw/day	Workers	Systemic
DNEL	Dermal	1.5 mg/kg bw/day	General Population	Systemic
PNEC	Fresh water	256 µg/l	-	-
PNEC	Microorganisms in sewage treatment	177 mg/l	-	-

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

[cont...]

# SAFETY DATA SHEET

## POLYURETHANE VARNISH - GLOSS

Page: 6

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

### Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Colourless

**Odour:** Solvent

**Evaporation rate:** No data available.

**Oxidising:** No data available.

**Solubility in water:** Insoluble

**Viscosity:** No data available.

**Boiling point/range°C:** No data available.

**Melting point/range°C:** No data available.

**Flammability limits %: lower:** No data available.

**upper:** No data available.

**Flash point°C:** 39 cc

**Part.coeff. n-octanol/water:** No data available.

**Autoflammability°C:** No data available.

**Vapour pressure:** No data available.

**Relative density:** 0.91

**pH:** No data available.

**VOC g/l:** >399

#### 9.2. Other information

**Other information:** No data available.

### Section 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

#### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

#### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

#### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

### Section 11: Toxicological information

[cont...]

# SAFETY DATA SHEET

## POLYURETHANE VARNISH - GLOSS

Page: 7

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

**HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS**

GASES	RBT	24H LD50	> 5000	mg/kg
ORAL	RAT	LD50	> 5000	mg/kg
VAPOURS	RAT	8H LC50	> 5000	mg/m3

**HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%).**

DERMAL	RAT	LD50	>3400	mg/kg
ORAL	RAT	LD50	>15000	mg/kg
VAPOURS	RAT	LD50	>13100	mg/m3

**XYLENE**

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

**2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT**

DERMAL	RAT	LD50	2000	mg/kg
ORAL	RAT	LD50	2043-5000	mg/kg
VAPOURS	RAT	8H LC50	110	mg/m3

**2-BUTANONE OXIME**

ORL	MUS	LD50	1	gm/kg
ORL	RAT	LD50	930	mg/kg
SCU	RAT	LD50	2702	mg/kg

**Relevant hazards for product:**

Hazard	Route	Basis
STOT-single exposure	-	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

[cont...]

# SAFETY DATA SHEET

POLYURETHANE VARNISH - GLOSS

Page: 8

## Section 12: Ecological information

### 12.1. Toxicity

**Hazardous ingredients:**

#### HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

ALGAE	72H EbL50	>1000	mg/l
ALGAE	72H ErL50	>1000	mg/l
Daphnia magna	48H EL50	>1000	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LL50	>1000	mg/l

#### 2-ETHYLHEXANOIC ACID, ZIRCONIUM SALT

ALGAE	96H EC10	32	mg/l
DAPHNIA	48H EC50	62.5	mg/l
FISH	96H LC50	100	mg/l

#### 2-BUTANONE OXIME

ALGAE	72H IC50	83	mg/l
DAPHNIA	48H EC50	750	mg/l
FISH	48H LC50	560	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

[cont...]



# SAFETY DATA SHEET

POLYURETHANE VARNISH - GLOSS

Page: 9

## 14.1. UN number

UN number: UN1263

## 14.2. UN proper shipping name

Shipping name: PAINT  
(CONTAINS; HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS; HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%).)

## 14.3. Transport hazard class(es)

Transport class: 3

## 14.4. Packing group

Packing group: III

## 14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

## 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.  
EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.  
H226: Flammable liquid and vapour.  
H304: May be fatal if swallowed and enters airways.  
H312: Harmful in contact with skin.  
H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H318: Causes serious eye damage.

[cont...]

# SAFETY DATA SHEET

## POLYURETHANE VARNISH - GLOSS

Page: 10

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H361: Suspected of damaging fertility or the unborn child <state specific effect if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H372: Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.