

SAFETY DATA SHEET Holts Brake Cleaner

SECTION 1: Identification of the	ne substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	Holts Brake Cleaner
Product number	52460600131, 72460500136, HMTN0101A, PRO25A, 52460601131, 52460602131
Synonyms; trade names	PRO25A
REACH registration notes	This is a MIXTURE; no registration information contained in this document . Holts are classed as Downstream User.
1.2. Relevant identified uses o	f the substance or mixture and uses advised against
Identified uses	Car maintenance product. Cleaning agent.
1.3. Details of the supplier of the supplier of the supplier of the supplier of the supplication of the su	ne safety data sheet
Supplier	A Holts Car Care Product Holt Lloyd International Ltd Barton Dock Road Stretford Manchester M32 0YQ - England, UK +44 (0) 161 866 4800 FAX +44 (0) 161 866 4854 www.holtsauto.com
Contact person	Regulatory Affairs, Contact Email address: info@holtsauto.com
1.4. Emergency telephone nur	nber
Emergency telephone	UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs Out of office hours Tel: 020 7358 9167
National emergency telephone number	https://poisoncentres.echa.europa.eu/
SECTION 2: Hazards identifica	ation
2.1. Classification of the subst	ance or mixture
Classification (EC 1272/2008)	
Physical hazards	Aerosol 1 - H222, H229
Health hazards	Skin Irrit. 2 - H315 STOT SE 3 - H336
Environmental hazards	Aquatic Chronic 2 - H411
Classification (67/548/EEC or 1999/45/EC)	Xi;R38. F+;R12. N;R51/53. R67.

2.2. Label elements

Pi	icto	a	ra	m
	ICIC	U	a	111



Signal word	Danger
Hazard statements	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	 P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing spray. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/ container in accordance with local regulations.
Contains	Naphtha (petroleum), hydrotreated light
Supplementary precautionary statements	 P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/ doctor if you feel unwell. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Naphtha (petroleum), hydrotreated light		60-100%
CAS number: 64742-49-0	EC number: 265-151-9	
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	Xn;R65. Xi;R38. F;R11. N;R51/53. R67.	
Skin Irrit. 2 - H315		
STOT SE 3 - H336		
Asp. Tox. 1 - H304		
Aquatic Chronic 2 - H411		

BUTANE	5-10%	
CAS number: 106-97-8	EC number: 203-448-7	
Classification Flam. Gas 1 - H220 Press. Gas	Classification (67/548/EEC or 1999/45/EC) F+;R12	
ISOBUTANE	1-5%	
CAS number: 75-28-5	EC number: 200-857-2	
Classification Flam. Gas 1 - H220 Press. Gas	Classification (67/548/EEC or 1999/45/EC) F+;R12	
The Full Text for all R-Phrases	s and Hazard Statements are Displayed in Section 16.	
SECTION 4: First aid measure	es	
4.1. Description of first aid me	asures	
Inhalation	Move affected person to fresh air at once. Keep affected person warm and at rest. Get medical attention immediately.	
Ingestion	Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Do not induce vomiting. Never give anything by mouth to an unconscious person. Do not induce vomiting.	
Skin contact	Remove affected person from source of contamination. Get medical attention if any discomfor continues.	
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.	
4.2. Most important symptoms	and effects, both acute and delayed	
4.3. Indication of any immedia	te medical attention and special treatment needed	
SECTION 5: Firefighting meas	sures	
5.1. Extinguishing media		
Suitable extinguishing media	Use fire-extinguishing media suitable for the surrounding fire.	
5.2. Special hazards arising fr	om the substance or mixture	
Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.	
5.3. Advice for firefighters Protective actions during firefighting	Move containers from fire area if it can be done without risk.	

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Methods for cleaning upWear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,
clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames
or other sources of ignition near spillage. Provide adequate ventilation.

6.4. Reference to other sections

SECTION 7: Handling and st	SECTION 7: Handling and storage		
7.1. Precautions for safe han	dling		
Usage precautions	Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.		
7.2. Conditions for safe stora	ge, including any incompatibilities		
Storage precautions	Protect containers from damage.		
Storage class	Flammable compressed gas storage.		
7.3. Specific end use(s)			
SECTION 8: Exposure Contr	ols/personal protection		
8.1. Control parameters			
Occupational exposure limits			
BUTANE			

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³ Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

ISOBUTANE

Long-term exposure limit (8-hour TWA): OES 800 ppm Short-term exposure limit (15-minute): OES 800 ppm WEL = Workplace Exposure Limit

NON HAZARDOUS INGREDIENTS

Ingredient comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

ιŋ)
N. N.

Eye/face protection	The following protection should be worn: Chemical splash goggles.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. EN374 It is recommended that gloves are made of the following material: Rubber (natural, latex).
Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
Hygiene measures	Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Do not smoke in work area.
Respiratory protection	No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance

Aerosol.

Colour	Colourless.
Odour	aromatic hydrocarbons
Initial boiling point and range	63° - 100°C @
Flash point	<1C°C
Relative density	0.672 @ °C
Auto-ignition temperature	200°C
Viscosity	0.44mm² @ 40°C
9.2. Other information	
Volatile organic compound	This product contains a maximum VOC content of 97 %.
SECTION 10: Stability and rea	activity
10.1. Reactivity10.2. Chemical stability10.3. Possibility of hazardous10.4. Conditions to avoid	reactions
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalis.
10.5. Incompatible materials 10.6. Hazardous decomposition	on products
Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Thermal decomposition or combustion products may include the following substances: Acrid smoke or fumes. Carbon dioxide (CO2). Carbon monoxide (CO).
SECTION 11: Toxicological in	formation
11.1. Information on toxicolog	ical effects
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea. Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations. May cause eye and respiratory system irritation. Symptoms following overexposure may include the following: Headache.
Ingestion	May cause chemical burns in mouth, oesophagus and stomach. Harmful: may cause lung damage if swallowed.
Skin contact	Irritating to skin. Prolonged or repeated exposure may cause severe irritation.
Eye contact	Vapour or spray in the eyes may cause irritation and smarting.
Route of entry	Inhalation Skin and/or eye contact
SECTION 12: Ecological Infor	mation
Ecotoxicity	Dangerous for the environment. May cause long-term adverse effects in the aquatic

12.1. Toxicity

- 12.2. Persistence and degradability
- 12.3. Bioaccumulative potential
- 12.4. Mobility in soil

may cause long-term adverse effects in the aquatic environment.

environment. The product contains a substance which is toxic to aquatic organisms and which

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects	
SECTION 13: Disposal conside	erations
13.1. Waste treatment method	S
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Empty containers must not be punctured or incinerated because of the risk of an explosion. Avoid the spillage or runoff entering drains, sewers or watercourses. Toxic to aquatic organisms.
Waste class	WGK : 3 (Germany)
SECTION 14: Transport inform	ation
14.1. UN number	
UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950
14.2. UN proper shipping name	<u>e</u>
Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS (CONTAINS Naphtha (petroleum), hydrotreated light)
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS
14.3. Transport hazard class(e	<u>is)</u>
ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1
Transport labels	

14.4. Packing group		
ADR/RID packing group	None	
IMDG packing group	None	
ADN packing group	None	
ICAO packing group	None	
14.5. Environmental hazards		

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-D, S-U

ADR transport category

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

2

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009
-	No. 716).
	The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).
EU legislation	Dangerous Substances Directive 67/548/EEC.
	Dangerous Preparations Directive 1999/45/EC.
	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18
	December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of
	Chemicals (REACH) (as amended).
	Detergents Regulation EC 648/2004
	Commission Directive 91/322/EEC of 29 May 1991 on establishing indicative limit values by
	implementing Council Directive 80/1107/EEC on the protection of workers from the risks related to exposure to chemical, physical and biological agents at work. Aerosol Dispensers Directive 2008/47/EC (2008/47/EC)

15.2. Chemical safety assessment

SECTION 16: Other information		
Revision date	06/01/2016	
Revision	14	
Supersedes date	09/12/2014	
SDS number	12870	
Risk phrases in full	 R11 Highly flammable. R12 Extremely flammable. R38 Irritating to skin. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R67 Vapours may cause drowsiness and dizziness. 	

Hazard statements in full	H220 Extremely flammable gas.
	H222 Extremely flammable aerosol.
	H225 Highly flammable liquid and vapour.
	H229 Pressurised container: may burst if heated
	H304 May be fatal if swallowed and enters airways.
	H315 Causes skin irritation.
	H336 May cause drowsiness or dizziness.
	H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.