

EVO-STIK CARPET ADHESIVE
 Supersedes Date: 01-Nov-2017

Revision Date 01-Nov-2017
 Version 1

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
1.1. Product Identifier

Product Name EVO-STIK CARPET ADHESIVE
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives, sealants.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet
Company Name

Bostik Limited
 Common Rd
 ST16 3EH
 Stafford UK
 Tel: +44 (1785) 27 26 25
 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom	+44 (1785) 272650
Ireland	+353 (1) 8624900 (Monday- Friday 9am-5pm)

Section 2: HAZARD IDENTIFICATION
2.1. Classification of the substance or mixture
Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aspiration toxicity	Category 1 - (H304)
Skin Corrosion/Irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Chronic aquatic toxicity	Category 3 - (H412)
Aerosols	Category 1 - (H222)

2.2. Label Elements
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Hydrocarbons, C6, isoalkanes, <5% n-hexane, Acetone



Safety Data Sheet

EVO-STIK CARPET ADHESIVE
Supersedes Date: 01-Nov-2017

Revision Date 01-Nov-2017
Version 1

Signal Word
DANGER

Hazard statements

H319 - Causes serious eye irritation
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H412 - Harmful to aquatic life with long lasting effects
H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P103 - Read label before use
P211 - Do not spray on an open flame or other ignition source
P251 - Do not pierce or burn, even after use
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires child resistant fastenings if supplied to the general public
This product requires child resistant fastenings when supplied to the general public unless the product is placed on the market in the form of aerosols or in a container with a sealed spray attachment

2.3. Other Hazards

General Hazards

No information available.

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Mixture

3.2 Mixtures

Chemical Name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	270-704-2	68476-85-7	>25 - <40	Flam. Gas 1 (H220) Press. Gas		No data available
Acetone	200-662-2	67-64-1	15 - 25	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)		01-2119471330-49 -XXXX
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	--	10 - <20	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315)		01-2119475515-33 -xxxx

Safety Data Sheet

EVO-STIK CARPET ADHESIVE
Supersedes Date: 01-Nov-2017

Revision Date 01-Nov-2017
Version 1

				Aquatic Chronic 2 (H411)		
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9	--	5 - <10	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225) (EUH066)		01-2119484651-34-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL.

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Section 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	Immediate medical attention is required. In case of accident or being unwell, seek medical advice immediately (show directions for use or safety data sheet if possible). If symptoms persist, call a doctor.
Inhalation	Remove to fresh air. Call a doctor. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapours. If symptoms persist, call a doctor.
Skin Contact	Wash off immediately with plenty of water. Wash contaminated clothing before reuse. If skin irritation persists, call a doctor. Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a doctor.
Ingestion	Do NOT induce vomiting. Rinse mouth. Drink plenty of water. If symptoms persist, call a doctor. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Call a doctor.
Self-Protection of the First Aider	Remove all sources of ignition. Use personal protective equipment as required.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Keep victim warm and quiet. Treat symptomatically.

Section 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing agent suitable for type of surrounding fire. Dry chemical or CO₂. Water spray, fog or regular foam. Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.

Safety Data Sheet

EVO-STIK CARPET ADHESIVE
Supercedes Date: 01-Nov-2017

Revision Date 01-Nov-2017
Version 1

Unsuitable Extinguishing Media

No information available

5.2. Special hazards arising from the substance or mixture

Some may burn but none ignite readily. Ruptured cylinders may rocket. EXTREMELY FLAMMABLE.

5.3. Advice for firefighters

Caution! Container under pressure. Heating causes rise in pressure with risk of bursting. Cool container with water spray. In the event of fire and/or explosion do not breathe fumes.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal Precautions

Ensure adequate ventilation, especially in confined areas. Remove all sources of ignition. Evacuate personnel to safe areas. Use personal protective equipment as required. Keep people away from and upwind of spill/leak.

Ventilate the area.

For emergency responders

Use personal protection recommended in Section 8.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Methods for Containment

If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.

Methods for cleaning up

Pick up and transfer to properly labelled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert absorbent material.

6.4. Reference to other sections

Reference to other sections

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION
Section 13: DISPOSAL CONSIDERATIONS

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Advice on safe handling

Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Use with local exhaust ventilation. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapours/spray.

General Hygiene Considerations

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep tightly closed in a dry and cool place. Keep in properly labelled containers. Keep away from heat, sparks, flame and other

Safety Data Sheet

EVO-STIK CARPET ADHESIVE
Supersedes Date: 01-Nov-2017

Revision Date 01-Nov-2017
Version 1

sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

OTHER INFORMATION

Recommendation(s). Observe technical data sheet.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Chemical Name	European Union	Ireland	United Kingdom
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene 68476-85-7	-	TWA: 1000 ppm TWA: 1800 mg/m ³ STEL: 2250 mg/m ³ STEL: 1250 ppm	STEL: 1250 ppm STEL: 2180 mg/m ³ TWA: 1000 ppm TWA: 1750 mg/m ³
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3630 mg/m ³	STEL: 1500 ppm STEL: 3620 mg/m ³ TWA: 500 ppm TWA: 1210 mg/m ³

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering Controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/Face Protection Tight sealing safety goggles. Face protection shield.
Skin and Body Protection Antistatic footwear. Wear fire/flame resistant/retardant clothing. Gloves made of plastic or rubber. Suitable protective clothing.

Environmental Exposure Controls Do not allow into any sewer, on the ground or into any body of water.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State Aerosol
Appearance Aerosol
Colour No information available
Odour No information available
Odour Threshold No information available

Property	Values	Remarks • Method
pH	No information available	
Melting point / freezing point	No information available	
Boiling Point	= -40 °C / -40 °F	
Flash Point	< -60 °C / < -76 °F	
Evaporation Rate	No information available	
Flammability (solid, gas)	No information available	Not applicable for liquids
Flammability Limit in Air		
Upper Flammability Limit	No information available	
Lower Flammability Limit	No information available	
Vapour Pressure	No information available	
Vapour Density	No information available	
Relative Density	No information available	
Water Solubility	No information available	

Safety Data Sheet

EVO-STIK CARPET ADHESIVE
Supersedes Date: 01-Nov-2017

Revision Date 01-Nov-2017
Version 1

Solubility in Other Solvents	No information available
Partition Coefficient	No information available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Explosive Properties	No information available
Explosive Limits	No information available
Upper	No information available
Lower	No information available
Oxidising Properties	No information available
Kinematic Viscosity	No information available

Dynamic Viscosity No information available

9.2. Other information

Softening Point	No information available
Molecular Weight	No information available
Solvent content (%)	No information available
Solid content (%)	No information available
Density	No data available
Bulk Density	No data available
VOC content (%)	No data available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

None under normal use conditions.

10.2. Chemical stability

Stable under normal conditions.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge May be ignited by friction, heat, sparks or flames.

10.3. Possibility of hazardous reactions

Possibility of Hazardous Reactions

None under normal processing.

10.4. Conditions to avoid

Heat, flames and sparks.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

None under normal use conditions.

Section 11: TOXICOLOGY INFORMATION

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

No information or data specific to the product on this toxicological (health) effect is available.

Safety Data Sheet

EVO-STIK CARPET ADHESIVE
Supersedes Date: 01-Nov-2017

Revision Date 01-Nov-2017
Version 1

Inhalation	No data available.
Eye contact	Severely irritating to eyes.
Skin Contact	Irritating to skin.
Ingestion	Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.
Sensitisation	No data available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin Corrosion/Irritation	Not applicable.
Serious eye damage/eye irritation	Not applicable.
Sensitisation	Not applicable.
Germ Cell Mutagenicity	Not applicable.
Carcinogenicity	Not applicable.
Reproductive Toxicity	No information available.
STOT - Single Exposure	No information available.
STOT - Repeated Exposure	No information available.
Target Organ Effects	Central nervous system, Eyes, Respiratory system, Skin.
Aspiration hazard	Risk of serious damage to the lungs (by aspiration). May be fatal if swallowed and enters airways.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document mg/kg
ATEmix (dermal) 19,392.00 mg/kg mg/l

Component Information

Toxicity Data Data obtained on the component(s) include

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	>15800 mg/Kg (rat)	= 79 mg/l(Rat) 4 h
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics --	LD50 >5840 mg/kg Rat	LD50 >2920 mg/kg (Rat)	-
Hydrocarbons, C6, isoalkanes, <5% n-hexane --	>16750 mg/Kg (rat)	>3350 mg/Kg (rabbit OECD 402)	259354 mg/m ³ (vapour) (rat OECD 403)

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects

Safety Data Sheet

EVO-STIK CARPET ADHESIVE
Supersedes Date: 01-Nov-2017

Revision Date 01-Nov-2017
Version 1

Component Information

Data obtained on the component(s) include

Chemical Name	Algae/aquatic plants	Fish	Crustacea	M-Factor
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics --	-	-	EL50 (48h) =3mg/L Daphnia	
Hydrocarbons, C6, isoalkanes, <5% n-hexane --	13.6 mg/l (Pseudokirchneriella subcapitata)	18.3 mg/l (Oncorhynchus mykiss)	31.9 mg/l (Daphnia magna)	

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Partition coefficient No information available

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

No information available

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors.

Section 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Improper disposal or reuse of this container may be dangerous and illegal.

OTHER INFORMATION Waste codes should be assigned by the user based on the application for which the product was used.

Section 14: TRANSPORTATION INFORMATION

ADR

14.1 UN/ID no UN1950
14.2 Proper Shipping Name Aerosols
14.3 Hazard Class 2

Safety Data Sheet

EVO-STIK CARPET ADHESIVE
Supersedes Date: 01-Nov-2017

Revision Date 01-Nov-2017
Version 1

Hazard Labels	2.1
14.4 Packing Group	Not regulated
Description	UN1950, Aerosols, 2, (D)
14.5 Environmental Hazard	Not applicable
14.6 Special Provisions	190, 327, 344, 625
Classification Code	5F
Tunnel restriction code	(D)
Limited Quantity (LQ)	1 L

IMDG

14.1 UN/ID no	UN1950
14.2 Proper Shipping Name	Aerosols
14.3 Hazard Class	2.1
14.4 Packing Group	Not regulated
Description	UN1950, Aerosols, 2.1
14.5 Marine Pollutant	Np
14.6 Special Provisions	63,190, 277, 327, 344, 381, 959
Limited Quantity (LQ)	See SP277
EmS-No	F-D, S-U
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	No information available

RID

14.1 UN/ID no	UN1950
14.2 Proper Shipping Name	Aerosols
14.3 Hazard Class	2
Hazard Labels	2.1
14.4 Packing Group	Not regulated
Description	UN1950, Aerosols, 2
14.5 Environmental Hazard	Not applicable
Classification Code	5F
14.6 Special Provisions	190, 327, 344, 625
Limited Quantity (LQ)	1 L

ICAO (air)

14.1 UN/ID no	UN1950
14.2 Proper Shipping Name	Aerosols
14.3 Hazard Class	2.1
14.4 Packing Group	Not regulated
Description	UN1950, Aerosols, 2.1
14.5 Environmental Hazard	Not applicable
14.6 Special Provisions	A145, A167

IATA

14.1 UN/ID no	UN1950
14.2 Proper Shipping Name	Aerosols, flammable
14.3 Hazard Class	2.1
14.4 Packing Group	Not regulated
Description	UN1950, Aerosols, flammable, 2.1
14.5 Environmental Hazard	Not applicable
14.6 Special Provisions	A145, A167, A802
Limited Quantity (LQ)	30 kg G
ERG Code	10L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Safety Data Sheet

EVO-STIK CARPET ADHESIVE
Supercedes Date: 01-Nov-2017

Revision Date 01-Nov-2017
Version 1

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical Name	CAS No	Restrictions on use
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene	68476-85-7	28. 29.

EU-REACH (1907/2006) - Annex XIV - List of substances subject to Authorization

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

Chemical Name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Petroleum gases, liquefied <0.1% w/w 1,3 Butadiene - 68476-85-7	50	200

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

15.2. Chemical safety assessment

None

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H225 - Highly flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H411 - Toxic to aquatic life with long lasting effects
EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

SVHC: Substances of Very High Concern for Authorisation:

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)
Ceiling Maximum limit value * Skin designation

Safety Data Sheet

EVO-STIK CARPET ADHESIVE
Supersedes Date: 01-Nov-2017

Revision Date 01-Nov-2017
Version 1

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
STOT (RE): Specific target organ toxicity - Repeated exposure
STOT (SE): Specific target organ toxicity - Single exposure
EWC: European Waste Catalogue

Key literature references and sources for data

Classification and labeling data calculated from data received from raw material suppliers

Prepared By Product Safety & Regulatory Affairs

Revision Date 01-Nov-2017

Indication of changes

Revision Note Not applicable.

Training Advice No information available

Additional information No information available

This safety data sheet complies with the requirements of: Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet