



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 16

Loctite Super Glue Liquid

SDS No. : 209260
V004.1

Revision: 20.03.2019

printing date: 22.05.2019

Replaces version from: 13.01.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Loctite Super Glue Liquid

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Super glue

ua-productsafety.uk@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

| | |
|--|------------|
| Skin irritation H315 Causes skin irritation. | Category 2 |
| Serious eye irritation H319 Causes serious eye irritation. | Category 2 |
| Specific target organ toxicity - single exposure H335 May cause respiratory irritation. Target organ: respiratory tract irritation | Category 3 |

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

Ethyl 2-cyanoacrylate

Signal word:

Warning

Hazard statement:

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Supplemental information EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

Precautionary statement: P261 Avoid breathing vapors.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.

Precautionary statement: P501 Dispose of contents/container in accordance with national regulation.
Disposal

2.3. Other hazards

Persons suffering from allergic reactions to acrylates should avoid contact with the product.
 Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description:
 Cyanoacrylate Adhesive

Base substances of preparation:
 Cyanoacrylate

Declaration of the ingredients according to CLP (EC) No 1272/2008:

| Hazardous components CAS-No. | EC Number REACH-Reg No. | content | Classification |
|---|-------------------------------|---------------|--|
| Ethyl 2-cyanoacrylate 7085-85-0 | 230-391-5 01-2119527766-29 | 60- < 100 % | Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315 |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | 204-327-1 01-2119496065-33 | 0,1- < 1 % | Repr. 2 H361 |
| Hydroquinone 123-31-9 | 204-617-8 01-2119524016-51 | 0,01- < 0,1 % | Aquatic Acute 1 H400 Aquatic Chronic 1 H410 Carc. 2 H351 Muta. 2 H341 Acute Tox. 4; Oral H302 Eye Dam. 1 H318 Skin Sens. 1 H317 M factor (Acute Aquat Tox): 10 |

**For full text of the H - statements and other abbreviations see section 16 "Other information".
 Substances without classification may have community workplace exposure limits available.**

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:
 In case of adverse health effects seek medical advice.

Inhalation:
 Move to fresh air, consult doctor if complaint persists.

Skin contact:

Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a spoon, preferably after soaking in warm soapy water.

Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate enough heat to cause a burn.

Burns should be treated normally after the adhesive has been removed from the skin.

If lips are accidentally stuck together apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth.

Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action.

Eye contact:

If the eye is bonded closed, release eyelashes with warm water by covering with wet pad.

Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help to debond the adhesive.

Keep eye covered until debonding is complete, usually within 1-3 days.

Do not force eye open. Medical advice should be sought in case solid particles of cyanoacrylate trapped behind the eyelid cause any abrasive damage.

Ingestion:

Ensure that breathing passages are not obstructed. The product will polymerise immediately in the mouth making it almost impossible to swallow. Saliva will slowly separate the solidified product from the mouth (several hours).

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Redness, inflammation.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

carbon dioxide, foam, powder, water spray jet, fine water spray

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO₂) can be released.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

Danger of slipping on spilled product.

Ensure adequate ventilation.

Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Open and handle container with care.
 Ensure that workrooms are adequately ventilated.
 Avoid skin and eye contact.

Hygiene measures:

Do not eat, drink or smoke while working.
 Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

For optimum shelf life store in original containers under refrigerated conditions at 2 - 8°C (35.6 - 46.4 °F)
 Store in a cool place, max. storage temperature 30°C.
 Store in a dry place.
 Keep container tightly sealed and store in a frost free place.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s)

Super glue

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
 Great Britain

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|-----------------------------------|--|-----------------|
| Ethyl 2-cyanoacrylate 7085-85-0 [ETHYL CYANOACRYLATE] | 0,3 | 1,5 | Short Term Exposure Limit (STEL): | | EH40 WEL |
| Hydroquinone 123-31-9 [HYDROQUINONE] | | 0,5 | Time Weighted Average (TWA): | | EH40 WEL |

Occupational Exposure Limits

Valid for
 Ireland

| Ingredient [Regulated substance] | ppm | mg/m ³ | Value type | Short term exposure limit category / Remarks | Regulatory list |
|---|-----|-------------------|------------------------------|--|-----------------|
| Ethyl 2-cyanoacrylate 7085-85-0 [ETHYL CYANOACRYLATE] | 0,2 | | Time Weighted Average (TWA): | | IR_OEL |
| Hydroquinone 123-31-9 [HYDROQUINONE] | | 0,5 | Time Weighted Average (TWA): | | IR_OEL |

Predicted No-Effect Concentration (PNEC):

| Name on list | Environmental Compartment | Exposure period | Value | | | | Remarks |
|---|------------------------------|-----------------|---------------|-----|---------------|--------|---------|
| | | | mg/l | ppm | mg/kg | others | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | aqua (freshwater) | | 0,0068 mg/l | | | | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | aqua (marine water) | | 0,00068 mg/l | | | | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | aqua (intermittent releases) | | 0,048 mg/l | | | | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | sewage treatment plant (STP) | | 100 mg/l | | | | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | sediment (freshwater) | | | | 102 mg/kg | | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | sediment (marine water) | | | | 10,2 mg/kg | | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | Soil | | | | 20,4 mg/kg | | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | oral | | | | 10 mg/kg | | |
| Hydroquinone 123-31-9 | aqua (freshwater) | | 0,00057 mg/l | | | | |
| Hydroquinone 123-31-9 | aqua (marine water) | | 0,000057 mg/l | | | | |
| Hydroquinone 123-31-9 | sediment (freshwater) | | | | 0,0049 mg/kg | | |
| Hydroquinone 123-31-9 | sediment (marine water) | | | | 0,00049 mg/kg | | |
| Hydroquinone 123-31-9 | aqua (intermittent releases) | | 0,00134 mg/l | | | | |
| Hydroquinone 123-31-9 | Soil | | | | 0,00064 mg/kg | | |
| Hydroquinone 123-31-9 | sewage treatment plant (STP) | | 0,71 mg/l | | | | |

Derived No-Effect Level (DNEL):

| Name on list | Application Area | Route of Exposure | Health Effect | Exposure Time | Value | Remarks |
|--|--------------------|-------------------|--|---------------|------------------------|---------|
| Ethyl 2-cyanoacrylate 7085-85-0 | Workers | Inhalation | Long term exposure - local effects | | 9,25 mg/m ³ | |
| Ethyl 2-cyanoacrylate 7085-85-0 | Workers | Inhalation | Long term exposure - systemic effects | | 9,25 mg/m ³ | |
| Ethyl 2-cyanoacrylate 7085-85-0 | General population | Inhalation | Long term exposure - local effects | | 9,25 mg/m ³ | |
| Ethyl 2-cyanoacrylate 7085-85-0 | General population | Inhalation | Long term exposure - systemic effects | | 9,25 mg/m ³ | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | Workers | dermal | Acute/short term exposure - systemic effects | | 3,175 mg/kg | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | Workers | Inhalation | Acute/short term exposure - systemic effects | | 22,4 mg/m ³ | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | Workers | dermal | Long term exposure - systemic effects | | 0,635 mg/kg | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | Workers | Inhalation | Long term exposure - systemic effects | | 4,48 mg/m ³ | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | General population | dermal | Acute/short term exposure - systemic effects | | 1,59 mg/kg | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | General population | Inhalation | Acute/short term exposure - systemic effects | | 5,5 mg/m ³ | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | General population | oral | Acute/short term exposure - systemic effects | | 1,59 mg/kg | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | General population | dermal | Long term exposure - systemic effects | | 0,318 mg/kg | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | General population | Inhalation | Long term exposure - systemic effects | | 1,1 mg/m ³ | |
| 6,6'-di-tert-Butyl-2,2'-methylenedi-p-cresol 119-47-1 | General population | oral | Long term exposure - systemic effects | | 0,318 mg/kg | |
| Hydroquinone 123-31-9 | Workers | dermal | Long term exposure - systemic effects | | 3,33 mg/kg | |
| Hydroquinone 123-31-9 | Workers | inhalation | Long term exposure - systemic effects | | 2,1 mg/m ³ | |
| Hydroquinone 123-31-9 | General population | dermal | Long term exposure - systemic effects | | 1,66 mg/kg | |
| Hydroquinone 123-31-9 | General population | inhalation | Long term exposure - systemic effects | | 1,05 mg/m ³ | |
| Hydroquinone 123-31-9 | General population | oral | Long term exposure - systemic effects | | 0,6 mg/kg | |

Biological Exposure Indices:

None

8.2. Exposure controls:

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.

Combination filter: ABEKP (EN 14387)

This recommendation should be matched to local conditions.

Hand protection:

Recommended are gloves made from Nitril rubber (Material thickness >0,1 mm, Perforation time < 30s).Gloves should be replaced after each short time contact or contamination. Available at laboratory specialized trade or at pharmacies / chemist's shops.

In the case of longer contact protective gloves made from nitrile rubber are recommended according to EN 374. material thickness > 0.4 mm

Perforation time > 30 minutes

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

| | |
|---|------------------------------------|
| Appearance | liquid transparent Straw |
| Odour threshold | No data available / Not applicable |
| pH | No data available / Not applicable |
| Melting point | No data available / Not applicable |
| Solidification temperature | No data available / Not applicable |
| Initial boiling point | No data available / Not applicable |
| Flash point | 80 - 93 °C (176 - 199.4 °F) |
| Evaporation rate | No data available / Not applicable |
| Flammability | No data available / Not applicable |
| Explosive limits | No data available / Not applicable |
| Vapour pressure | No data available / Not applicable |
| Relative vapour density: | No data available / Not applicable |
| Density (20 °C (68 °F)) | 1,05 g/cm ³ |
| Bulk density | No data available / Not applicable |
| Solubility | No data available / Not applicable |
| Solubility (qualitative) (20 °C (68 °F); Solvent: Water) | Insoluble |
| Solubility (qualitative) (Solvent: Acetone) | Soluble |
| Partition coefficient: n-octanol/water | No data available / Not applicable |
| Auto-ignition temperature | No data available / Not applicable |
| Decomposition temperature | No data available / Not applicable |
| Viscosity (; 40 °C (104 °F)) | 30,0 - 50,0 mPa.s |
| Viscosity (kinematic) | No data available / Not applicable |
| Explosive properties | No data available / Not applicable |
| Oxidising properties | No data available / Not applicable |

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

General toxicological information:

Persons suffering from allergic reactions to acrylates should avoid contact with the product.

11.1. Information on toxicological effects

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|---------------|----------------|---------|--|
| Ethyl 2-cyanoacrylate 7085-85-0 | LD50 | > 5.000 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | LD50 | > 10.000 mg/kg | rat | not specified |
| Hydroquinone 123-31-9 | LD50 | 367 mg/kg | rat | OECD Guideline 401 (Acute Oral Toxicity) |

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Species | Method |
|---|---------------|----------------|---------|--|
| Ethyl 2-cyanoacrylate 7085-85-0 | LD50 | > 2.000 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | LD50 | > 10.000 mg/kg | rat | not specified |
| Hydroquinone 123-31-9 | LD50 | > 2.000 mg/kg | rabbit | OECD Guideline 402 (Acute Dermal Toxicity) |

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

Bonds skin in seconds. Considered to be of low toxicity: acute dermal LD50 (rabbit)>2000mg/kg
Due to polymerisation at the skin surface allergic reaction is unlikely to occur

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|------------------------------------|------------------------|------------------|---------|--|
| Ethyl 2-cyanoacrylate 7085-85-0 | slightly irritating | 24 h | rabbit | OECD Guideline 404 (Acute Dermal Irritation / Corrosion) |
| Hydroquinone 123-31-9 | not irritating | 24 h | rabbit | Weight of evidence |

Serious eye damage/irritation:

Liquid product will bond eyelids. In a dry atmosphere (RH<50%) vapours may cause irritation and lachrymatory effect

| Hazardous substances CAS-No. | Result | Exposure time | Species | Method |
|------------------------------------|------------|------------------|---------|---|
| Ethyl 2-cyanoacrylate 7085-85-0 | irritating | 72 h | rabbit | OECD Guideline 405 (Acute Eye Irritation / Corrosion) |

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Test type | Species | Method |
|------------------------------------|-----------------|---------------------------------------|------------|--|
| Ethyl 2-cyanoacrylate 7085-85-0 | not sensitising | | guinea pig | not specified |
| Hydroquinone 123-31-9 | sensitising | Guinea pig maximisation test | guinea pig | equivalent or similar to OECD Guideline 406 (Skin Sensitisation) |
| Hydroquinone 123-31-9 | sensitising | Mouse local lymphnode assay (LLNA) | mouse | equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay) |

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result | Type of study / Route of administration | Metabolic activation / Exposure time | Species | Method |
|--|----------|--|--------------------------------------|---------|---|
| Ethyl 2-cyanoacrylate 7085-85-0 | negative | bacterial reverse mutation assay (e.g Ames test) | | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Ethyl 2-cyanoacrylate 7085-85-0 | negative | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Ethyl 2-cyanoacrylate 7085-85-0 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Hydroquinone 123-31-9 | negative | bacterial reverse mutation assay (e.g Ames test) | with and without | | equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay) |
| Hydroquinone 123-31-9 | negative | in vitro mammalian chromosome aberration test | with and without | | OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) |
| Hydroquinone 123-31-9 | positive | mammalian cell gene mutation assay | with and without | | OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) |
| Hydroquinone 123-31-9 | positive | intraperitoneal | | mouse | equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test) |
| Hydroquinone 123-31-9 | negative | oral: gavage | | rat | equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test) |
| Hydroquinone 123-31-9 | positive | intraperitoneal | | mouse | equivalent or similar to OECD Guideline 483 (Mammalian Spermatogonial Chromosome Aberration Test) |

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous components CAS-No. | Result | Route of application | Exposure time / Frequency of treatment | Species | Sex | Method |
|------------------------------|--------------|----------------------|--|---------|-------------|--|
| Hydroquinone 123-31-9 | carcinogenic | oral: gavage | 103 w 5 d/w | rat | male/female | equivalent or similar OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies) |
| Hydroquinone 123-31-9 | carcinogenic | oral: gavage | 103 w 5 d/w | mouse | female | equivalent or similar OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies) |

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Test type | Route of application | Species | Method |
|--|--|----------------------|----------------------|---------|---|
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | NOAEL P 12,5 mg/kg | screening | oral: gavage | rat | OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test) |
| Hydroquinone 123-31-9 | NOAEL P 15 mg/kg NOAEL F1 150 mg/kg NOAEL F2 150 mg/kg | Two generation study | oral: gavage | rat | EPA OTS 798.4700 (Reproduction and Fertility Effects) |

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Result / Value | Route of application | Exposure time / Frequency of treatment | Species | Method |
|------------------------------|------------------|----------------------|--|---------|--|
| Hydroquinone 123-31-9 | NOAEL 50 mg/kg | oral: gavage | 13 w 5 d/w | rat | not specified |
| Hydroquinone 123-31-9 | NOAEL 73,9 mg/kg | dermal | 13 w 6 h/d, 5 d/w | rat | equivalent or similar to OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study) |

Aspiration hazard:

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|------------|---------------|---------------------|--|
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | LC50 | | | Oryzias latipes | OECD Guideline 203 (Fish, Acute Toxicity Test) |
| Hydroquinone 123-31-9 | LC50 | 0,638 mg/l | 96 h | Oncorhynchus mykiss | OECD Guideline 203 (Fish, Acute Toxicity Test) |

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|------------|---------------|---------------|--|
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | EC50 | | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |
| Hydroquinone 123-31-9 | EC50 | 0,134 mg/l | 48 h | Daphnia magna | OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test) |

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|---------------|-------------|---------------|---------------|---|
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | NOEC | | | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |
| Hydroquinone 123-31-9 | NOEC | 0,0057 mg/l | 21 d | Daphnia magna | OECD 211 (Daphnia magna, Reproduction Test) |

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|------------|------------|---------------|---|---|
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | EC50 | | 72 h | Pseudokirchneriella subcapitata (reported as Selenastrum capricornutum) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | NOEC | | 72 h | Pseudokirchneriella subcapitata (reported as Selenastrum capricornutum) | OECD Guideline 201 (Alga, Growth Inhibition Test) |
| Hydroquinone 123-31-9 | EC50 | 0,335 mg/l | 72 h | Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata) | OECD Guideline 201 (Alga, Growth Inhibition Test) |

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

| Hazardous substances CAS-No. | Value type | Value | Exposure time | Species | Method |
|---|------------|---------------|---------------|---------|--|
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | EC 50 | > 10.000 mg/l | 3 h | | OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test) |
| Hydroquinone 123-31-9 | EC 50 | 0,038 mg/l | 30 min | | not specified |

12.2. Persistence and degradability

| Hazardous substances CAS-No. | Result | Test type | Degradability | Exposure time | Method |
|---|--|-----------|---------------|---------------|--|
| Ethyl 2-cyanoacrylate 7085-85-0 | not readily biodegradable. | aerobic | 57 % | 28 d | OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test) |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | under test conditions no biodegradation observed | aerobic | 0 % | 28 d | OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I)) |
| Hydroquinone 123-31-9 | readily biodegradable | aerobic | 75 - 81 % | 30 d | EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test) |

12.3. Bioaccumulative potential

| Hazardous substances CAS-No. | Bioconcentration factor (BCF) | Exposure time | Temperature | Species | Method |
|---|-------------------------------|---------------|-------------|-----------------|--|
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | 320 - 780 | 60 d | | Cyprinus carpio | OECD Guideline 305 E (Bioaccumulation: Flow-through Fish Test) |

12.4. Mobility in soil

| Hazardous substances CAS-No. | LogPow | Temperature | Method |
|---|--------|-------------|--|
| Ethyl 2-cyanoacrylate 7085-85-0 | 0,776 | 22 °C | EU Method A.8 (Partition Coefficient) |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | 6,25 | 20 °C | OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method) |
| Hydroquinone 123-31-9 | 0,59 | | EU Method A.8 (Partition Coefficient) |

12.5. Results of PBT and vPvB assessment

| Hazardous substances CAS-No. | PBT / vPvB |
|---|---|
| Ethyl 2-cyanoacrylate 7085-85-0 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane 119-47-1 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |
| Hydroquinone 123-31-9 | Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria. |

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

Waste code

080409

SECTION 14: Transport information

14.1. UN number

| | |
|------|---------------------|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | 3334 |

14.2. UN proper shipping name

| | |
|------|---|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | Aviation regulated liquid, n.o.s. (Cyanoacrylate ester) |

14.3. Transport hazard class(es)

| | |
|------|---------------------|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | 9 |

14.4. Packing group

| | |
|------|---------------------|
| ADR | Not dangerous goods |
| RID | Not dangerous goods |
| ADN | Not dangerous goods |
| IMDG | Not dangerous goods |
| IATA | III |

14.5. Environmental hazards

| | |
|------|----------------|
| ADR | not applicable |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | not applicable |

14.6. Special precautions for user

| | |
|------|--|
| ADR | not applicable |
| RID | not applicable |
| ADN | not applicable |
| IMDG | not applicable |
| IATA | Not more than 500 ml (each inner package) - Unrestricted |

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content 0,00 %
(VOCV 814.018 VOC regulation
CH)

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H341 Suspected of causing genetic defects.
- H351 Suspected of causing cancer.
- H361 Suspected of damaging fertility or the unborn child.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (ua-productsafety.de@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.

Annex - Exposure Scenarios:

Exposure Scenarios for ethyl 2-cyanoacrylate can be downloaded under the following link:
http://mymsds.henkel.com/mymsds/.470833..en.ANNEX_DE.15743123.0.DE.pdf
Alternatively they can be accessed on the internet site www.mymsds.henkel.com by entering number 470833.