

## Safety Data Sheet

### KERAQUICK S1

Safety Data Sheet dated 20/10/2015, version 1

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: KERAQUICK S1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Cement based powder adhesive

Uses advised against:

==

1.3. Details of the supplier of the safety data sheet

Supplier:

MAPEI U.K. Ltd - Mapei House Steel Park Road

Halesowen - West Midlands B62 8HD

Competent person responsible for the safety data sheet:

sicurezza@mapei.it

1.4. Emergency telephone number

MAPEI U.K. Ltd - phone: +44(0)121 508 6970

fax: +44(0)121 5086 960

www.mapei.co.uk (office hours)

#### SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.

⚠ Warning, Skin Sens. 1, May cause an allergic skin reaction.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Symbols:



Warning

Hazard Statements:

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

## Safety Data Sheet

### KERAQUICK S1

#### Precautionary Statements:

P261 Avoid breathing dust.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER.

#### Special Provisions:

None

#### Contents:

Portland cement, Cr(VI) < 2 ppm

#### Special provisions according to Annex XVII of REACH and subsequent amendments:

None

#### 2.3. Other hazards

vPvB Substances: None - PBT Substances: None

#### Other Hazards:

No other hazards

See at paragraph 11 the additional information concerning crystalline silica

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

N.A.

#### 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 50% - < 75% free crystalline silica ( $\text{Ø} > 10 \mu$ )

CAS: 14808-60-7, EC: 238-878-4

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

>= 1% - < 2.5% Portland cement, Cr(VI) < 2 ppm

CAS: 65997-15-1, EC: 266-043-4

⚠ 3.8/3 STOT SE 3 H335

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.3/1 Eye Dam. 1 H318

⚠ 3.4.2/1 Skin Sens. 1 H317

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### In case of skin contact:

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

##### In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

##### In case of Ingestion:

Wash the mouth thoroughly and drink plenty of water. In case of disease consult a physician immediately and present this safety-data sheet.

## Safety Data Sheet

### KERAQUICK S1

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

If brought into contact with the skin, the product may cause sensitisation of the skin.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

#### SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Carbon dioxide (CO<sub>2</sub>).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

The product does not present a fire hazard

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Rapidly recover the product, wearing protective clothing.

Scoop into containers and seal for disposal.

After the product has been recovered, rinse the area and materials involved with water.

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

#### SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes and exposure to high dust concentration.

Avoid powder development and deposit

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Fine dust may form explosive mixture with air. Keep away from open flames, heat and sparks.

Do not remove shrink film in hazardous locations (because of risk of static charging/discharge)

7.2. Conditions for safe storage, including any incompatibilities

Always keep the containers tightly closed.

## Safety Data Sheet

### KERAQUICK S1

Incompatible materials:  
Keep away from water or from damp surroundings.  
Instructions as regards storage premises:  
Adequately ventilated premises.

7.3. Specific end use(s)  
None in particular

#### SECTION 8: Exposure controls/personal protection

8.1. Control parameters

free crystalline silica ( $\text{Ø} > 10 \mu$ ) - CAS: 14808-60-7

ACGIH - LTE mg/m<sup>3</sup>(8h): 0.025 mg/m<sup>3</sup> - Notes: A2 (R) - Pulm fibrosis, lung cancer

Portland cement, Cr(VI) < 2 ppm - CAS: 65997-15-1

ACGIH - LTE mg/m<sup>3</sup>(8h): 1 mg/m<sup>3</sup> - Notes: A4, (E,R) - Pulm func, resp symptoms, asthma

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

8.2. Exposure controls

Eye protection:

Safety goggles.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Not needed for normal use.

A dust mask (P2) should be worn if above exposure limits

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

#### SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	powder
Colour:	white o grey
Odour:	slight, typical of cement
Odour threshold:	N.A.
pH:	N.A.
pH(water dispersion,10%):	12-12,5
Melting point / freezing point:	N.A.
Initial boiling point and boiling range:	N.A.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.

## Safety Data Sheet

### KERAQUICK S1

Vapour density:	N.A.
Flash point:	== °C
Evaporation rate:	N.A.
Vapour pressure:	N.A.
Relative density:	N.A.
Apparent density:	1.5 g/cm <sup>3</sup>
Vapour density (air=1):	N.A.
Solubility in water:	<5 g/l
Solubility in oil:	insoluble
Viscosity:	N.A.
Auto-ignition temperature:	== °C
Explosion limits(by volume):	==
Decomposition temperature:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Explosive properties:	==
Oxidizing properties:	N.A.

#### 9.2. Other information

Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

## SECTION 10: Stability and reactivity

- 10.1. Reactivity  
Stable under normal conditions
- 10.2. Chemical stability  
Stable under normal conditions
- 10.3. Possibility of hazardous reactions
- 10.4. Conditions to avoid  
Stable under normal conditions.
- 10.5. Incompatible materials  
None in particular.
- 10.6. Hazardous decomposition products  
None.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Route(s) of entry:

Ingestion:	Yes
Inhalation:	Yes
Contact:	No

There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

N.A.

Corrosive/Irritating Properties:

Skin:

The product can cause a temporary irritation by prolonged contact.

Eye:

The product can cause a temporary irritation by contact.

Sensitizing Properties:

Frequent contact may cause sensitization.

## Safety Data Sheet

### KERAQUICK S1

#### Carcinogenic Effects:

The IARC (International Agency for Research on Cancer) believes that the crystalline silica inhaled at the workplace can cause lung cancer in man.

However, it also points out that the cancer effect depends on the silica characteristics and on the biological-physical condition of the environment.

There is a large amount of information in support of the fact that increased risk of cancer is limited to persons suffering from silicosis.

In the current situation of studies, protection of workers from silicosis can be ensured by respecting the exposure limit values.

#### Mutagenic Effects:

No effects are known.

#### Teratogenic Effects:

No effects are known.

#### Additional Information:

Susceptibility to skin irritation and sensitization varies from person to person.

In a sensitized individual the allergic dermatitis may not appear until after several days or weeks of frequent and prolonged contact.

Therefore, even though the skin irritation potential is slight, skin contact should be avoided. Once sensitization has occurred, exposure of the skin to very small quantities of the material may cause erythema and edema.

For this reason, the contact with the skin should be avoided. Once sensitization has occurred, exposures to small amounts of material may cause erythema and edema locally.

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

## SECTION 12: Ecological information

### 12.1. Toxicity

Adopt good industrial practices, so that the product is not released into the environment.

Not available data on the mixture

Biodegradability: no data available on the preparation.

N.A.

### 12.2. Persistence and degradability

N.A.

### 12.3. Bioaccumulative potential

N.A.

### 12.4. Mobility in soil

N.A.

### 12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

### 12.6. Other adverse effects

## Safety Data Sheet

### KERAQUICK S1

Not available data on the mixture

#### SECTION 13: Disposal considerations

##### 13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force. 91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.

Disposal of hardened product (EC waste code) : 17 01 01

Disposal of not hardened product (EC waste code) : 17 01 01

The suggested European waste code is just based on the composition of the product.

According to the specific process or application field a different waste code may be necessary.

#### SECTION 14: Transport information

##### 14.1. UN number

UN Number: ==

##### 14.2. UN proper shipping name

N.A.

##### 14.3. Transport hazard class(es)

Rail/Road(RID/ADR): no dangerous good

ADR-Upper number: NA

Air (ICAO/IATA): no dangerous good

Sea (IMO/IMDG): no dangerous good

N.A.

##### 14.4. Packing group

N.A.

##### 14.5. Environmental hazards

Marine pollutant: No

N.A.

##### 14.6. Special precautions for user

N.A.

##### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No

#### SECTION 15: Regulatory information

##### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) 2015/830

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restrictions related to the substances contained:

No restriction.

Legislative Decree no. 81 of the 9th of April 2008 Title XI "Dangerous substances - Chapter I - Protection against chemical agents"

Directive 2000/39/CE and s.m.i. (Professional threshold limit)

## Safety Data Sheet

### KERAQUICK S1

Legislative Decree no. 152 of the 3rd of April 2006 and subsequent modifications and additions.  
(Environmental regulations)  
Directive 105/2003/CE (Seveso III): N.A.  
ADR Agreement – IMDG Code – IATA Regulation  
VOC (2004/42/EC) : N.A. g/l

#### Social Dialogue on Respirable Crystalline Silica

On April 26, 2006 was signed a multi-sector social dialogue, based on a "Guide to Good Practices", on workers health protection who are in contact with products containing crystalline silica.  
The text of the agreement published in G.U. European Union (2006 / C 279/02) and the "Guide to Good Practices", with attachments, are available on [www.nepsi.eu](http://www.nepsi.eu) website, they offer guidelines and useful information for handling products containing respirable crystalline silica.

Provisions related to directives 82/501/EC(Seveso), 96/82/EC(Seveso II):  
N.A.  
15.2. Chemical safety assessment  
No

#### SECTION 16: Other information

Text of phrases referred to under heading 3:

H335 May cause respiratory irritation.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

NIOSH - Registry of toxic effects of chemical substances

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,

Commission of the European Communities

SAX'S - Dangerous properties of industrial materials

Istituto Superiore di Sanità - Inventario Nazionale Sostanze Chimiche

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

## Safety Data Sheet

### KERAQUICK S1

	(ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
OEL:	Substance with a Union workplace exposure limit.
VLE:	Threshold Limiting Value.
WGK:	German Water Hazard Class.
TSCA:	United States Toxic Substances Control Act Inventory
DSL:	DSL - Canadian Domestic Substances List