

SAFETY DATA SHEET

DANISH OIL

Page 1 Issued: 31/07/04

Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: DANISH OIL

Product code: DANO

Synonyms: DANISH OIL

Use / description of product: Flammable. Liquid.

Company name: Rustins Ltd

Waterloo Road Cricklewood London NW2 7TX United Kingdom

Tel: +44 (0)208 450 4666 Fax: +44 (0)208 452 2008

Emergency tel: +44 (0)208 205 8709

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: METHANOL <1%

CAS: 67-56-1

EINECS: 200-659-6

[F] R11; [T] R23/24/25; [T] R39/23/24/25

• NAPTHA (PETROLEUM) HYDROTREATED HEAVY 70-90%

CAS: 64742-48-9 EINECS: 265-150-3

[Xn] R65; [Xi] R66; [-] R67

3. HAZARDS IDENTIFICATION

Main hazards: Flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause

drowsiness and dizziness.

Other hazards: (see section 16).

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: May cause irritation on prolonged or repeated contact.

Eye contact: Irritation with short term redness and stinging.

Ingestion: May cause nausea and diarrhoea.

Inhalation: May cause irritation of the respiratory tract.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietry

skin cleaner. Do NOT use solvents or thinners. If irritation persists seek medical attention.

DANISH OIL

Eye contact: Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10

minutes, holding the eyelids apart, and seek medical advice.

Ingestion: If accidentally swallowed, wash mouth out with water. Do not induce vomiting, keep at rest

and obtain medical attention.

Inhalation: Remove to fresh air, keep the patient warm and at rest. If breathing has stopped, administer

artificial respiration. Give nothing by mouth if unconscious, place in the recovery position and

seek medical advice.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide (CO2). Dry chemical powder. Alcohol resistant foam. Sand or earth. Do NOT

use water jet.

Exposure hazards: In a fire, hazardous decomposition products such as smoke and Carbon Monoxide may be

produced.

Protection of fire-fighters: Exposure to decomposition products may be a hazard to health. Appropriate self-contained

breathing apparatus may be required. Cool closed containers exposed to fire with water spray.

Do NOT allow run-off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Ventilate the area. Eliminate all sources of ignition. No Smoking. Avoid inhaling vapour. Mark

out the contaminated area with signs and prevent access to unauthorised personnel. Do not

attempt to take action without suitable protective clothing (see section 8).

Environmental precautions: Do not discharge into drains or rivers. If the product enters drains or sewers, the local water

company should be contacted immediately. In the case of contamination of streams, rivers or

lakes contact the relevant environment agency.

Clean-up procedures: Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth,

vermiculite. Transfer into a suitable container for disposal in accordance with the waste

regulations (see section 13) Do not use equipment in clean-up procedure which may produce

sparks. Clean preferably with a detergent, avoid the use of solvents. There is a danger that

absorbent material, used to clean up, may spontaneously combust. Absorbents should be

sprayed with water prior to disposal.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid inhalation of vapour. Avoid skin and eye

contact. Smoking, eating and drinking should be prohibited in areas of storage and use. Skin contact constitutes the most pronounced hazard. Persons with a history of skin sensitisation problems should only be employed in processes in which this product is used under appropriate medical supervision. Exclude sources of heat, sparks and open flame. Earth any equipment

 $used \ in \ handling. \ Use \ non-sparking \ tools. \ Rags \ used \ to \ apply \ the \ oil \ may \ self-ignite \ without$

warning. Remove used cloths/rags from premises regularly and always at close of business.

Issued: 31/07/04

SAFETY DATA SHEET

DANISH OIL

Rags should ideally be burnt. If this is not possible they should be washed in warm soapy water and disposed of without crumpling. Absorbents should be sprayed with water prior to disposal. The Manual Handling Operations Regulations may apply to the handling of containers of this

product.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight. Exclude sources of heat, sparks and open flame. Take precautionary measures to prevent product spills into drains, the ground or waters. Although the storage of this product is not subject to specific statutory requirements, the principles contained in the HSE guidance note Storage of Flammable Liquids in containers, should be observed.

Suitable packaging: Ideally, keep in original container. If transfer is necessary use glass or coated steel containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: METHANOL

TWA (8 hr exposure limit): 266 mg/m3 STEL (15 min exposure limit): 333 mg/m3 (OES)

Engineering measures: Provide adequate ventilation. Where reasonably practicable, this should be achieved by the

use of local exhaust ventilation and good general extraction. If these are not sufficient to

maintain concentrations of particulates and/or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn (see Respiratory

protection below).

Respiratory protection: All personal protective equipment, including respiratory protective equipment, used to control

exposure to hazardous substances must be selected to meet the requirements of the COSHH

Regulations.

Hand protection: Where repeated skin exposure may occur, wear Nitrile gloves.

Eye protection: Safety goggles. Ensure eye bath is to hand.

Skin protection: Overalls are normally suitable, PVC apron if risk of splashing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid
Colour: Brown

Oxidising: Non-oxidising (by EC criteria)

Viscosity: Oily

Boiling point/range°C: 150-190

Flash point°C: 43

Relative density: 0.850 @ 20C

10. STABILITY AND REACTIVITY

Stability: Stable under normal storage and handling conditions (see Section 7).

Conditions to avoid: Avoid heat, flames and sparks. Direct sunlight.

Materials to avoid: Oxidising agents. Strong acids.

[cont...]

Page 3

Issued: 31/07/04

SAFETY DATA SHEET

DANISH OIL Page 4

Haz. decomp. products: In a fire, hazardous decomposition products such as smoke and carbon monoxide may be

produced.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: METHANOL

IVN RAT LD50 2131 mg/kg ORL MUS LD50 7300 mg/kg ORL RAT LD50 5628 mg/kg

Routes of exposure: This product has not been tested for toxicity. The toxicological properties given in this section

are based on those of the solvents. The vapour is irritating to the eyes and splashes of liquid may cause discomfort and possible damage. Prolonged skin contact will have a defatting effect, which may lead to irritation and possibly dermatitis. Vapour irritates the eyes and the

respiratory tract.

12. ECOLOGICAL INFORMATION

Mobility: Insoluble in water. Partially volatile. Partially absorbed into soil. The product should not be

allowed to enter drains or water courses or be deposited where it can affect ground or surface

waters.

Other adverse effects: There is no data available on the product itself.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1263 ADR Class: 3

Labelling: 3 Hazard ID no: 30



IMDG/IMO

UN no: 1263 **Class:** 3

Packing group: III EmS: 3-05

Marine pollutant: Yes Labelling: 3

SAFETY DATA SHEET

DANISH OIL Page 5

IATA / ICAO

UN no: 1263 Class: 3

Packing group: III Packing instructions: 310

Labelling: 3

15. REGULATORY INFORMATION

Risk phrases: R10: Flammable.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S2: Keep out of the reach of children.

S7: Keep container tightly closed.

S16: Keep away from sources of ignition - No smoking.

S51: Use only in well-ventilated areas.

Precautionary phrases: Contains cobalt octoate, methyl ethyl ketoxime. May produce an allergic reaction.

Note: The regulatory information given above only indicates the principal regulations specifically

applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions. Safety Data Sheet

complies with UK regulatory references in accordance with CHIP 3.

16. OTHER INFORMATION

Other information: The product complies with the requirements of the Toy Safety Regulations, BS EN 71 Part 3

1995. A certificate of conformity can be supplied upon request. DANGER of spontaneous combustion. After use, any cloths or rags should ideally be immediately burnt but if this is not possible, then they should be washed in warm soapy water. Even after washing the rags must never be crumpled into a ball but spread out and disposed of. Use synthetic fibre cloths where possible as natural fibres, especially cotton, increase the chances of spontaneous combustion. Brushes and rollers should be cleaned with White Spirit and then washed in warm soapy water.

Risk phrases used in s.2: R11: Highly flammable.

R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.

 $R39/23/24/25 \colon Toxic \colon danger \ of \ very \ serious \ irreversible \ effects \ through \ inhalation, \ in \ contact$

with skin and if swallowed.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall

be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. As the specific conditions of use of the

[cont...]

SAFETY DATA SHEET

DANISH OIL

Page 6

product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.