
Page 1/7

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.03.2014

Version number 1

Revision: 20.03.2014



(Contd. on page 2)

Page 2/7

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.03.2014

Version number 1

Revision: 20.03.2014

Trade name: Touch-up Stick, all colours

	(Contd. of page 1)
· Hazard s	statements
H226 Fla	ammable liquid and vapour.
Н336 Ма	ay cause drowsiness or dizziness.
• Precauti	ionary statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapours.
P271	Use only outdoors or in a well-ventilated area.
P304+P.	340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P405	Store locked up.
P501	Dispose of contents / container in accordance with regional regulations.
· Addition	al information:
	iner sizes up to 125ml the labelling can be reduced in accordance with Article 29 (2) in connection
	nex I No. 1.5.2.
<i>EUH066</i>	6 Repeated exposure may cause skin dryness or cracking.
• 2.3 Othe	er hazards
· Results o	of PBT and vPvB assessment
	ot applicable.
• vPvB: No	ot applicable.
3 Compo	osition/information on ingredients
	nical characterization: Mixtures ion: Mixture of substances listed below with nonhazardous additions.
·Dangero	ous components:
CAS: 12	3-86-4 n-butyl acetate 25-<50%

· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-butyl acetate R10-66-67 � Flam. Liq. 3, H226; � STOT SE 3, H336	25-<50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	xylene, mixture of isomers Xn R20/21; Xi R38 R10 Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	2.5-<5.0%
CAS: 64742-94-5 EINECS: 265-198-5 Reg.nr.: 01-2119510128-50	Solvent naphtha (petroleum), heavy arom. Xn R65 Asp. Tox. 1, H304	2.5-<5.0%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol Xi R36; F R11 R67 Flam. Liq. 2, H225; I Eye Irrit. 2, H319; STOT SE 3, H336	<2.5%
CAS: 64742-95-6 EINECS: 265-199-0 Reg.nr.: 01-2119486773-24	Solvent naphtha (petroleum), light arom. 🗙 Xn R65; 🗙 Xi R37; 🌄 N R51/53	<u>≤</u> 0.5%

• Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1 67/548 EU), so the classification as carcinogen need not to apply. For the wording of the listed risk phrases refer to section 16.

4 First aid measures

*

• 4.1 Description of first aid measures

· After inhalation: Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

Printing date 20.03.2014

Version number 1

Revision: 20.03.2014

Trade name: Touch-up Stick, all colours

- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water

Water with full jet

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters -
- · Protective equipment: No special measures required.

6 Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Do not flush with water or aqueous cleansing agents Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

- · 7.1 Precautions for safe handling Use only in well ventilated areas.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm

Long-term value: 724 mg/m³, 150 ppm

(Contd. on page 4)

(Contd. of page 2)

GB

Printing date 20.03.2014

Version number 1

Revision: 20.03.2014

Trade name: Touch-up Stick, all colours

WEL	20-7 xylene, mixture of isomers
	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm
	Sk; BMGV
	-0 propan-2-ol
	Short-term value: 1250 mg/m ³ , 500 ppm
	Long-term value: 999 mg/m ³ , 400 ppm
	dients with biological limit values:
-	20-7 xylene, mixture of isomers
	V 650 mmol/mol creatinine
DMO	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid
A dditi	ional information: The lists valid during the making were used as basis.
Person Gener Respin	xposure controls nal protective equipment: ral protective and hygienic measures: Wash hands before breaks and at the end of work. ratory protection:
Person Gener Respin Not ne Other Protect Solver In cass KCL O The gi Select degrad Mater Penett Butyl Aceto	nal protective equipment: ral protective and hygienic measures: Wash hands before breaks and at the end of work. ratory protection: ecessary if room is well-ventilated. wise, filter class A / P2 or self contained. ction of hands: nt resistant gloves se of contact with spray dust protective gloves made of butyl shoud be used (min. 0.4 mm thick), e. Camatril, article no. 898 or similar products love material has to be impermeable and resistant to the product/ the substance/ the preparation. tion of the glove material on consideration of the penetration times, rates of diffusion and the dation rial of gloves Butyl rubber, BR ration time of glove material rubber gloves with a thickness of 0.4 mm are resistant to: one: 480 min
Person Gener Respin Not ne Other Protect Solver In cass KCL O The gi Select degrad Mater Peneta Butyl Aceto Butyl	nal protective equipment: ral protective and hygienic measures: Wash hands before breaks and at the end of work. ratory protection: ecessary if room is well-ventilated. wise, filter class A / P2 or self contained. ction of hands: nt resistant gloves se of contact with spray dust protective gloves made of butyl shoud be used (min. 0.4 mm thick), e. Camatril, article no. 898 or similar products love material has to be impermeable and resistant to the product/ the substance/ the preparation. tion of the glove material on consideration of the penetration times, rates of diffusion and the dation rial of gloves Butyl rubber, BR ration time of glove material rubber gloves with a thickness of 0.4 mm are resistant to:
Person Gener Respin Not ne Other Protect Solver In cass KCL O The gi Select degrad Mater Peneta Butyl Aceto Butyl Ethyl	nal protective equipment: ral protective and hygienic measures: Wash hands before breaks and at the end of work. ratory protection: eccessary if room is well-ventilated. wise, filter class A / P2 or self contained. ction of hands: nt resistant gloves se of contact with spray dust protective gloves made of butyl shoud be used (min. 0.4 mm thick), e. Camatril, article no. 898 or similar products love material has to be impermeable and resistant to the product/ the substance/ the preparation. tion of the glove material on consideration of the penetration times, rates of diffusion and the dation rial of gloves Butyl rubber, BR ration time of glove material rubber gloves with a thickness of 0.4 mm are resistant to: one: 480 min acetate: 60 min

<i>ippearanee</i>
Form:
Colour:

· Odour:

Fluid According to product specification Characteristic Not determined.

 · Odour threshold:
 Not determined.

 · pH-value:
 Not determined.

 · Change in condition Melting point/Melting range:
 Undetermined.

 · Boiling point/Boiling range:
 124 °C

 · Flash point:
 27 °C

 · Flammability (solid, gaseous):
 Not applicable.

(Contd. on page 5)

GB

Printing date 20.03.2014

Version number 1

Revision: 20.03.2014

Trade name: Touch-up Stick, all colours

	(Contd. of page
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
· Vapour pressure at 20 °C:	10.7 hPa
Density at 20 °C:	0.96 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/w	ater): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	90 s (ISO 4 mm)
Solvent content:	
VOC-(EU)	
	486.0 g/l
9.2 Other information	No further relevant information available.

10 Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity:
- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information: Vapours have narcotic effect.

12 Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 6)

GB

Printing date 20.03.2014

Version number 1

Revision: 20.03.2014

(Contd. of page 5)

Trade name: Touch-up Stick, all colours

- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

15 01 04 metallic packaging

· Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.*

14 Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1263	
· 14.2 UN proper shipping name · ADR · IMDG, IATA	UN1263 PAINT PAINT	
· 14.3 Transport hazard class(es)		
ADR		
· Class	3 (F1) Flammable liquids.	
- Label	3	
· Class	3 Flammable liquids.	
Label	3	
· 14.4 Packing group · ADR, IMDG, IATA	III	
14.5 Environmental hazards:		
Marine pollutant:	No	
· 14.6 Special precautions for user · Danger code (Kemler):	Warning: Flammable liquids. 30	
		(Contd. on page

Printing date 20.03.2014

Version number 1

Revision: 20.03.2014

Trade name: Touch-up Stick, all colours

	(Contd. of	page 6)
· EMS Number:	<i>F-E,<u>S-E</u></i>	
• 14.7 Transport in bulk according to Anno MARPOL73/78 and the IBC Code	ex II of Not applicable.	
· Transport/Additional information:		
·ADR		
· Limited quantities (LQ)	5L	
· Transport category	3	
• Tunnel restriction code	D/E	
· UN "Model Regulation":	UN1263, PAINT, 3, III	

15 Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture .

- Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- R10 Flammable.
- R11 Highly flammable.

R20/21 Harmful by inhalation and in contact with skin.

- *R36 Irritating to eyes.*
- R37 Irritating to respiratory system.
- R38 Irritating to skin.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- *R65 Harmfull: may cause lung damage if swallowed*
- *R66 Repeated exposure may cause skin dryness or cracking.*
- *R67 Vapours may cause drowsiness and dizziness.*
- · Contact: Anwendungstechnik
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINECS: European Inventory of Existing Commercial Chemic ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)