

SAFETY DATA SHEET Tyreweld

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Tyreweld

Product number TW1, TW2, TW3, 72051040001, HT4YB, HREP0023A, HREP0022A, HREP0024A,

HREP0025A, HREP0026A, HREP0027A, HREP0028A, HREP0033A, HREP0048A, HREP0053A, HREP0054A, HREP0055A, 72051020000, 79051382928, 79051382929, 79051392928, 79051392929, 79051372928, 79051372929, HT5SFKY6, HT2Y, HT2YRU, HT3SFKY, 72051020001, HT5YRU, HT3Y, HT2YPL, HT5YPL, 72051400001, HT2YA, HT3YA, HT4YA, 71051100002, 72051020012, 62051010001, 53012010001, 53012020001, 72081191125, 5010218214521, 3256640015776, 5010218214552, 5010218214514, 3256640015813, 5010218003163, 72051030001, HREP0403A,

HREP0404A, HREP0601A, HT2, HREP0304A, 72051041012, HREP0504A, HREP0406A, HREP0402A, HREP0502A, 72051030012, HREP0503A, HREP0402B, HREO0502B, HREP0018A, 72051030022, 72051030089, 72051040012, 72051400054, HREP0066A,

HRE0067A

REACH registration notes This is a MIXTURE; no reg

This is a MIXTURE; no registration information contained in this document . Holts are classed

as Downstream User.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Car maintenance product.

1.3. Details of the supplier of the safety data sheet

Supplier A Holts Car Care Product

Holt Lloyd International Ltd

Barton Dock Road

Stretford Manchester

M32 0YQ - England, UK +44 (0) 161 866 4800 FAX +44 (0) 161 866 4854

www.holtsauto.com

Contact person Contact Email address: info@holtsauto.com

1.4. Emergency telephone number

Emergency telephone UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs Out of office hours Tel: 020 7358

9167

National emergency telephone https://poisoncentres.echa.europa.eu/

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Not Classified

Tyreweld

Environmental hazards Not Classified

Classification (67/548/EEC or F+;R12.

1999/45/EC)

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

Precautionary statements P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with local regulations.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

BUTANE 10-30%

CAS number: 106-97-8 EC number: 203-448-7

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Gas 1 - H220 F+;R12

Press. Gas

ISOBUTANE 10-30%

CAS number: 75-28-5 EC number: 200-857-2

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Gas 1 - H220 F+;R12

Press. Gas

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Keep affected person away from heat, sparks and flames. Move affected person to fresh air at

once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention

immediately.

Ingestion Not relevant.

Tyreweld

Skin contact Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact If liquid has entered the eyes, proceed as follows. Remove any contact lenses and open

eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15

minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure. Get medical attention promptly if symptoms occur after washing.

Inhalation Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion Due to the physical nature of this material it is unlikely that swallowing will occur.

Skin contact Prolonged skin contact may cause redness and irritation.

Eye contact May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray,

fog or mist.

5.2. Special hazards arising from the substance or mixture

Specific hazards Risk of explosion if heated. Containers can burst violently or explode when heated, due to

excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during

firefighting

Containers close to fire should be removed or cooled with water. Use water to keep fire

exposed containers cool and disperse vapours.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8.

6.2. Environmental precautions

Environmental precautions Not considered to be a significant hazard due to the small quantities used.

6.3. Methods and material for containment and cleaning up

Methods for cleaning upWear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,

clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Wear protective

clothing as described in Section 8 of this safety data sheet.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Tyreweld

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and

eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air

contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

Storage class Flammable compressed gas storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³ Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

ISOBUTANE

Long-term exposure limit (8-hour TWA): OES 800 ppm Short-term exposure limit (15-minute): OES 800 ppm

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment





Appropriate engineering

controls

Provide adequate general and local exhaust ventilation.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. The following protection should be worn: Chemical splash goggles or

face shield.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. It is recommended that gloves are made

of the following material: Rubber (natural, latex). EN374

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or

prolonged vapour contact.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Do not

smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat,

drink or smoke.

Respiratory protection
No specific recommendations. Respiratory protection must be used if the airborne

contamination exceeds the recommended occupational exposure limit.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Tyreweld

Appearance Aerosol.

Colour White.

Odour Slight.

pH pH (concentrated solution): 9.5

Upper/lower flammability or

explosive limits

Lower flammable/explosive limit: 4.8 Upper flammable/explosive limit: 9.5

Relative density 0.995 @ °C

Solubility(ies) Slightly soluble in water. Insoluble in organic solvents.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Not applicable.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Strong oxidising agents. Strong alkalis. Strong mineral acids.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation Extensive use of the product in areas with inadequate ventilation may result in the

accumulation of hazardous vapour concentrations. May cause eye and respiratory system irritation. Symptoms following overexposure may include the following: Headache. Vapours

may cause headache, fatigue, dizziness and nausea.

IngestionNo harmful effects expected from quantities likely to be ingested by accident.

Skin contact Prolonged and frequent contact may cause redness and irritation.

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

SECTION 12: Ecological Information

EcotoxicityThe product is not expected to be hazardous to the environment. The product components

are not classified as environmentally hazardous. However, large or frequent spills may have

hazardous effects on the environment.

Tyreweld

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all

surfaces. The product is insoluble in water. The product hardens to a solid, immobile

substance.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Empty containers must not be punctured or incinerated because of the risk of an explosion.

Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

SECTION 14: Transport information

General LIMITED QUANTITIES

Road transport notes 5F

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name

AEROSOLS

(ADR/RID)

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

Tyreweld

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

ADR/RID packing group None

IMDG packing group None

ADN packing group None

ICAO packing group None

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable. **Annex II of MARPOL 73/78**

--- --- --- IDO O-----

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

EU legislation Dangerous Substances Directive 67/548/EEC.

Dangerous Preparations Directive 1999/45/EC.

Detergents Regulation EC 648/2004

VOC Directive - 2004/42/EC

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Authorisations (Title VII

Regulation 1907/2006)

No specific authorisations are known for this product.

Restrictions (Title VIII

Regulation 1907/2006)

No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 08/09/2015

Tyreweld

Revision 28

Supersedes date 09/06/2014

SDS number 12866

Risk phrases in full R12 Extremely flammable.

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.