

Page: 1

Compilation date: 25/2/14

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier Product name: SILICONE 825 Product code: 825-1.2. Relevant identified uses of the substance or mixture and uses advised against 1.3. Details of the supplier of the safety data sheet Company name: EVERBUILD BUILDING PRODUCTS LTD SITE 41, KNOWSTHORPE WAY CROSS GREEN INDUSTRIAL ESTATE LEEDS WEST YORKSHIRE LS9OSW ENGLAND Tel: 0044 113 240 3456 Fax: 0044 113 240 0024 Email: sds@everbuild.co.uk 1.4. Emergency telephone number Emergency tel: 0044 113 240 3456 (office hours only) Manufacturer: EVERBUILD BUILDING PRODUCTS LTD Site 41 Knowsthorpe Way, Cross Green Industrial Estate Leeds West Yorkshire LS9 0SW United Kingdom Tel: (0044) 113 240 3456 Fax: (0044) 113 240 0024 Emergency tel: (0044) 113 240 3456 Email: sds@everbuild.co.uk Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: This product has no classification under CHIP.

Classification under CLP: This product has no classification under CLP.

SILICONE 825

Page: 2

2.2. Label elements

Label elements: This product has no label elements.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

BIS (ETHYL ACETOACETATO-O(1)-O(3)-) BIS(2-METHYLPROPAN-1-OLATO)TITANIUM

EINECS	CAS	CHIP Classification	CLP Classification	Percent
281-161-6	83877-91-2	-: R10; Xi: R36/38	-	1-10%

TRIMETHOXY VINYLSILANE

220-449-8	2768-02-7	-: R10; Xn: R20	Acute Tox. 4: H332; Flam. Liq. 3: H226		
METHANOL - REACH registered number(s): 01-2119433307-44-XXXX					
200-659-6	67-56-1	F: R11; T: R23/24/25; T: R39/23/24/25	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370	<1%	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

SILICONE 825

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-

side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

METHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	266 mg/m3	333 mg/m3	-	

DNEL/PNEC Values

DNEL / PNEC No data available.

SILICONE 825

8.2. Exposure controls

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Paste		
Colour:	Various		
Odour:	Sweet-smelling		
Evaporation rate:	Negligible		
Oxidising:	Non-oxidising (by EC criteria)		
Solubility in water:	Insoluble		
Also soluble in:	Most organic solvents.		
Viscosity:	Highly viscous		
Boiling point/range°C:	>200	Flash point°C:	>100`C
Relative density:	1.4	VOC g/l:	16.9

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Heat. Moist air. Humidity.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

[cont...]

SILICONE 825

Page: 5

Hazardous ingredients:

METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

TRIMETHOXY VINYLSILANE

Daphnia magna	-	21D NOEC 28	mg/l
Daphnia magna	48H EC50	169	mg/l
GREEN ALGA (Selenastrum capricornutum)	-	72H NOEC 25	mg/l
GREEN ALGA (Selenastrum capricornutum)	72H IC50	210	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	191	mg/l

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Dispose of according to local or national legislation

SILICONE 825

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information		
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No	
	453/2010.	
	* indicates text in the SDS which has changed since the last revision.	
Phrases used in s.2 and s.3:	H225: Highly flammable liquid and vapour.	
	H226: Flammable liquid and vapour.	
	H301: Toxic if swallowed.	
	H311: Toxic in contact with skin.	
	H331: Toxic if inhaled.	
	H332: Harmful if inhaled.	
	H370: Causes damage to organs <or affected,="" all="" if="" known="" organs="" state=""> <state of<="" route="" th=""></state></or>	
	exposure if it is conclusively proven that no other routes of exposure cause the hazard>.	
	R10: Flammable.	
	R11: Highly flammable.	
	R20: Harmful by inhalation.	
	R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.	
	R36/38: Irritating to eyes and skin.	
	R39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in	
	contact with skin and if swallowed.	
Legend to abbreviations:	PNEC = predicted no effect level	
	DNEL = derived no effect level	
	LD50 = median lethal dose	
	LC50 = median lethal concentration	
	EC50 = median effective concentration	
	IC50 = median inhibitory concentration	
	dw = dry weight	

SILICONE 825

bw = body weight cc = closed cup oc = open cup MUS = mouse GPG = guinea pig RBT = rabbit HAM = hamster HMN = human MAM = mammal PGN = pigeon IVN = intravenous SCU = subcutaneous SKN = skin DRM = dermal OCC = ocular/corneal PCP = phycico-chemical properties Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.