

Ink for Milwaukee® Liquid Paint Marker BLUE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 10/6/2023 Revision date: 10/6/2023 Version: 1.0
SDS No: 13047-0027

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Ink for Milwaukee® Liquid Paint Marker BLUE
UFI : 7X1D-ST35-FW0X-CDQ5
Further information : 4932492144 (LIQUID PAINT MARKER - BLUE)

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Use of the substance/mixture : Paint markers

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Techtronic Industries GmbH
Max-Eyth-Straße
71364 Winnenden
Germany
T +49 7195-12-0
regulatory-DE@TTI-EMEA.com
E-mail address of competent person responsible for the SDS: sds@gbk-ingelheim.de

1.4. Emergency telephone number

Emergency number : Emergency CONTACT (24-Hour-Number): GBK GmbH +49 6132-84463

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2 H225
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. May cause drowsiness or dizziness. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) : 

Signal word (CLP) : Danger
Contains : n-butyl acetate; Butanone; 2-methoxy-1-methylethyl acetate
Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.
H319 - Causes serious eye irritation.
H336 - May cause drowsiness or dizziness.

Ink for Milwaukee® Liquid Paint Marker BLUE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 13047-0027

Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280 - Wear eye protection, face protection. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P403+P235 - Store in a well-ventilated place. Keep cool. P501 - Dispose of contents and container to Dispose of contents/container in accordance with local and national regulations.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking.
Child-resistant fastening	: Not applicable
Tactile warning	: Applicable

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
n-butyl acetate Substance with a Community workplace exposure limit	CAS-No.: 123-86-4 EC-No.: 204-658-1 EC Index-No.: 607-025-00-1 REACH-no: 01-2119485493-29	37 - 40	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066
Butanone Substance with a Community workplace exposure limit	CAS-No.: 78-93-3 EC-No.: 201-159-0 EC Index-No.: 606-002-00-3 REACH-no: 01-2119457290-43	10 - 13	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
2-methoxy-1-methylethyl acetate Substance with a Community workplace exposure limit	CAS-No.: 108-65-6 EC-No.: 203-603-9 EC Index-No.: 607-195-00-7 REACH-no: 01-2119475791-29	7 - 10	Flam. Liq. 3, H226 STOT SE 3, H336

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing.

Ink for Milwaukee® Liquid Paint Marker BLUE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 13047-0027

- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : May cause drowsiness or dizziness.
- Symptoms/effects after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
- Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapour.
- Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing spray, vapours, mist. Avoid contact with skin and eyes.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

Ink for Milwaukee® Liquid Paint Marker BLUE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 13047-0027

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing spray, vapours, mist. Avoid contact with skin and eyes.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Storage area : Store away from heat. Store away from direct sunlight or other heat sources.

7.3. Specific end use(s)

See Section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

n-butyl acetate (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Butyl acetate
IOEL TWA	241 mg/m ³
IOEL TWA [ppm]	50 ppm
IOEL STEL	723 mg/m ³
IOEL STEL [ppm]	150 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831
Butanone (78-93-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Butanone
IOEL TWA	600 mg/m ³
IOEL TWA [ppm]	200 ppm
IOEL STEL	900 mg/m ³
IOEL STEL [ppm]	300 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
2-methoxy-1-methylethyl acetate (108-65-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Methoxy-1-methylethylacetate
IOEL TWA	275 mg/m ³
IOEL TWA [ppm]	50 ppm

Ink for Milwaukee® Liquid Paint Marker BLUE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 13047-0027

2-methoxy-1-methylethyl acetate (108-65-6)	
IOEL STEL	550 mg/m ³
IOEL STEL [ppm]	100 ppm
Remark	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

n-butyl acetate (123-86-4)	
PNEC (Water)	
PNEC aqua (freshwater)	0.18 mg/l
PNEC aqua (marine water)	0.018 mg/l
PNEC aqua (intermittent, freshwater)	0.36 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.981 mg/kg dwt
PNEC sediment (marine water)	0.0981 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.0903 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	35.6 mg/l
Butanone (78-93-3)	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	900 mg/m ³
Long-term - systemic effects, dermal	1161 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	600 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	450 mg/m ³
Long-term - systemic effects, oral	31 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	106 mg/m ³
Long-term - systemic effects, dermal	412 mg/kg bodyweight/day
2-methoxy-1-methylethyl acetate (108-65-6)	
DNEL/DMEL (Workers)	
Acute - local effects, inhalation	550 mg/m ³
Long-term - systemic effects, dermal	796 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	275 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, oral	500 mg/kg bodyweight/day

Ink for Milwaukee® Liquid Paint Marker BLUE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 13047-0027

2-methoxy-1-methylethyl acetate (108-65-6)	
Long-term - systemic effects, oral	36 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	33 mg/m ³
Long-term - systemic effects, dermal	320 mg/kg bodyweight/day
Long-term - local effects, inhalation	33 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.635 mg/l
PNEC aqua (marine water)	0.0635 mg/l
PNEC aqua (intermittent, freshwater)	6.35 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	3.29 mg/kg dwt
PNEC sediment (marine water)	0.329 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.29 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	100 mg/l

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:

Protective goggles (EN 166)

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Chemically resistant protective gloves. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Ink for Milwaukee® Liquid Paint Marker BLUE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 13047-0027

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Blue.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: 80 °C (Butanone)
Flammability (solid, gas)	: Highly flammable liquid and vapour
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: -7.5 °C (Butanone)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Ink for Milwaukee® Liquid Paint Marker BLUE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 13047-0027

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

2-methoxy-1-methylethyl acetate (108-65-6)

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
-----------------	--

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure : May cause drowsiness or dizziness.

n-butyl acetate (123-86-4)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

Butanone (78-93-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

2-methoxy-1-methylethyl acetate (108-65-6)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

n-butyl acetate (123-86-4)

LOAEL (oral, rat, 90 days)	500 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
----------------------------	---

NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Guideline: EPA OTS 798.2650 (90-Day Oral Toxicity in Rodents)
----------------------------	---

2-methoxy-1-methylethyl acetate (108-65-6)

NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
-------------------------------------	--

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)
Hazardous to the aquatic environment, long-term (chronic) : Not classified (Based on available data, the classification criteria are not met)

n-butyl acetate (123-86-4)

LC50 fish 1	18 mg/l Test organisms (species): Pimephales promelas
-------------	---

Ink for Milwaukee® Liquid Paint Marker BLUE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 13047-0027

n-butyl acetate (123-86-4)	
EC50 Daphnia 1	44 mg/l Test organisms (species): Daphnia sp.
EC50 72h - Algae [1]	397 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	246 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	47.6 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	23.2 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

Butanone (78-93-3)	
LC50 fish 1	2973 mg/l Test organisms (species): Pimephales promelas
EC50 Daphnia 1	308 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	1220 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	1240 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

2-methoxy-1-methylethyl acetate (108-65-6)	
LC50 fish 1	> 100 mg/l Test organisms (species): Oryzias latipes
EC50 Daphnia 1	> 500 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 1000 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	47.5 mg/l Test organisms (species): Oryzias latipes Duration: '14 d'

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Disposal must be done according to official regulations.

Additional information : Flammable vapours may accumulate in the container.






Ink for Milwaukee® Liquid Paint Marker BLUE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 13047-0027

SECTION 14: Transport information


In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1263	UN 1263	UN 1263	UN 1263	UN 1263
14.2. UN proper shipping name				
PAINT	PAINT	Paint	PAINT	PAINT
Transport document description				
UN 1263 PAINT, 3, II, (D/E)	UN 1263 PAINT, 3, II	UN 1263 Paint, 3, II	UN 1263 PAINT, 3, II	UN 1263 PAINT, 3, II
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
II	II	II	II	II
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: F1
Special provisions (ADR)	: 163, 367, 640C, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Transport category (ADR)	: 2
Hazard identification number (Kemler No.)	: 33
Orange plates	:



Tunnel restriction code (ADR) : D/E

Transport by sea

Special provisions (IMDG)	: 163, 367
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E2
Packing instructions (IMDG)	: P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP8, TP28
EmS-No. (Fire)	: F-E

Ink for Milwaukee® Liquid Paint Marker BLUE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 13047-0027

EmS-No. (Spillage) : S-E
Stowage category (IMDG) : B

Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y341
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 353
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 364
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3, A72, A192
ERG code (IATA) : 3L

Inland waterway transport

Classification code (ADN) : F1
Special provisions (ADN) : 163, 367, 640D, 650
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E2
Equipment required (ADN) : PP, EX, A
Ventilation (ADN) : VE01
Number of blue cones/lights (ADN) : 1

Rail transport

Classification code (RID) : F1
Special provisions (RID) : 163, 367, 640D, 650
Limited quantities (RID) : 5L
Excepted quantities (RID) : E2
Packing instructions (RID) : P001, IBC02, R001
Transport category (RID) : 2
Hazard identification number (RID) : 33

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Ink for Milwaukee® Liquid Paint Marker BLUE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 13047-0027

Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Methylethylketone	Butanone	78-93-3	2914 12 00	Category 3		Annex I

Seveso Directive (Disaster Risk Reduction)

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P5c FLAMMABLE LIQUIDS Flammable liquids, Categories 2 or 3 not covered by P5a and P5b	5000	50000

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration

Ink for Milwaukee® Liquid Paint Marker BLUE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 13047-0027

Abbreviations and acronyms:	
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties
DOT	Department of Transport
TDG	Transportation of Dangerous Goods
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
GHS	Globally Harmonized System of Classification, Labelling and Packaging of Chemicals
IBC-Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
MARPOL 73/78	MARPOL 73/78: International Convention for the Prevention of Pollution From Ships
ADG	Transport of Australian Dangerous Goods

Other information

: Data of sections 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities. The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge. The delivery specifications are contained in the corresponding product sheet. This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

Full text of H- and EUH-statements:	
EUH066	Repeated exposure may cause skin dryness or cracking.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Ink for Milwaukee® Liquid Paint Marker BLUE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
SDS No: 13047-0027

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Flam. Liq. 2	H225	On basis of test data
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should therefore not be construed as guaranteeing any specific property of the product.