

Section 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier****Product name:** XYLENE THINNERS**CAS number:** 1330-20-7**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.3. Details of the supplier of the safety data sheet****Company name:** Rustins Ltd

Waterloo Road

Cricklewood

London

NW2 7TX

United Kingdom

Tel: +44 (0)208 450 4666**Fax:** +44 (0)208 452 2008**Email:** rustins@rustins.co.uk**1.4. Emergency telephone number****Section 2: Hazards identification****2.1. Classification of the substance or mixture****Classification under CLP:** Skin Irrit. 2: H315; Acute Tox. 4: H312+332; Flam. Liq. 3: H226**Classification under CHIP:** -: R10; Xn: R20/21; Xi: R38**Most important adverse effects:** Flammable liquid and vapour. Harmful in contact with skin or if inhaled. Causes skin irritation.**2.2. Label elements****Label elements under CLP:****Hazard statements:** H226: Flammable liquid and vapour.

H312+332: Harmful in contact with skin or if inhaled.

H315: Causes skin irritation.

Signal words: Warning**Hazard pictograms:** GHS02: Flame

GHS07: Exclamation mark

**Precautionary statements:** P260: Do not breathe vapours.

SAFETY DATA SHEET

XYLENE THINNERS

Page: 2

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing.

Rinse skin with water.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312: Call a POISON CENTER or doctor if you feel unwell.

P370+378: In case of fire: Use carbon dioxide for extinction.

2.3. Other hazards

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.1. Substances

Chemical identity: XYLENE

CAS number: 1330-20-7

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Consult a doctor. Give 1 cup of water to drink every 10 minutes.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. If unconscious, check for breathing and apply artificial respiration if necessary. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

5.2. Special hazards arising from the substance or mixture

5.3. Advice for fire-fighters

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

6.4. Reference to other sections

[cont...]

SAFETY DATA SHEET

XYLENE THINNERS

Page: 3

Section 7: Handling and storage

7.1. Precautions for safe handling

7.2. Conditions for safe storage, including any incompatibilities

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

XYLENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m ³	441 mg/m ³	-	-

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Boiling point/range °C: 137

Flash point °C: 23 - 55

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

10.5. Incompatible materials

10.6. Hazardous decomposition products

Section 11: Toxicological information

[cont...]

SAFETY DATA SHEET

XYLENE THINNERS

Page: 4

11.1. Information on toxicological effects

Hazardous ingredients:

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH DRM	Based on test data
Skin corrosion/irritation	DRM	Based on test data

Symptoms / routes of exposure

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1307

14.2. UN proper shipping name

Shipping name: XYLENES

14.3. Transport hazard class(es)

Transport class: 3

[cont...]

SAFETY DATA SHEET

XYLENE THINNERS

Page: 5

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: Yes

14.6. Special precautions for user

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: H226: Flammable liquid and vapour.

H312+332: Harmful in contact with skin or if inhaled.

H315: Causes skin irritation.

R10: Flammable.

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.