



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
Supersedes Date: 07-Sep-2022

Revision date 10-May-2024  
Revision Number 1.01

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product Name BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING

### Other means of identification

Pure substance/mixture Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Coatings

Uses advised against None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik GmbH  
Industriestrasse 3 – 11  
33829 Borgholzhausen, Germany  
Tel: +49 (0) 5425 / 801 0  
Fax: +49 (0) 5425 / 801 140

E-mail address SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

Ireland **NPIC - National Poison Information Centre**  
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)  
Healthcare Professionals: +353 (01) 8092566 (24 hour service)

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

Europe 112

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification according to  
Regulation (EC) No. 1272/2008  
[CLP]

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

### 2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### EU Specific Hazard Statements

EUH208 - Contains Trimethoxyvinylsilane & N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction  
EUH210 - Safety data sheet available on request

#### Precautionary Statements - EU (§28, 1272/2008)

# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
**Supersedes Date:** 07-Sep-2022

**Revision date** 10-May-2024  
**Revision Number** 1.01

P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children

## 2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Harmful to aquatic life.  
Combustible liquid.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No..	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Limestone 40 - <80 %	215-279-6	1317-65-3	[C]	-	-	-	[5]
Bis(2-propylheptyl)phthalate 10 - <20 %	258-469-4	53306-54-0	-	-	-	-	01-2119446694-30-XXXX
Poly[oxy(methyl-1,2-ethanediy)], .alpha.-[3-(dimethoxymethylsilyl)propyl]-.omega.-[3-(dimethoxymethylsilyl)propoxy-] 1 - <2.5 %	-	75009-88-0	-	-	-	-	[7]
.alpha., .alpha.', .alpha."-1,2,3-Propanetriyltris[.omega.-[3-(dimethoxymethylsilyl)propoxy] poly[oxy(methyl-1,2-ethanediy)] 1 - <2.5 %	-	151865-59-7	-	-	-	-	[7]
Trimethoxyvinylsilane 1 - <2.5 %	220-449-8 (014-049-00-0)	2768-02-7	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	-	-	01-2119513215-52-XXXX
Diisononyl 1,2-cyclohexanedicarboxylate 1 - <2.5 %	431-890-2	166412-78-8	-	-	-	-	01-0000017810-74-XXXX
Titanium dioxide 0.1- <1 %	236-675-5 (022-006-00-2)	13463-67-7	[C]	-	-	-	01-2119489379-17-XXXX
N-(3-(trimethoxysilyl)propyl)ethylenediamine 0.1- <1 %	217-164-6	1760-24-3	Eye Dam. 1 (H318) Skin Sens. 1B (H317) STOT SE 3 (H335)	-	-	-	01-2119970215-39-XXXX
Octadecyl 3-(3',5'-di-tert-butyl-4'-hydroxyphenyl)propionate	218-216-0	2082-79-3	-	-	-	-	01-2119491195-33-XXXX

# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
**Supersedes Date:** 07-Sep-2022

**Revision date** 10-May-2024  
**Revision Number** 1.01

0.1 - <1 %							
Quartz (fine fraction) 0.1 - <0.5 %	238-878-4	14808-60-7	STOT RE 1 (H372)	-	-	-	[5]
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 0.1 - <0.3 %	258-207-9	52829-07-9	Eye Dam. 1 (H318) Repr. 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)	-	-	-	01-2119537297-32-XXXX
Dioctyltin oxide 0.1 - <0.3 %	212-791-1	870-08-6	STOT SE 2 (H371)	-	-	-	01-2119971268-27-xxxx
Ethyl silicate 0.01 - <0.1 %	201-083-8 (014-005-00-0)	78-10-4	Acute Tox. 4 (H332) Eye Irrit. 2 (H319) STOT SE 3 (H335) Flam. Liq. 3 (H226)	-	-	-	01-2119496195-28-xxxx
1,2-Ethanediamine, N,N'-bis[3-(trimethoxysilyl)propyl]- 0.01 - <0.1 %	272-453-4	68845-16-9	Eye Dam. 1 (H318)	-	-	-	-
Ethane-1,1-diamine, N,N-bis(3-(trimethylsiloxy)propyl) 0.01 <= 0.036 %	-	74956-86-8	Eye Dam. 1 (H318)	-	-	-	-
1-Aza-2-silacyclopentane-1-ethanamine, 2,2-dimethoxy- 0.01 <= 0.036 %	-	618914-51-5	Eye Dam. 1 (H318)	-	-	-	-
Benzenepropanoic acid, 3-(1,1-dimethylethyl)-4-hydroxy-5-methyl-, 1,2-ethanediyldis(oxy-2,1-ethanediy) ester 0.01 <= 0.036 %	253-039-2	36443-68-2	-	-	-	-	01-2119956160-44-XXXX
Ethanol 0.0025 - <0.01 %	200-578-6 (603-002-00-5)	64-17-5	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)	-	-	-	01-2119457610-43-XXXX
Methyl alcohol 0.0025 - <0.01 %	200-659-6 (603-001-00-X)	67-56-1	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307-44-XXXX
Methyl silicate <0.0015 %	211-656-4	681-84-5	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Acute Tox. 1 (H330) Flam. Liq. 3 (H226)	-	-	-	01-2119957658-18-XXXX

**Air contaminants formed when using the substance or mixture as intended**

Chemical name	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Methyl alcohol 67-56-1	200-659-6 (603-001-00-X)	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307-44-XXXX

**Full text of H- and EUH-phrases: see section 16**

*Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes*

*[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring*

# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
**Supersedes Date:** 07-Sep-2022

**Revision date** 10-May-2024  
**Revision Number** 1.01

## Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Limestone	215-279-6	1317-65-3	-	-	-	-	-
Bis(2-propylheptyl)phthalate	258-469-4	53306-54-0	-	-	-	-	-
Trimethoxyvinylsilane	220-449-8 (014-049-00-0)	2768-02-7	-	-	-	11	-
Diisononyl 1,2-cyclohexanedicarboxylate	431-890-2	166412-78-8	-	-	-	-	-
Titanium dioxide	236-675-5 (022-006-00-2)	13463-67-7	-	-	-	-	-
N-(3-(trimethoxysilyl)propyl)ethylenediamine	217-164-6	1760-24-3	-	-	1.5	-	-
Octadecyl 3-(3',5'-di-tert-butyl-4'-hydroxyphenyl)propionate	218-216-0	2082-79-3	-	-	-	-	-
Quartz (fine fraction)	238-878-4	14808-60-7	-	-	-	-	-
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	258-207-9	52829-07-9	-	-	-	-	-
Diocetyl tin oxide	212-791-1	870-08-6	-	-	-	-	-
Ethyl silicate	201-083-8 (014-005-00-0)	78-10-4	-	-	4.9	11	-
1,2-Ethanediamine, N,N'-bis[3-(trimethoxysilyl)propyl]-	272-453-4	68845-16-9	-	-	-	-	-
Benzenepropanoic acid, 3-(1,1-dimethylethyl)-4-hydroxy-5-methyl-, 1,2-ethanediybis(oxy-2,1-ethanediy) ester	253-039-2	36443-68-2	-	-	-	-	-
Ethanol	200-578-6 (603-002-00-5)	64-17-5	-	-	-	-	-
Methyl alcohol	200-659-6 (603-001-00-X)	67-56-1	100	300	0.501	3	-
Methyl silicate	211-656-4	681-84-5	-	-	-	0.392	-

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## Notes

See section 16 for more information

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10

## SECTION 4: First aid measures

# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
Supersedes Date: 07-Sep-2022

Revision date 10-May-2024  
Revision Number 1.01

## 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a doctor.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>Skin contact</b>	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Call a doctor immediately. Never give anything by mouth to an unconscious person. Small amounts of toxic methanol are released by hydrolysis.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8).

## 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	None known.
<b>Effects of Exposure</b>	No information available.

## 4.3. Indication of any immediate medical attention and special treatment needed

<b>Note to doctors</b>	Treat symptomatically. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.
------------------------	---

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

<b>Suitable Extinguishing Media</b>	Water spray, carbon dioxide (CO <sub>2</sub> ), dry chemical, alcohol-resistant foam.
<b>Unsuitable extinguishing media</b>	Full water jet.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards arising from the chemical</b>	Thermal decomposition can lead to release of irritating gases and vapours.
<b>Hazardous combustion products</b>	Carbon oxides. Carbon monoxide. Carbon dioxide (CO <sub>2</sub> ). Silicon dioxide.

### 5.3. Advice for firefighters

<b>Special protective equipment and precautions for fire-fighters</b>	Wear self contained breathing apparatus for fire fighting if necessary.
---	---

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Use personal protective equipment as required. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.
<b>For emergency responders</b>	Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
Supercedes Date: 07-Sep-2022

Revision date 10-May-2024  
Revision Number 1.01

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

## 6.3. Methods and material for containment and cleaning up

**Methods for containment** Stop leak if you can do it without risk. Do not touch or walk through spilled material. Dyke far ahead of liquid spill for later disposal. Do not scatter spilled material with high pressure water streams.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from moisture. Keep away from food, drink and animal feedingstuffs.

**Recommended storage temperature** Keep at temperatures between 10 and 35 °C.

### 7.3. Specific end use(s)

**Specific use(s)**  
Coatings.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

**Exposure Limits** Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	Ireland	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> *	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 600 ppm STEL: 780 mg/m <sup>3</sup> Sk*	TWA: 200 ppm TWA: 266 mg/m <sup>3</sup> STEL: 250 ppm STEL: 333 mg/m <sup>3</sup> Sk*
Titanium dioxide	-	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>

# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
**Supersedes Date:** 07-Sep-2022

**Revision date** 10-May-2024  
**Revision Number** 1.01

13463-67-7		TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>	TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Dioctyltin oxide 870-08-6	-	TWA: 0.1 mg/m <sup>3</sup> STEL: 0.2 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup> STEL: 0.2 mg/m <sup>3</sup> Sk*

**Derived No Effect Level (DNEL)**      No information available

<b>Derived No Effect Level (DNEL)</b>			
<b>Bis(2-propylheptyl)phthalate (53306-54-0)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	125 mg/kg bw/d	
worker Long term Local health effects	Inhalation	5 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Inhalation	35.3 mg/m <sup>3</sup>	

<b>Trimethoxyvinylsilane (2768-02-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	27,6 mg/m <sup>3</sup>	
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	

<b>Titanium dioxide (13463-67-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

<b>N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Inhalation	35.5 mg/m <sup>3</sup>	
Long term Systemic health effects worker	Dermal	5 mg/kg bw/d	
Short term Systemic health effects worker	Dermal	5 mg/kg bw/d	

<b>Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Long term Systemic health effects	Inhalation	2.82 mg/m <sup>3</sup>	
worker	Dermal	1.6 mg/kg	

# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
**Supersedes Date:** 07-Sep-2022

**Revision date** 10-May-2024  
**Revision Number** 1.01

Long term Systemic health effects			
--------------------------------------	--	--	--

<b>Diocyltin oxide (870-08-6)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	0.05 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	0.004 mg/m <sup>3</sup>	

<b>Ethyl silicate (78-10-4)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Dermal	12.1 mg/kg bw/d	
worker Systemic health effects Long term	Dermal	12.1 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	85 mg/m <sup>3</sup>	
worker Short term Local health effects	Inhalation	85 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Inhalation	85 mg/m <sup>3</sup>	
worker Long term Local health effects	Inhalation	85 mg/m <sup>3</sup>	

<b>Benzenepropanoic acid, 3-(1,1-dimethylethyl)-4-hydroxy-5-methyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester (36443-68-2)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Inhalation	3 mg/m <sup>3</sup>	
Long term Systemic health effects worker	Dermal	86 mg/kg	

<b>Ethanol (64-17-5)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	950 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	343 mg/kg bw/d	

<b>Derived No Effect Level (DNEL)</b>			
<b>Bis(2-propylheptyl)phthalate (53306-54-0)</b>			
Type	Exposure route	Derived No Effect Level	Safety factor



# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
**Supersedes Date:** 07-Sep-2022

**Revision date** 10-May-2024  
**Revision Number** 1.01

		(DNEL)	
Consumer Long term Systemic health effects	Dermal	62.5 mg/kg	
Consumer Long term Local health effects	Inhalation	1.25 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Inhalation	8.7 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Oral	5 mg/kg	

<b>Trimethoxyvinylsilane (2768-02-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m <sup>3</sup>	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

<b>Titanium dioxide (13463-67-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

<b>N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects Consumer	Oral	2.5 mg/kg bw/d	
Long term Systemic health effects Consumer	Inhalation	8.7 mg/m <sup>3</sup>	
Long term Systemic health effects Consumer	Dermal	mg/kg bw/d	

<b>Quartz (fine fraction) (14808-60-7)</b>			
<b>Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	0.8 mg/kg	
Consumer Long term Systemic health effects	Oral	0.4 mg/kg	

<b>Diocetyl tin oxide (870-08-6)</b>			
Type	Exposure route	Derived No Effect Level	Safety factor

# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
**Supersedes Date:** 07-Sep-2022

**Revision date** 10-May-2024  
**Revision Number** 1.01

		(DNEL)	
Consumer Long term Systemic health effects	Oral	0.0005 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	0.025 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	0.0009 mg/m <sup>3</sup>	

## Ethyl silicate (78-10-4)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	8.4 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	8.4 mg/kg bw/d	
Consumer Short term Systemic health effects	Inhalation	25 mg/m <sup>3</sup>	
Consumer Short term Local health effects	Inhalation	25 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Inhalation	25 mg/m <sup>3</sup>	
Consumer Long term Local health effects	Inhalation	25 mg/m <sup>3</sup>	

## Benzenepropanoic acid, 3-(1,1-dimethylethyl)-4-hydroxy-5-methyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester (36443-68-2)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects Consumer	Dermal	43 mg/kg	
Long term Systemic health effects Consumer	Oral	4,3 mg/kg	

## Ethanol (64-17-5)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	114 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	206 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	87 mg/kg bw/d	

## Predicted No Effect Concentration (PNEC)

# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
**Supersedes Date:** 07-Sep-2022

**Revision date** 10-May-2024  
**Revision Number** 1.01

<b>Predicted No Effect Concentration (PNEC)</b>	
<b>Bis(2-propylheptyl)phthalate (53306-54-0)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater sediment	0.939 g/kg
Marine sediment	0.0939 mg/kg
Soil	26.5 mg/kg

<b>Trimethoxyvinylsilane (2768-02-7)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

<b>Titanium dioxide (13463-67-7)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

<b>N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.062 mg/l
Marine water	0.0062 mg/l
Freshwater - intermittent	0.62 mg/l
Freshwater sediment	0.05 mg/kg
Marine sediment	0.005 mg/kg
Soil	0.0075 mg/kg
Sewage treatment plant	25 mg/l

<b>Quartz (fine fraction) (14808-60-7)</b>	
<b>Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.018 mg/l
Marine water	0.0018 mg/l
Freshwater sediment	29 mg/kg
Marine sediment	2.9 mg/kg
Soil	5.9 mg/kg

<b>Diocetyl tin oxide (870-08-6)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater sediment	0.02798 mg/kg dry weight
Marine sediment	0.002798 mg/kg dry weight
Microorganisms in sewage treatment	100 mg/l

<b>Ethyl silicate (78-10-4)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.192 mg/l
Marine water	0.0192 mg/l
Freshwater sediment	0.18 mg/kg dry weight
Marine sediment	0.018 mg/kg dry weight
Soil	0.05 mg/kg

<b>Benzenepropanoic acid, 3-(1,1-dimethylethyl)-4-hydroxy-5-methyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester (36443-68-2)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Sewage treatment plant	1 mg/l
Freshwater	0.00055 mg/l
Marine water	0.000055 mg/l

# SAFETY DATA SHEET

BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING  
Supersedes Date: 07-Sep-2022

Revision date 10-May-2024  
Revision Number 1.01

Freshwater sediment	0.195 mg/kg dry weight
---------------------	------------------------

Ethanol (64-17-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	154 mg/l
Marine water	15.4 mg/l
Sewage treatment plant	100 mg/l

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166
<b>Hand protection</b>	Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
<b>Skin and body protection</b>	None under normal use conditions.
<b>Respiratory protection</b>	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
<b>Recommended filter type:</b>	Organic gases and vapours filter conforming to EN 14387. White. Brown.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Appearance</b>	Paste
<b>Colour</b>	Grey
<b>Odour</b>	Slight. Characteristic.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>Melting point / freezing point</b>	No data available	
<b>Initial boiling point and boiling range</b>	No data available	
<b>Flammability</b>	No data available	
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Flash point</b>	> 61 °C	CC (closed cup)
<b>Autoignition temperature</b>	No data available	
<b>Decomposition temperature</b>		None known
<b>pH</b>	No data available	
<b>pH (as aqueous solution)</b>	No data available	
<b>Kinematic viscosity</b>	No data available	
<b>Dynamic viscosity</b>	approx 10 - 20 Pa.s	Spindle 3 @ 100 rpm @ 23 °C
<b>Water solubility</b>	Reacts with water.	
<b>Solubility(ies)</b>	No data available	
<b>Partition coefficient</b>	No data available	
<b>Vapour pressure</b>	No data available	
<b>Relative density</b>	1.4 - 1.6	
<b>Bulk Density</b>	No data available	
<b>Density</b>	ca. 1.5 g/cm <sup>3</sup>	
<b>Relative vapour density</b>	No data available	
<b>Particle characteristics</b>	No data available	

# SAFETY DATA SHEET

BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING  
Supersedes Date: 07-Sep-2022

Revision date 10-May-2024  
Revision Number 1.01

**Particle Size** No information available  
**Particle Size Distribution** No information available

## 9.2. Other information

**Solid content (%)** No information available  
**VOC content** No data available

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

**Reactivity** Product cures with moisture.

### 10.2. Chemical stability

**Stability** Stable under normal conditions.

### Explosion data

**Sensitivity to mechanical impact** None.  
**Sensitivity to static discharge** None.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

### 10.4. Conditions to avoid

**Conditions to avoid** Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

### 10.5. Incompatible materials

**Incompatible materials** None known based on information supplied.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** None under normal use conditions. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

#### **Product Information**

**Inhalation** Based on available data, the classification criteria are not met.

**Eye contact** Based on available data, the classification criteria are not met.

**Skin contact** Based on available data, the classification criteria are not met. May cause sensitisation in

# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
**Supersedes Date:** 07-Sep-2022

**Revision date** 10-May-2024  
**Revision Number** 1.01

susceptible persons.

## Ingestion

Based on available data, the classification criteria are not met.

## Symptoms related to the physical, chemical and toxicological characteristics

### Symptoms

No information available.

### Acute toxicity

### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (dermal)** 11,543.80 mg/kg  
**ATEmix (inhalation-vapour)** 863.60 mg/l

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone	>5000 mg/kg (Rattus)	-	-
Bis(2-propylheptyl)phthalate	LD50 > 5000 mg/kg (Rattus) OECD 401	LD50 > 2000 mg/kg (Oryctolagus cuniculus) OECD 402	> 20.5 mg/L ( Rat ) 1 h
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
Diisononyl 1,2-cyclohexanedicarboxylate	LD50 >5000 mg/kg Rat (OECD 423)	LD50 >2000 mg/Kg (Rattus) (OECD 402)	-
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L ( Rattus ) 4 h
N-(3-(trimethoxysilyl)propyl)eth ylenediamine	LD50 = 2295 mg/kg (Rattus) EPA OPPTS 870.1100	LD50 > 2000 mg/kg (Oryctolagus cuniculus) EPA OPPTS 870.1200	1.49 - 2.44 mg/L ( Rat ) 4 h
Octadecyl 3-(3',5'-di-tert-butyl-4'-hydroxyp henyl)propionate	>5000 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus cuniculus)	>1800 mg/L (Rattus) 4 h
Quartz (fine fraction)	>2000 mg/kg (Rattus)	-	-
Bis(2,2,6,6-tetramethyl-4-piperi dyl) sebacate	LD50 (Rattus) > 2000 mg/kg OECD 423	LD50 (Rattus) > 3 170 mg/kg OECD 402	=500 mg/m <sup>3</sup> (Rattus) 4 h
Dioctyltin oxide	=2500 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus) OECD 402	-
Ethyl silicate	LD50 > 2500 mg/kg (Rattus) OECD 423	= 5878 mg/kg (Oryctolagus cuniculus) = 6300 µL/kg (Oryctolagus cuniculus)	= 10 mg/L ( Rat male ) 4 h > 16.8 mg/L ( Rat female ) 4 h
Benzenepropanoic acid, 3-(1,1-dimethylethyl)-4-hydroxy -5-methyl-, 1,2-ethanediylbis(oxy-2,1-etha nediyl) ester	LD50 >7000 mg/kg Rat	LD50 >2000 mg/Kg Rat	-
Ethanol	6200 - 15000 mg/kg (Rattus) OECD 401	-	=124.7 mg/L (Rattus) 4 h
Methyl alcohol	=2500 mg/kg (Rattus)	200-1000 mg/kg (Oryctolagus cuniculus)	=22500 ppm (Rattus) 8 h = 64000 ppm (Rattus) 4 h
Methyl silicate	LD50 > 2500 mg/kg	= 17 g/kg (Oryctolagus cuniculus) = 17 mL/kg (Oryctolagus cuniculus)	LC 50 = 0.392 mg/l

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
Supersedes Date: 07-Sep-2022

Revision date 10-May-2024  
Revision Number 1.01

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Quartz (fine fraction) (14808-60-7)					
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		24 hours	Non-irritant

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			Eye Damage

**Respiratory or skin sensitisation** May produce an allergic reaction. OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data. May cause sensitisation in susceptible persons.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

Component Information		
Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
**Supersedes Date:** 07-Sep-2022

**Revision date** 10-May-2024  
**Revision Number** 1.01

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Results
OECD Test No. 414: Pre-natal Development Toxicity Study	Rat, Rabbit	reproductive toxicant

**STOT - single exposure** Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)  
 Dioctyltin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Oral	5 mg/kg	28 days	0.3 - 0.5 mg/kg bw/d May cause damage to the following organs: Immune system

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Sub-chronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapour		90 days	0.058 NOAEL

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)  
 Dioctyltin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rat Rabbit			28 days	0.3 -0.5 mg/kg bw/d

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmondesmus subspicatus)	CL50 (96h)>10000mg/ L (Oncorhynchus)	-	CE50 (48h) >1000 mg/L Daphnia Magna		



# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
**Supersedes Date:** 07-Sep-2022

**Revision date** 10-May-2024  
**Revision Number** 1.01

		mykiss)				
Bis(2-propylheptyl)phthalate 53306-54-0	EC50 (72h) > 100 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) > 10000 mg/l (Danio rerio) OECD 203	-	EC50 (48h) > 100 mg/l (Daphnia magna) EU Method C.2		
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
Diisononyl 1,2-cyclohexanedicarboxylate 166412-78-8	EC50 >100mg/L (Scenedesmus subspicatus) Static (OECD 201)	LC50 (96h) >100mg/L (Brachydanio rerio) Static (OECD 203)	-	EC50 (48h) >100 mg/L (Daphnia magna) Static (OECD 202)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-	LC50 (96H) =597 mg/L (Danio rerio)Semi-static	-	EC50 (48h) =81mg/L Daphnia magna Static		
Octadecyl 3-(3',5'-di-tert-butyl-4'-hydroxyphenyl)propionate 2082-79-3	EC50: >30mg/L (72h, Desmodesmus subspicatus)	LC50: >100mg/L (96h, Lepomis macrochirus)	-	EC50: >100mg/L (24h, Daphnia magna)		
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	EC50 72Hr 0.705 mg/l (Pseudokirchneriella subcapitata)	LC50 (96h) = 5.29 mg/l (Oryzias latipes)	-	LC50 48Hr 8.58 mg/l (Daphnia magna)		
Diocetyl tin oxide 870-08-6	EC50 (3hr) >1.000 mg/l (bacteria) (Activated Sludge, Respiration Inhibition Test)	LC50 (96hr) >0,09 mg/l (Brachydanio rerio (zebra)) (Acute Toxicity Test)	-	EC50 (48Hr) >0,21 mg/l (Daphnia magna (Daphnia magna)) (Daphnia sp. Acute Immobilisation Test)		
Ethyl silicate 78-10-4	EC 50 (72h) > 100 mg/L (Pseudokirchneriella subcapitata) OECD 201	LC50 (96h) > 245 mg/L (Danio rerio) EU Method C.1	-	-		
Benzenepropanoic acid, 3-(1,1-dimethylethyl)-4-hydroxy-5-methyl-, 1,2-ethanediylobis(oxy-2,1-ethanediy) ester 36443-68-2	EC50 (72h) >100 mg/L Algae (Desmodesmus subspicatus) Static	LC50 (96h) 43 mg/L (Lepomis macrochirus) OECD 203	-	LD50 (48h) >100 mg/L Daphnia magna		
Ethanol 64-17-5	EC50 72hr 12.9 g/l (Selenastrum capricornutum) NOEC 3.24 g/l (Skeletonema costatum)	LC50: >100mg/L (96h, Pimephales promelas)	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	LC50: (48h, Daphnia magna) EC50: =12.34 mg/L		
Methyl alcohol	-	LC50: >100mg/L	EC50 = 39000	-		

# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
**Supersedes Date:** 07-Sep-2022

**Revision date** 10-May-2024  
**Revision Number** 1.01

67-56-1		(96h, Pimephales promelas) LC50: 18 - 20mg/L (96h, Oncorhynchus mykiss) LC50: =28200mg/L (96h, Pimephales promelas) LC50: 13500 - 17600mg/L (96h, Lepomis macrochirus) LC50: 19500 - 20700mg/L (96h, Oncorhynchus mykiss)	mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min			
---------	--	---	--	--	--	--

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Exposure time	Value	Results
OECD Test No. 303: Simulation Test - Aerobic Sewage Treatment -- A: Activated Sludge Units; B: Biofilms	28 days	Total organic carbon (TOC)	24 % Moderate

Dioctyltin oxide (870-08-6)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	755 hours	biodegradation	Not readily biodegradable 2 %

## 12.3. Bioaccumulative potential

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
Limestone	0.9
Bis(2-propylheptyl)phthalate	>6
Poly[oxy(methyl-1,2-ethanediy)], .alpha.-[3-(dimethoxymethylsilyl)propyl]-.omega.-[3-(dimethoxymethylsilyl)propoxy-]	1.8
Trimethoxyvinylsilane	1.1
Diisononyl 1,2-cyclohexanedicarboxylate	10
N-(3-(trimethoxysilyl)propyl)ethylenediamine	-0.3
Octadecyl 3-(3',5'-di-tert-butyl-4'-hydroxyphenyl)propionate	13.5
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	0.35
Dioctyltin oxide	6
Ethyl silicate	3.18
Benzenepropanoic acid,	8.2

# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
Supersedes Date: 07-Sep-2022

Revision date 10-May-2024  
Revision Number 1.01

3-(1,1-dimethylethyl)-4-hydroxy-5-methyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester	
Ethanol	-0.35
Methyl alcohol	-0.77

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Bis(2-propylheptyl)phthalate	The substance is not PBT / vPvB
Trimethoxyvinylsilane	The substance is not PBT / vPvB
Diisononyl 1,2-cyclohexanedicarboxylate	The substance is not PBT / vPvB
Titanium dioxide	The substance is not PBT / vPvB
N-(3-(trimethoxysilyl)propyl)ethylenediamine	The substance is not PBT / vPvB
Octadecyl 3-(3',5'-di-tert-butyl-4'-hydroxyphenyl)propionate	The substance is not PBT / vPvB
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	The substance is not PBT / vPvB
Diocetyl tin oxide	The substance is not PBT / vPvB
Ethyl silicate	The substance is not PBT / vPvB
Benzenepropanoic acid, 3-(1,1-dimethylethyl)-4-hydroxy-5-methyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester	The substance is not PBT / vPvB
Ethanol	The substance is not PBT / vPvB
Methyl alcohol	The substance is not PBT / vPvB
Methyl silicate	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Waste from residues/unused products** Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

**Contaminated packaging** Handle contaminated packages in the same way as the product itself.

**European Waste Catalogue** 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

**Other information** Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

### Land transport (ADR/RID)

**14.1 UN number or ID number** Not regulated

**14.2 UN proper shipping name** -

**14.3 Transport hazard class(es)** Not regulated

# SAFETY DATA SHEET

BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING  
Supersedes Date: 07-Sep-2022

Revision date 10-May-2024  
Revision Number 1.01

14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special precautions for user  
Special Provisions None

## IMDG

14.1 UN number or ID number Not regulated  
14.2 UN proper shipping name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Marine pollutant NP  
14.6 Special precautions for user  
Special Provisions None

14.7 Maritime transport in bulk  
according to IMO instruments  
Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

## Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated  
14.2 UN proper shipping name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special precautions for user  
Special Provisions None

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

#### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Diocetyl tin oxide	870-08-6	20.

#### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

#### Export Notification requirements

This product contains substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals

Chemical name	European Export/Import Restrictions per (EC) 649/2012 - Annex Number
Diocetyl tin oxide	I.1

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
---------------	--------------------------------	--------------------------------

# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
Supercedes Date: 07-Sep-2022

Revision date 10-May-2024  
Revision Number 1.01

Methyl alcohol - 67-56-1	500	5000
--------------------------	-----	------

## Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

## Persistent Organic Pollutants

Not applicable

## REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### **Full text of H-Statements referred to under section 3**

H226 - Flammable liquid and vapour  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H332 - Harmful if inhaled  
H335 - May cause respiratory irritation  
H361f - Suspected of damaging fertility  
H400 - Very toxic to aquatic life  
H411 - Toxic to aquatic life with long lasting effects

#### **Notes relating to the identification, classification and labelling of substances**

**Note V:** If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

**Note W:** It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung

#### **Notes relating to the classification and labelling of mixtures**

**Note 10:** The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

#### **Legend SECTION 8: Exposure controls/personal protection**

# SAFETY DATA SHEET

**BOSTIK WATERSTOP FLEXIBLE WATERPROOF COATING**  
Supersedes Date: 07-Sep-2022

Revision date 10-May-2024  
Revision Number 1.01

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	SK*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	On basis of test data
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

## Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)  
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA\_RAC)  
European Chemicals Agency (ECHA) (ECHA\_API)  
Environmental Protection Agency  
Acute Exposure Guideline Level(s) (AEGL(s))  
International Uniform Chemical Information Database (IUCLID)  
National Institute of Technology and Evaluation (NITE)  
NIOSH (National Institute for Occupational Safety and Health)  
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications  
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme  
Organisation for Economic Co-operation and Development Screening Information Data Set

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 10-May-2024

**Revision note** SDS sections updated:

**Training Advice** No information available

**Further information** No information available

## Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1272/2008 and Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**