

## BIG BOY METAL FILLER HIGH TEMPERATURE BIG81

Printing: 26/04/2021

Date of compilation: 26/04/2021

Version: 1

### SECTION 1: IDENTIFICATION OF SUBSTANCE/MIXTURE AND OF COMPANY/UNDERTAKING

#### 1.1. Product identifier

Big Boy Metal Filler High Temperature 250ml  
Other means of identification: Non-applicable

ref: BIG81

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant uses: Car repair. For professional user/industrial user only.  
Uses advised against: All uses not specified in this section or in Section 7.3

#### 1.3. Details of the supplier of the safety data sheet

Silverhook Ltd.  
Unit 14 Bates Road  
Harold Wood, London, England  
RM3 0JH  
Tel.: + 44 (0) 1708330500  
Fax.: + 44 (0) 1708330504  
Email: [522@silverhook.co.uk](mailto:522@silverhook.co.uk)  
Responsible person E-mail: 522@silverhook.co.uk

#### 1.4. Emergency telephone number

+ 44 (0) 1708330500 (during office hours)

### SECTION 2: HAZARD IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### GB CLP Regulation

Classification of this product has been carried out in accordance with GB CLP Regulation.  
Eye Irrit. 2: Eye irritation, Category 2, H319  
Flam. Liq. 3: Flammable liquids, Category 3, H226  
Repr. 2: Reproductive toxicity, Category 2, H361  
Skin Irrit. 2: Skin irritation, Category 2, H315  
STOT RE 1: Specific target organ toxicity, repeated exposure, Category 1, H372

#### 2.2. Label elements

##### GB CLP Regulation

Danger



##### Hazard statements

Eye Irrit. 2: H319 - Causes serious eye irritation.  
Flam. Liq. 3: H226 - Flammable liquid and vapour.  
Repr. 2: H361 - Suspected of damaging fertility or the unborn child.  
Skin Irrit. 2: H315 - Causes skin irritation.  
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.

##### Precautionary statements

P201: Obtain special instructions before use.  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352: IF ON SKIN: Wash with plenty of soap and water.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313: IF exposed or concerned: Get medical advice/attention.  
P370+P378: In case of fire: Use ABC powder extinguisher to put it out.  
P501: Dispose of the contents and/or its container in line with regulations on dangerous waste or packaging and waste packaging respectively.

#### 2.3. Other hazards

Non-applicable.

### SECTION 3: COMPOSITION/ INFORMATION ON INGREDIENTS

#### 3.1. Substance

## BIG BOY METAL FILLER HIGH TEMPERATURE BIG81

Non-applicable.

### 3.2. Mixture

**Chemical description:** Mixture composed of chemical products

**Components:**

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 100-42-5	<b>styrene</b> Acute Tox. 4: H332; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 1: H372 - Danger 	10 - <25 %
CAS: 13463-67-7	<b>Titanium dioxide (aerodynamic diameter ≤ 10 µm)</b> Carc. 2: H351 - Warning 	<1 %

To obtain more information on the hazards of the substances consult Sections 11, 12 and 16.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

### 4.2. Most important symptoms and effects, both acute and delayed

Acute and delayed effects are indicated in Sections 2 and 11.

### 4.3. Indication of any immediate medical attention and special treatment needed

Non-applicable.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing media

**Suitable extinguishing media**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).

**Unsuitable extinguishing media**

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

### 5.2. Special hazards arising from the substance or mixture

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

### 5.3. Advice for firefighters

## **BIG BOY METAL FILLER HIGH TEMPERATURE BIG81**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

### **Additional provisions**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See Section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

### **6.2. Environmental precautions**

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

### **6.3. Methods and material for containment and cleaning up**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult Section 13.

### **6.4. Reference to other sections**

See Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

A. - Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (Section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B. - Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in The Equipment and Protective Systems Intended for Use in Potentially Explosive Atmospheres Regulations 2016 and with the minimum requirements for protecting the security and health of workers under the selection criteria of The Dangerous Substances and Explosive Atmospheres Regulations 2002, 2002 No. 2776. Consult section 10 for conditions and materials that should be avoided.

C. - Technical recommendations to prevent ergonomic and toxicological risks

**PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT.** Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See Section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D. - Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See Subsection 6.3)

### **7.2. Conditions for safe storage, including any incompatibilities**

A. - Technical measures for storage

Minimum Temp.: 15°C

Maximum Temp.: 25°C

**BIG BOY METAL FILLER HIGH TEMPERATURE BIG81**

Maximum time: 12 Months

B. - General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see Subsection 10.5

**7.3. Specific end use(s)**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

Substances whose occupational exposure limits have to be monitored in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Occupational exposure limits		
	WEL (8h)	100 ppm	430 mg/m <sup>3</sup>
styrene CAS: 100-42-5	WEL (15 min)	250 ppm	1080 mg/m <sup>3</sup>
Titanium dioxide (aerodynamic diameter ≤ 10 µm) CAS: 13463-67-7	WEL (8h)		4 mg/m <sup>3</sup>
	WEL (15 min)		

**8.2. Exposure controls**

A. - General security and hygiene measures in the work place

In accordance with the order of importance to control professional exposure it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have UKCA marking. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see Subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B. - Respiratory protection

Pictogram	PPE	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (Filter type: A)	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C. - Specific protection for the hands

Pictogram	PPE	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material cannot be calculated in advance with total reliability and has therefore to be checked prior to the application.

D. - Ocular and facial protection

Pictogram	PPE	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E. - Body protection

**BIG BOY METAL FILLER HIGH TEMPERATURE BIG81**

Pictogram	PPE	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	Replace boots at any sign of deterioration.

F. - Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see Subsection 7.1.D

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20°C: Liquid  
Appearance: Viscous  
Colour:  Grey  
Odour: Characteristic  
Odour threshold: Non-applicable \*

**Volatility:**

Boiling point at atmospheric pressure: 146°C  
Vapour pressure at 20°C: 609 Pa  
Vapour pressure at 50°C: 3230.82 Pa (3.23 kPa)  
Evaporation rate at 20°C: Non-applicable \*

**Product description:**

Density at 20°C: 1830 kg/m<sup>3</sup>  
Relative density at 20°C: 1.83  
Dynamic viscosity at 20°C: Non-applicable \*  
Kinematic viscosity at 20°C: Non-applicable \*  
Kinematic viscosity at 40°C: >20.5 cSt  
Concentration: Non-applicable \*  
pH: Non-applicable \*  
Vapour density at 20°C: Non-applicable \*  
Partition coefficient n-octanol/water 20°C: Non-applicable \*  
Solubility in water at 20°C:  
Solubility properties: Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**BIG BOY METAL FILLER HIGH TEMPERATURE BIG81**

Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
<b>Flammability:</b>	
Flash Point:	32°C
Heat of combustion:	Non-applicable *
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	345°C
Lower flammability limit:	Not available
Upper flammability limit:	Not available
<b>Explosive:</b>	
Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *

**9.2. Other information**

Surface tension at 20°C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1. Reactivity**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See Section 7.

**10.2. Chemical stability**

Chemically stable under the conditions of storage, handling and use.

**10.3. Possibility of hazardous reactions**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4. Conditions to avoid**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5. Incompatible materials**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases. Can react violently

**10.6. Hazardous decomposition products**

See Subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1. Information on toxicological effects**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

**BIG BOY METAL FILLER HIGH TEMPERATURE BIG81**

- A - Ingestion (acute effect):  
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see Section 3.  
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B - Inhalation (acute effect):  
 - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see Section 3.  
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see Section 3.
- C - Contact with the skin and the eyes (acute effect):  
 - Contact with the skin: Produces skin inflammation.  
 - Contact with the eyes: Produces eye damage after contact.
- D - CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):  
 - Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see Section 3.  
     IARC: styrene (2A); Talc (3); Solvent naphtha (petroleum), light arom., < 0.1 % EC 200-753-7 (3); 2,6-di-tert-butyl-p- cresol (3); Titanium dioxide (aerodynamic diameter ≤ 10 µm) (2B); Quartz (1 %< RCS < 10%) (1); styrene (2A)  
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see Section 3.  
 - Reproductive toxicity: Suspected of damaging fertility or the unborn child
- E - Sensitizing effects:  
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see Section 3.  
 - Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see Section 3.
- F - Specific target organ toxicity (STOT) - single exposure:  
 Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see Section 3.
- G - Specific target organ toxicity (STOT)-repeated exposure:  
 - Specific target organ toxicity (STOT)-repeated exposure: Serious health effects in the case of prolonged consumption, including death, serious functional disorders or morphological changes of toxicological importance.  
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see Section 3.
- H - Aspiration hazard:  
 Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see Section 3.

**Other information**

CAS 13463-67-7 Titanium dioxide (aerodynamic diameter ≤ 10 µm): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm

**Specific toxicology information on the substances**

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
styrene CAS: 100-42-5	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	12 mg/L (4 h)	Rat
Titanium dioxide (aerodynamic diameter ≤ 10 µm) CAS: 13463-67-7	LD50 oral	10000 mg/kg	Rat
	LD50 dermal	10000 mg/kg	Rabbit
	LC50 inhalation	>5 mg/L	

The experimental information related to the eco-toxicological properties of the product itself is not available

**BIG BOY METAL FILLER HIGH TEMPERATURE BIG81**

**SECTION 12: ECOLOGICAL INFORMATION**

**12.1. Toxicity**

Not available

**12.2. Persistence and degradability**

Not available

**12.3. Bioaccumulative potential**

Not available

**12.4. Mobility in soil**

Identification	Absorption/desorption		Volatility	
styrene CAS: 100-42-5	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	3.21E-2 N/m (25 °C)	Moist soil	Non-applicable

**12.5. Results of PBT and vPvB assessment**

Non-applicable.

**12.6. Other adverse effects**

Not described.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1. Waste treatment methods**

**Waste management (disposal and evaluation)**

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

**Regulations related to waste management**

In accordance with Annex II of UK UK REACH the provisions related to waste management are stated UK legislation: The Waste Regulations 2011.

**SECTION 14: TRANSPORT INFORMATION**

Transport of dangerous goods by land  
With regard to ADR 2021 and RID 2021

**14.1. UN Number**

UN3269

**14.2. UN proper shipping name**

Polyester resin kit, liquid base material

**14.3. Transport hazard class(es)**

3

Labels: 3

**14.4. Packing group**

III

**14.5. Environmental hazards**

No.

**14.6. Special precautions for user**

Physico-chemical properties: See Section 9

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Non-applicable



Transport of dangerous goods by sea  
With regard to IMDG 39-18

**14.1. UN Number**

UN3269

**14.2. UN proper shipping name**

Polyester resin kit, liquid base material

**14.3. Transport hazard class(es)**

3

Labels: 3

**14.4. Packing group**

III

**14.5. Marine pollutant**

No

**14.6. Special precautions for user**

Special regulations	340, 236
EmS Codes	F-E, S-D
Physico-Chemical properties:	See Section 9
Limited quantities	5L



## BIG BOY METAL FILLER HIGH TEMPERATURE BIG81

Segregation group Non-applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Non-applicable.

Transport of dangerous goods by air  
With regard to IATA/ICAO 2021

### 14.1. UN Number

UN3269

### 14.2. UN proper shipping name

Polyester resin kit, liquid base material

### 14.3. Transport hazard class(es)

3

Labels: 3

### 14.4. Packing group

III

### 14.5. Environmental hazards

No

### 14.6. Special precautions for user

Physico-chemical properties: See Section 9

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Non-applicable.



## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **Specific provisions in terms of protecting people or the environment**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

#### **Other legislation**

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019.

Control of Substances Hazardous to Health Regulations 2002 (as amended) EH40/2005 Workplace exposure limits.

## SECTION 16: OTHER INFORMATION

#### **Legislation related to safety data sheets**

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

#### **Texts of the legislative phrases mentioned in Section 2**

H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H361: Suspected of damaging fertility or the unborn child.

H372: Causes damage to organs through prolonged or repeated exposure.

#### **Texts of the legislative phrases mentioned in Section 3**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in Section 3

#### **GB CLP Regulation**

Acute Tox. 4: H332 - Harmful if inhaled.

Carc. 2: H351 - Suspected of causing cancer (Inhalation).

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Repr. 2: H361d - Suspected of damaging the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.

#### **Advice related to training**

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### **Principal bibliographical sources**

<http://echa.europa.eu> <http://eur-lex.europa.eu>

#### **Abbreviations and acronyms**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

**BIG BOY METAL FILLER HIGH TEMPERATURE BIG81**

Disclaimer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.