



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**BOSTIK PRO SEALANT FP403 HYBRID GREY**  
Supersedes Date: 14-Jun-2022

Revision date 14-Jun-2022  
Revision Number 1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product Name BOSTIK PRO SEALANT FP403 HYBRID GREY

Pure substance/mixture Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

United Kingdom +44 (1785) 272650  
Ireland **NPIC - National Poison Information Centre**  
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)  
Healthcare Professionals: +353 (01) 8092566 (24 hour service)  
Europe 112

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin sensitisation	Category 1A - (H317)
Chronic aquatic toxicity	Category 3 - (H412)

### 2.2. Label elements

Contains Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate, N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine, Trimethoxyvinylsilane, Dioctyltinbis(acetylacetonate), N-(3-(trimethoxysilyl)propyl)ethylenediamine

# SAFETY DATA SHEET

BOSTIK PRO SEALANT FP403 HYBRID GREY  
Supersedes Date: 14-Jun-2022

Revision date 14-Jun-2022  
Revision Number 1



**Signal word**  
Warning

## Hazard statements

H317 - May cause an allergic skin reaction.  
H412 - Harmful to aquatic life with long lasting effects.

## EU Specific Hazard Statements

EUH212 - Warning! Hazardous respirable dust may be formed when used. Do not breathe dust

## Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P261 - Avoid breathing fumes  
P280 - Wear protective gloves  
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap  
P501 - Dispose of contents/ container to an approved waste disposal plant

## 2.3. Other hazards

Harmful to aquatic life.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Titanium dioxide	236-675-5	13463-67-7	1 - <5	[C]	-	01-2119489379-17-XXXX
Trimethoxyvinylsilane	220-449-8	2768-02-7	1- <2.5	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	01-2119513215-52-XXXX
Diocetyl tinbis(acetylacetonate)	483-270-6	54068-28-9	0.1 - <1	STOT SE 2 (H371) Skin Sens. 1 (H317)	Skin Sens. 1 :: C>=5%	01-0000020199-67-XXXX

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT FP403 HYBRID GREY**  
Supersedes Date: 14-Jun-2022

Revision date 14-Jun-2022  
Revision Number 1

N-(3-(trimethoxysilyl)propyl)ethylenediamine	217-164-6	1760-24-3	0.1 - <1	Eye Dam. 1 (H318) Skin Sens. 1 (H317) Acute Tox. 4 (H332) STOT SE 3 (H335)	-	01-2119970215-39-XXXX
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	1065336-91-5	0.1 - <1	Skin Sens. 1A (H317) Repr. 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	-	01-2119491304-40-XXXX
N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine	221-336-6	3069-29-2	0.1 - <1	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1A (H317)	-	01-2119963926-21-xxxx

## Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	IF exposed or concerned: Get medical advice/attention. Remove to fresh air.
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
<b>Skin contact</b>	Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** Itching. Rashes. Hives.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Note to doctors** May cause sensitisation in susceptible persons. Treat symptomatically.

## SECTION 5: Firefighting measures

# SAFETY DATA SHEET

BOSTIK PRO SEALANT FP403 HYBRID GREY  
Supersedes Date: 14-Jun-2022

Revision date 14-Jun-2022  
Revision Number 1

## 5.1. Extinguishing media

**Suitable Extinguishing Media** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** Full water jet.

## 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** Product is or contains a sensitiser. May cause sensitisation by skin contact.

**Hazardous combustion products** Carbon oxides. Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Silicon dioxide.

## 5.3. Advice for firefighters

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**For emergency responders** Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

**Environmental precautions** See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

### 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT FP403 HYBRID GREY**  
Supersedes Date: 14-Jun-2022

Revision date 14-Jun-2022  
Revision Number 1

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

**Recommended storage temperature** Keep at temperatures between 10 and 35 °C.

## 7.3. Specific end use(s)

**Specific use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**Exposure Limits** This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Dioctyltinbis(acetylacetonate) 54068-28-9	-	TWA: 0.1 mg/m <sup>3</sup> STEL: 0.2 mg/m <sup>3</sup> Sk*

**Derived No Effect Level (DNEL)** No information available

### Derived No Effect Level (DNEL) Titanium dioxide (13463-67-7)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

### Trimethoxyvinylsilane (2768-02-7)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	27,6 mg/m <sup>3</sup>	
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	

### Dioctyltinbis(acetylacetonate) (54068-28-9)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	0.07 mg/kg bw/d	

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT FP403 HYBRID GREY**  
**Supersedes Date:** 14-Jun-2022

**Revision date** 14-Jun-2022  
**Revision Number** 1

Long term Systemic health effects worker	Inhalation	84 mg/m <sup>3</sup>	
Short term Systemic health effects worker	Inhalation	84 mg/m <sup>3</sup>	
Long term Short term Local health effects worker	Inhalation	0.091 mg/m <sup>3</sup>	

## **N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)**

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	35.5 mg/m <sup>3</sup>	
worker Systemic health effects Long term	Dermal	5 mg/kg bw/d	

## **Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)**

### **N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)**

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	12 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	1.7 mg/kg bw/d	

## **Derived No Effect Level (DNEL)**

### **Titanium dioxide (13463-67-7)**

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

### **Trimethoxyvinylsilane (2768-02-7)**

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m <sup>3</sup>	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

## **N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)**

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects	Oral	2.5 mg/kg bw/d	

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT FP403 HYBRID GREY**  
**Supersedes Date:** 14-Jun-2022

**Revision date** 14-Jun-2022  
**Revision Number** 1

Long term Consumer Systemic health effects Long term	Inhalation	8.7 mg/m <sup>3</sup>	
Consumer Systemic health effects Long term	Dermal	2.5 mg/kg bw/d	

<b>N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	2.9 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	0.83 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.83 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.

<b>Predicted No Effect Concentration (PNEC)</b>	
<b>Titanium dioxide (13463-67-7)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

<b>Trimethoxyvinylsilane (2768-02-7)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

<b>Diocetyl tinbis(acetylacetonate) (54068-28-9)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	26 µg/l
Marine water	2.6 µg/l
Freshwater - intermittent	260 µg/l
Sewage treatment plant	1 mg/l
Freshwater sediment	0.155 mg/kg dry weight
Marine sediment	0.0155 mg/kg dry weight
Soil	0.0158 mg/kg dry weight

<b>N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.062 mg/l
Marine water	0.0062 mg/l
Sewage treatment plant	25 mg/l

<b>N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.062 mg/l
Marine water	0.006 mg/l

# SAFETY DATA SHEET

BOSTIK PRO SEALANT FP403 HYBRID GREY  
Supersedes Date: 14-Jun-2022

Revision date 14-Jun-2022  
Revision Number 1

Sewage treatment plant	25 mg/l
Freshwater sediment	0.24 mg/kg dry weight
Marine sediment	0.024 mg/kg dry weight
Soil	0.01 mg/kg dry weight

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

**Eye/face protection** Tight sealing safety goggles.

**Hand protection** Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

**Skin and body protection** Suitable protective clothing.

**Environmental exposure controls** No information available.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Solid
<b>Appearance</b>	Paste
<b>Colour</b>	Grey
<b>Odour</b>	Characteristic.
<b>Odour threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>Melting point / freezing point</b>	No data available	None known
<b>Initial boiling point and boiling range</b>	No data available	None known
<b>Flammability</b>	No data available	None known
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Flash point</b>	> 60 °C	None known
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>		None known
<b>pH</b>	No data available	Reacts with water
<b>pH (as aqueous solution)</b>	No data available	None known
<b>Kinematic viscosity</b>	> 21	None known
<b>Dynamic viscosity</b>	No data available	
<b>Water solubility</b>	No data available	None known
<b>Solubility(ies)</b>	No data available	None known
<b>Partition coefficient</b>	No data available	None known
<b>Vapour pressure</b>	No data available	None known
<b>Relative density</b>	No data available	None known
<b>Bulk Density</b>	No data available	
<b>Liquid Density</b>	1.48	
<b>Relative vapour density</b>	No data available	None known
<b>Particle characteristics</b>		
<b>Particle Size</b>	No information available	
<b>Particle Size Distribution</b>	No information available	

### 9.2. Other information

#### VOC Content (%)

9.2.1. Information with regards to physical hazard classes



# SAFETY DATA SHEET

**BOSTIK PRO SEALANT FP403 HYBRID GREY**  
Supercedes Date: 14-Jun-2022

Revision date 14-Jun-2022  
Revision Number 1

Not applicable

9.2.2. Other safety characteristics  
No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** Product cures with moisture.

### 10.2. Chemical stability

**Stability** Stable under normal conditions.

### Explosion data

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** None.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

### 10.4. Conditions to avoid

**Conditions to avoid** Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

### 10.5. Incompatible materials

**Incompatible materials** None known based on information supplied.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

#### Product Information

**Inhalation** Based on available data, the classification criteria are not met.

**Eye contact** Based on available data, the classification criteria are not met.

**Skin contact** May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components).

**Ingestion** Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Itching. Rashes. Hives.

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT FP403 HYBRID GREY**  
**Supersedes Date:** 14-Jun-2022

**Revision date** 14-Jun-2022  
**Revision Number** 1

## Acute toxicity

### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (inhalation-vapour)** 926.1827 mg/l

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L ( Rattus ) 4 h
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
Diocetylbinbis(acetylacetonate)	LD50 =2500 mg/kg (Rattus)	LD50 >2000 mg/kg (Rattus)	= 5.1 mg/L ( Rat ) 4 h
N-(3-(trimethoxysilyl)propyl)ethylenediamine	=2295 mg/kg (Rattus)	>2000 mg/Kg (Rattus)	LC50 4H (Aerosol)1.5 - 2.44 mg/L air
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LD50 = 3230 mg/Kg (Rat) OECD 401	LD50 >3170 mg/Kg (Rat)	-
N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine	=200 - 2000 mg/Kg (Rattus) (OECD 401)	>5000 mg/Kg (Oryctolagus cuniculus) (OECD 402)	> 5.2 mg/L ( Rat ) 4 h

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			irritant

### Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye		24 hours	Non-irritant

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT FP403 HYBRID GREY**  
**Supersedes Date:** 14-Jun-2022

**Revision date** 14-Jun-2022  
**Revision Number** 1

Acute Eye Irritation/Corrosion					
--------------------------------	--	--	--	--	--

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit				Eye Damage

**Respiratory or skin sensitisation** May cause sensitisation by skin contact.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse	Dermal	Not a skin sensitiser

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation, Buehler test	Guinea pig	Dermal	sensitising

Diocetyl tinbis(acetylacetonate) (54068-28-9)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay		Dermal	> 5 % sensitising

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig		Sensitizing

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

Component Information

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Not Classifiable

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT FP403 HYBRID GREY**  
**Supersedes Date:** 14-Jun-2022

**Revision date** 14-Jun-2022  
**Revision Number** 1

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Sub-chronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapour		90 days	0.058 NOAEL

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
Diocetyl tinbis(acetylacetonate) 54068-28-9	-	LC50 (96h) =86 mg/L (Static)	-	EC50 (48h) =58.6 mg/L (Daphnia magna)		
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-	LC50 (96H) =597 mg/L (Danio rerio)Semi-static	-	EC50 (48h) =81mg/L Daphnia magna Static		
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate 1065336-91-5	EC50 (72 h) 1,68 mg/l (growth rate), Desmodesmus subspicatus (OECD 201)	LC50 (96 h) 0,9 mg/l, Brachydanio rerio (OECD 203)	-	-	1	1

### 12.2. Persistence and degradability

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT FP403 HYBRID GREY**  
Supersedes Date: 14-Jun-2022

Revision date 14-Jun-2022  
Revision Number 1

**Persistence and degradability** No information available.

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable

## 12.3. Bioaccumulative potential

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
Trimethoxyvinylsilane	1.1
N-(3-(trimethoxysilyl)propyl)ethylenediamine	-0.3
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	2.77

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does not apply
Trimethoxyvinylsilane	The substance is not PBT / vPvB
Diocetylbinbis(acetylacetonate)	The substance is not PBT / vPvB
N-(3-(trimethoxysilyl)propyl)ethylenediamine	The substance is not PBT / vPvB
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	The substance is not PBT / vPvB
N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Waste from residues/unused products** Dispose of waste in accordance with environmental legislation. Dispose of in accordance with local regulations.

**Contaminated packaging** Do not reuse empty containers. Handle contaminated packages in the same way as the product itself.

**European Waste Catalogue** 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances

# SAFETY DATA SHEET

BOSTIK PRO SEALANT FP403 HYBRID GREY  
Supersedes Date: 14-Jun-2022

Revision date 14-Jun-2022  
Revision Number 1

**Other information** Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

### Land transport (ADR/RID)

14.1 UN number or ID number Not regulated  
14.2 Proper Shipping Name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special Provisions None

### IMDG

14.1 UN number or ID number Not regulated  
14.2 Proper Shipping Name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Marine pollutant NP  
14.6 Special Provisions None  
14.7 Maritime transport in bulk according to IMO instruments Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated  
14.2 Proper Shipping Name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special Provisions None

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

##### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Diocetyl tin bis(acetylacetonate)	54068-28-9	20.

##### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

##### Export Notification requirements

This product contains substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT FP403 HYBRID GREY**  
Supersedes Date: 14-Jun-2022

Revision date 14-Jun-2022  
Revision Number 1

Chemical name	European Export/Import Restrictions per (EC) 689/2008 - Annex Number
Diocetyl tinbis(acetylacetonate)	I.1

**Ozone-depleting substances (ODS) regulation (EC) 1005/2009**  
Not applicable

**Persistent Organic Pollutants**  
Not applicable

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour  
H302 - Harmful if swallowed  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H332 - Harmful if inhaled  
H335 - May cause respiratory irritation  
H361f - Suspected of damaging fertility  
H371 - May cause damage to organs  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects

#### **Legend**

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

**Key literature references and sources for data**  
No information available

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT FP403 HYBRID GREY**  
**Supersedes Date:** 14-Jun-2022

**Revision date** 14-Jun-2022  
**Revision Number** 1

---

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 14-Jun-2022

**Indication of changes**

**Revision note** First time release.

**Training Advice** No information available

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**