



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**BOSTIK PRO SEALANT PU91 CONSTRUCTION  
POLYURETHANE BLACK**  
Supersedes Date: 13-Apr-2022

Revision date 18-May-2022

Revision Number 2

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** BOSTIK PRO SEALANT PU91 CONSTRUCTION POLYURETHANE BLACK

**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Sealant

**Uses advised against** Not to be used in production of toys or childcare articles

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** +44 (1785) 272650

**Ireland**

**NPIC - National Poison Information Centre**

Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)

Healthcare Professionals: +353 (01) 8092566 (24 hour service)

**Europe**

112

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

### 2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### **Signal word**

None

#### **Hazard statements**

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### **EU Specific Hazard Statements**

EUH204 - Contains isocyanates. May produce an allergic reaction

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION  
POLYURETHANE BLACK**  
Supersedes Date: 13-Apr-2022

Revision date 18-May-2022

Revision Number 2

EUH208 - Contains Aromatic Polyisocyanate & Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate & Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane. May produce an allergic reaction  
EUH210 - Safety data sheet available on request

## Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

## 2.3. Other hazards

Causes mild skin irritation. Harmful to aquatic life.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	271-091-4	68515-49-1	10 - <20	[I]	-	01-2119422347-43
Diisononyl phthalate	249-079-5	28553-12-0	5 - <10	[I]	-	01-2119430798-28-XXXX
3-butyl-1-[4-({4-[(butylcarbamoyl)amino]phenyl}methyl)phenyl]urea	416-600-4	--	1 - <5	Aquatic Chronic 4 (H413)	-	01-0000016345-72-xxxx
N,N-dibenzyliden polyoxypropylene diamine (polymer)	-	136855-71-5	1- <2.5	Skin Irrit. 2 (H315)	-	[7]
Carbon black	215-609-9	1333-86-4	1- <2.5	[C]	-	01-2119384822-32-XXXX
Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate	945-730-9	--	0.1 - <1	Aquatic Acute 1 (H400) Aquatic Chronic 3 (H412)	-	01-2119511174-52-xxxx
Aromatic Polyisocyanate	-	53317-61-6	0.1 - <1	Eye Irrit. 2 (H319) Skin Sens. 1 (H317)	-	[7]
Ethyl acetate	205-500-4	141-78-6	0.1 - <1	Eye Irrit. 2	-	01-2119475103-

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION  
POLYURETHANE BLACK**  
Supersedes Date: 13-Apr-2022

Revision date 18-May-2022

Revision Number 2

				(H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)		46-XXXX
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	1065336-91-5	0.01 - <0.1	Skin Sens. 1A (H317) Repr. 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	-	01-2119491304-40-XXXX
Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane	924-669-1	192526-20-8	0.01 - <0.1	Skin Sens. 1A (H317)	-	01-2120768758-32-XXXX

NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration

## Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand.
<b>Inhalation</b>	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
<b>Skin contact</b>	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	If swallowed, rinse mouth with water (only if the person is conscious).

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Prolonged contact may cause redness and irritation.
-----------------	---

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Note to doctors</b>	Treat symptomatically.
------------------------	------------------------

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
-------------------------------------	---

# SAFETY DATA SHEET

BOSTIK PRO SEALANT PU91 CONSTRUCTION  
POLYURETHANE BLACK  
Supersedes Date: 13-Apr-2022

Revision date 18-May-2022

Revision Number 2

**Unsuitable extinguishing media** Full water jet.

## 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** No information available.

**Hazardous combustion products** Carbon oxides. Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Hydrogen cyanide. Isocyanates. Hydrochloric Acid. Sulphur oxides.

## 5.3. Advice for firefighters

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation.

**For emergency responders** Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

**Environmental precautions** See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

### 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep away from food, drink and animal feedingstuffs. Protect from moisture.

**Recommended storage temperature** Keep at temperatures between 10 and 35 °C.

### 7.3. Specific end use(s)

**Specific use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION  
POLYURETHANE BLACK**  
Supersedes Date: 13-Apr-2022

Revision date 18-May-2022

Revision Number 2

Other information Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**Exposure Limits** This product contains carbon black in a non-respirable form. Inhalation of carbon black is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Polyvinyl chloride 9002-86-2	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Diisononyl phthalate 28553-12-0	-	TWA: 5 mg/m <sup>3</sup> STEL: 15 mg/m <sup>3</sup>
Carbon black 1333-86-4	-	TWA: 3.5 mg/m <sup>3</sup> STEL: 7 mg/m <sup>3</sup>
Ethyl acetate 141-78-6	TWA: 734 mg/m <sup>3</sup> TWA: 200 ppm STEL: 1468 mg/m <sup>3</sup> STEL: 400 ppm	TWA: 734 mg/m <sup>3</sup> TWA: 200 ppm STEL: 1468 mg/m <sup>3</sup> STEL: 400 ppm

**Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL) 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich (68515-49-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	41.67 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	5.29 mg/m <sup>3</sup>	

Diisononyl phthalate (28553-12-0)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	51.72 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	366 mg/kg bw/d	

3-butyl-1-[4-({ 4-[(butylcarbamoyl)amino]phenyl} methyl)phenyl]urea (--)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects	Inhalation	49.37 mg/m <sup>3</sup>	
Long term Systemic health effects	Dermal	140 mg/kg bw/d	

Carbon black (1333-86-4)			
Type	Exposure route	Derived No Effect Level	Safety factor

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION  
POLYURETHANE BLACK**  
Supersedes Date: 13-Apr-2022

Revision date 18-May-2022

Revision Number 2

		(DNEL)	
worker Long term Systemic health effects	Inhalation	2 mg/m <sup>3</sup>	
worker Long term Local health effects	Inhalation	2 mg/m <sup>3</sup>	

## Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate (--)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	3.5 mg/m <sup>3</sup>	
worker Short term Systemic health effects	Inhalation	28 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	0.5 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	4 mg/kg bw/d	

## Ethyl acetate (141-78-6)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	63 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	1468 mg/m <sup>3</sup>	
worker Long term Local health effects	Inhalation	734 mg/m <sup>3</sup>	
worker Short term Local health effects	Inhalation	1468 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Inhalation	734 mg/m <sup>3</sup>	

## Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)

### Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane (192526-20-8)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	1.7 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	4.7 mg/kg bw/d	

## Derived No Effect Level (DNEL)

### 1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich (68515-49-1)

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION  
POLYURETHANE BLACK**  
Supersedes Date: 13-Apr-2022

Revision date 18-May-2022

Revision Number 2

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	0.75 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	20.38 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	1.3 mg/m <sup>3</sup>	

## 3-butyl-1-[4-({ 4-[(butylcarbamoyl)amino]phenyl} methyl)phenyl]urea (--)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects	Inhalation	7.4 mg/m <sup>3</sup>	
Long term Systemic health effects	Dermal	50 mg/kg bw/d	
Long term Systemic health effects	Oral	5 mg/kg bw/d	

## Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate (--)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	0.875 mg/m <sup>3</sup>	
Consumer Short term Systemic health effects	Inhalation	7 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	0.25 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	2 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.25 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	2 mg/kg bw/d	

## Ethyl acetate (141-78-6)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	4.5 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	37 mg/kg bw/d	
Consumer Short term Systemic health effects	Inhalation	734 mg/m <sup>3</sup>	
Consumer	Inhalation	367 mg/m <sup>3</sup>	

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION  
POLYURETHANE BLACK**  
Supersedes Date: 13-Apr-2022

Revision date 18-May-2022

Revision Number 2

Long term Local health effects			
Consumer Short term Local health effects	Inhalation	734 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Inhalation	367 mg/m <sup>3</sup>	

<b>Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane (192526-20-8)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	0.3 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	1.7 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.2 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.  
(PNEC)

<b>Predicted No Effect Concentration (PNEC)</b> <b>3-butyl-1-[4-({ 4-[(butylcarbamoyl)amino]phenyl} methyl)phenyl]urea (--)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.1 mg/l
Marine water	0.01 mg/l
Sewage treatment plant	10 mg/l
Freshwater sediment	76.36 mg/kg dry weight
Marine sediment	7.636 mg/kg dry weight
Soil	15.15 mg/kg dry weight

<b>Carbon black (1333-86-4)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	5 mg/l
Marine water	5 mg/l

<b>Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate (--)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.002 mg/l
Marine water	0 mg/l
Freshwater - intermittent	0.005 mg/l
Marine water - intermittent	0.001 mg/l
Freshwater sediment	3.43 mg/kg dry weight
Marine sediment	0.343 mg/kg dry weight
Microorganisms in sewage treatment	No hazard identified
Soil	0.68 mg/kg dry weight

<b>Ethyl acetate (141-78-6)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.26 mg/l
Marine water	0.026 mg/l
Freshwater sediment	1.25 mg/kg
Marine sediment	0.125 mg/kg
Soil	0.24 mg/kg



# SAFETY DATA SHEET

BOSTIK PRO SEALANT PU91 CONSTRUCTION  
POLYURETHANE BLACK  
Supersedes Date: 13-Apr-2022

Revision date 18-May-2022

Revision Number 2

Microorganisms in sewage treatment	650 mg/l
<b>Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane (192526-20-8)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.1 mg/l
Marine water	0.01 mg/l
Sewage treatment plant	100 mg/l
Freshwater sediment	0.428 mg/kg dry weight
Marine sediment	0.043 mg/kg dry weight

## 8.2. Exposure controls

<b>Engineering controls</b>	Ensure adequate ventilation, especially in confined areas.
<b>Personal protective equipment</b>	
<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
<b>Hand protection</b>	Nitrile rubber. Butyl rubber. Glove thickness > 0.4 mm. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. The breakthrough time for the mentioned glove material is in general greater than 60 min. Gloves must conform to standard EN 374
<b>Skin and body protection</b>	Suitable protective clothing.
<b>Respiratory protection</b>	In case of insufficient ventilation, wear suitable respiratory equipment.
<b>Recommended filter type:</b>	Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases and vapours filter conforming to EN 14387.
<b>Environmental exposure controls</b>	Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Solid
<b>Appearance</b>	Paste
<b>Colour</b>	Black
<b>Odour</b>	Characteristic.
<b>Odour threshold</b>	No information available

<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>
<b>Melting point / freezing point</b>	No data available	None known
<b>Initial boiling point and boiling range</b>	No data available	None known
<b>Flammability</b>	Not applicable for liquids .	
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Flash point</b>	> 61 °C	CC (closed cup)
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>		None known
<b>pH</b>	No data available	None known
<b>pH (as aqueous solution)</b>	No data available	None known
<b>Kinematic viscosity</b>	600000 mm <sup>2</sup> /s	None known
<b>Dynamic viscosity</b>	No data available	No information available
<b>Water solubility</b>	No data available Product cures with moisture Insoluble in water	
<b>Solubility(ies)</b>	No data available	None known
<b>Partition coefficient</b>	No data available	None known
<b>Vapour pressure</b>	No data available	None known
<b>Relative density</b>	No data available	None known
<b>Bulk Density</b>	No data available	
<b>Density</b>	1.28	

# SAFETY DATA SHEET

BOSTIK PRO SEALANT PU91 CONSTRUCTION  
POLYURETHANE BLACK  
Supersedes Date: 13-Apr-2022

Revision date 18-May-2022

Revision Number 2

Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

## 9.2. Other information

### VOC Content (%)

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Reactivity Product cures with moisture.

### 10.2. Chemical stability

Stability Stable under normal conditions.

### Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

### 10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture.

### 10.5. Incompatible materials

Incompatible materials None known based on information supplied.

### 10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met. Specific test data for the substance or mixture is not available. Causes mild skin irritation.

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION  
POLYURETHANE BLACK**  
Supersedes Date: 13-Apr-2022

Revision date 18-May-2022

Revision Number 2

**Ingestion** Based on available data, the classification criteria are not met.

## Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Prolonged contact may cause redness and irritation.

## Acute toxicity

## Numerical measures of toxicity

## Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	>60000 mg/kg (Rattus)	= 16000 mg/kg (Oryctolagus cuniculus)	> 0.13 mg/L ( Rat ) 6 h
Diisononyl phthalate	>9750 mg/kg (Rattus)	>3160 mg/Kg (Oryctolagus cuniculus)	>4.4 mg/L (Rattus) 4 h
3-butyl-1-[4-({4-[(butylcarbamoyl)amino]phenyl} methyl)phenyl]urea	>2000 mg/Kg (Rattus) (OECD 401)	>2000 mg/Kg (Rattus) (OECD 402)	-
Carbon black	LD50 > 8000 mg/kg (Rattus) OECD 401	> 3 g/kg (Oryctolagus cuniculus)	> 4.6 mg/m <sup>3</sup> ( Rat ) 4 h
Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate	>5000 mg/Kg (Rattus)	>2000 mg/Kg (Rattus) (OECD 402)	-
Aromatic Polyisocyanate	LD50 >2000 mg/Kg (Rattus)	-	LC50 >3.820 mg/L (Rattus) 4h dust/mist
Ethyl acetate	=5620 mg/kg (Rattus)	> 18000 mg/kg (Oryctolagus cuniculus) > 20 mL/kg (Oryctolagus cuniculus)	LC0 29.3 mg/l air
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	LD50 = 3230 mg/Kg (Rat) OECD 401	LD50 >3170 mg/Kg (Rat)	-
Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane	>2000 mg/Kg (Rattus) (OECD 423)	>2000 mg/Kg (Rattus) (OECD 402)	-

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Based on available data, the classification criteria are not met. Classification based on data available for ingredients. May cause skin irritation.

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION  
POLYURETHANE BLACK**  
Supersedes Date: 13-Apr-2022

Revision date 18-May-2022

Revision Number 2

**Respiratory or skin sensitisation** May produce an allergic reaction.

Ethyl acetate (141-78-6)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

Endocrine disrupting properties

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich 68515-49-1	EC50: >1.3mg/L (96h, Pseudokirchneriella subcapitata)	LC50 96 h > 0.62 mg/L (Oncorhynchus mykiss)	-	EC50: >0.18mg/L (48h, Daphnia magna)		
Diisononyl phthalate 28553-12-0	EC50 72 h > 500 mg/L (Desmodesmus subspicatus)	LC50 96 h > 100 mg/L (Brachydanio rerio semi-static)	-	EC50: >0.06mg/L (48h, Daphnia magna) EC50: >500mg/L (48h, Daphnia magna)		
3-butyl-1-[4-({4-[(butylcarbamoyl)amino]phenyl}methyl)phenyl]urea	-	LC50 (96h) >120 mg/L Danio rerio (OECD 203)	-	EC50 (48h) >100 mg/L Daphnia magna (OECD 202)		

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION  
POLYURETHANE BLACK**  
Supersedes Date: 13-Apr-2022

Revision date 18-May-2022

Revision Number 2

--						
Carbon black 1333-86-4	>10000 mg/l (Desmodesmus subspicatus) OECD 202	>1000 mg/l (Brachydanio rerio) OCDE 203	-	EC50: >5600mg/L (24h, Daphnia magna)		
Ethyl acetate 141-78-6	EC50: =3300mg/L (48h, Desmodesmus subspicatus)	LC50: =484mg/L (96h, Oncorhynchus mykiss) LC50: 352 - 500mg/L (96h, Oncorhynchus mykiss) LC50: 220 - 250mg/L (96h, Pimephales promelas)	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	EC50: =560mg/L (48h, Daphnia magna)		
Reaction mass of Bis(1,2,2,6,6-pentamet hyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate 1065336-91-5	EC50 (72 h) 1,68 mg/l (growth rate), Desmodesmus subspicatus (OECD 201)	LC50 (96 h) 0,9 mg/l, Brachydanio rerio (OECD 203)	-	-	1	1
Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimetho xysilane 192526-20-8	EC50 (72h) >100 mg/L Algae (Raphidocelis subcapitata) (OECD 201)	LC50 (96h)>100 mg/L Fish (Brachydanio rerio) (OECD 203)	-	EC50 (48h) >100 mg/L Daphnia magna (OECD 202)		

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

3-butyl-1-[4-((4-((butylcarbamoyl)amino)phenyl) methyl)phenyl]urea (--  
)

Method	Exposure time	Value	Results
OECD Guideline 310	28 days	0.4%	Not readily biodegradable
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	11%	Not readily biodegradable

Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl  
phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate (--  
)

Method	Exposure time	Value	Results
OECD Test No. 301C: Ready Biodegradability: Modified MITI Test (I) (TG 301 C)	28 days	75%	Readily biodegradable

Aromatic Polyisocyanate (53317-61-6)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)		biodegradation	34 % Not readily biodegradable

Ethyl acetate (141-78-6)

Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane (192526-20-8)

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION  
POLYURETHANE BLACK**  
Supercedes Date: 13-Apr-2022

Revision date 18-May-2022

Revision Number 2

Method	Exposure time	Value	Results
OECD Test No. 301C: Ready Biodegradability: Modified MITI Test (I) (TG 301 C)	28 days	3.85%	Not readily biodegradable

## 12.3. Bioaccumulative potential

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	8.8
Diisononyl phthalate	9.7
3-butyl-1-[4-({ 4-[(butylcarbamoyl)amino]phenyl} methyl)phenyl]urea	5.5
Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate	4.5
Ethyl acetate	0.73
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	2.77

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	The substance is not PBT / vPvB
Diisononyl phthalate	The substance is not PBT / vPvB PBT assessment does not apply
Carbon black	The substance is not PBT / vPvB PBT assessment does not apply
Ethyl acetate	The substance is not PBT / vPvB PBT assessment does not apply
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

## 12.7. Other adverse effects

No information available.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

**Waste from residues/unused products** Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

# SAFETY DATA SHEET

BOSTIK PRO SEALANT PU91 CONSTRUCTION  
POLYURETHANE BLACK  
Supercedes Date: 13-Apr-2022

Revision date 18-May-2022

Revision Number 2

**Contaminated packaging** Handle contaminated packages in the same way as the product itself.

**European Waste Catalogue** 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

**Other information** Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

### Land transport (ADR/RID)

14.1 UN number or ID number Not regulated  
14.2 Proper Shipping Name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special Provisions None

### IMDG

14.1 UN number or ID number Not regulated  
14.2 Proper Shipping Name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Marine pollutant NP  
14.6 Special Provisions None  
14.7 Maritime transport in bulk according to IMO instruments Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated  
14.2 Proper Shipping Name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special Provisions None

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

#### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	68515-49-1	52[b].
Diisononyl phthalate	28553-12-0	52[a].

52 . Not to be used in toys or childcare articles above 0.1% which can be placed in the mouth by children.

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION  
POLYURETHANE BLACK**  
Supersedes Date: 13-Apr-2022

Revision date 18-May-2022

Revision Number 2

## Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

## Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

## Persistent Organic Pollutants

Not applicable

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## SECTION 16: Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H225 - Highly flammable liquid and vapour

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H361f - Suspected of damaging fertility

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H412 - Harmful to aquatic life with long lasting effects

H413 - May cause long lasting harmful effects to aquatic life

#### Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

#### Key literature references and sources for data

No information available



# SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION  
POLYURETHANE BLACK**  
Supercedes Date: 13-Apr-2022

Revision date 18-May-2022

Revision Number 2

---

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 18-May-2022

**Indication of changes**

**Revision note** SDS sections updated, 3.

**Training Advice** No information available

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**