



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
Supercedes Date: 08-Apr-2022

Revision date 08-Apr-2022  
Revision Number 1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY  
**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Sealant  
**Uses advised against** None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** +44 (1785) 272650  
**Ireland** **NPIC - National Poison Information Centre**  
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)  
Healthcare Professionals: +353 (01) 8092566 (24 hour service)  
**Europe** 112

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

<b>Chronic aquatic toxicity</b>	Category 3 - (H412)
---------------------------------	---------------------

### 2.2. Label elements

#### Signal word

None

#### Hazard statements

H412 - Harmful to aquatic life with long lasting effects.

#### EU Specific Hazard Statements

EUH208 - Contains 3-(Triethoxysilyl) propylamine & 2-octyl-2H-isothiazol-3-one [OIT]. May produce an allergic reaction

#### Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
**Supersedes Date:** 08-Apr-2022

**Revision date** 08-Apr-2022  
**Revision Number** 1

P102 - Keep out of reach of children  
P273 - Avoid release to the environment  
P501 - Dispose of contents/ container to an approved waste disposal plant

## 2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Small amounts of 2-Pentanone oxime (CAS 623-40-5) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Limestone	215-279-6	1317-65-3	>25 - <40	[C]	-	[5]
2-Pentandione, O,O',O''-(methylsilylidyn e)trioxime	484-460-1	37859-55-5	1- <2.5	Acute Tox. 4 (H302) Eye Irrit. 2 (H319)	-	01-2120004323-76-XXXX
Titanium dioxide	236-675-5	13463-67-7	0.1 - <1	^	-	01-2119489379-17-XXXX
3-(Triethoxysilyl) propylamine	213-048-4	919-30-2	0.1 - <1	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Acute Tox. 4 (H302)	-	01-2119480479-24-XXXX
2-octyl-2H-isothiazol-3-one [OIT]	247-761-7	26530-20-1	0.0015 - <0.01	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Skin Corr. 1B (H314) Eye Dam 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	Skin Sens. 1A :: C>=0.0015%	-

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
Supersedes Date: 08-Apr-2022

Revision date 08-Apr-2022  
Revision Number 1

---

## **Full text of H- and EUH-phrases: see section 16**

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## **SECTION 4: First aid measures**

### **4.1. Description of first aid measures**

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a doctor.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
<b>Skin contact</b>	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

### **4.2. Most important symptoms and effects, both acute and delayed**

**Symptoms** None known.

### **4.3. Indication of any immediate medical attention and special treatment needed**

**Note to doctors** Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when the product is exposed to moisture or water. Treat symptomatically.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

**Suitable Extinguishing Media** Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam.

**Unsuitable extinguishing media** Full water jet.

### **5.2. Special hazards arising from the substance or mixture**

**Specific hazards arising from the chemical** Thermal decomposition can lead to release of irritating gases and vapours.

**Hazardous combustion products** Carbon oxides. Carbon dioxide (CO<sub>2</sub>). Silicon oxides. Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.

### **5.3. Advice for firefighters**

**Special protective equipment and precautions for fire-fighters** Wear self contained breathing apparatus for fire fighting if necessary.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

# SAFETY DATA SHEET

BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY  
Supersedes Date: 08-Apr-2022

Revision date 08-Apr-2022  
Revision Number 1

**Personal precautions** Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.

**For emergency responders** Use personal protection recommended in Section 8.

## 6.2. Environmental precautions

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

## 6.3. Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from moisture. Keep away from food, drink and animal feedingstuffs. Keep from freezing.

**Recommended storage temperature** Keep at temperatures between 10 and 35 °C. Do not freeze.

### 7.3. Specific end use(s)

**Specific use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

**Exposure Limits** Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Ethanol	-	TWA: 1000 ppm

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
**Supersedes Date:** 08-Apr-2022

**Revision date** 08-Apr-2022  
**Revision Number** 1

64-17-5		TWA: 1920 mg/m <sup>3</sup> STEL: 3000 ppm STEL: 5760 mg/m <sup>3</sup>
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> *	TWA: 200 ppm TWA: 266 mg/m <sup>3</sup> STEL: 250 ppm STEL: 333 mg/m <sup>3</sup> Sk*
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol 67-56-1	-	15 mg/L (urine - Methanol end of shift)	-

**Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL)			
Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

3-(Triethoxysilyl) propylamine (919-30-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	59 mg/m <sup>3</sup>	
worker Short term Systemic health effects	Inhalation	59 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	8.3 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	8.3 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

3-(Triethoxysilyl) propylamine (919-30-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	17 mg/m <sup>3</sup>	
Consumer Short term Systemic health effects	Inhalation	17.4 mg/m <sup>3</sup>	
Consumer Long term	Dermal	5 mg/kg bw/d	

# SAFETY DATA SHEET

BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY  
Supersedes Date: 08-Apr-2022

Revision date 08-Apr-2022  
Revision Number 1

Systemic health effects			
Consumer Short term Systemic health effects	Dermal	5 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.

Predicted No Effect Concentration (PNEC)	
Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

3-(Triethoxysilyl) propylamine (919-30-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.33 mg/l
Marine water	0.033 mg/l

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
<b>Hand protection</b>	Wear suitable gloves. Recommended Use: Neoprene™, Nitrile rubber, Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
<b>Skin and body protection</b>	None under normal use conditions.
<b>Respiratory protection</b>	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
<b>Recommended filter type:</b>	Organic gases and vapours filter conforming to EN 14387. White. Brown.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Solid
<b>Appearance</b>	Paste
<b>Colour</b>	Grey
<b>Odour</b>	Characteristic.
<b>Odour threshold</b>	No information available

Property	Values	Remarks • Method
<b>Melting point / freezing point</b>	No data available	None known
<b>Initial boiling point and boiling range</b>	> 300 °C	
<b>Flammability</b>	No data available	None known
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
Supersedes Date: 08-Apr-2022

Revision date 08-Apr-2022  
Revision Number 1

<b>Lower flammability or explosive limits</b>	No data available	
<b>Flash point</b>	> 100 °C	
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>		None known
<b>pH</b>	No data available	Not applicable Insoluble in water
<b>pH (as aqueous solution)</b>	No data available	None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	No data available	<b>Water solubility</b> No data available Immiscible in water Product cures with moisture
None known		<b>Solubility(ies)</b> No data available
None known		<b>Partition coefficient</b> No data available
hPa @ 20 °C		<b>Vapour pressure</b> 100
		<b>Relative density</b> 1.26
		<b>Bulk Density</b> No data available
		<b>Density</b> 1.26
None known		<b>Relative vapour density</b> No data available
		<b>Particle characteristics</b>
		<b>Particle Size</b> No information available
		<b>Particle Size Distribution</b> No information available

## 9.2. Other information

### VOC Content (%)

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics

No information available

Minimum Ignition Temperature >200  
(°C)

**Minimum Ignition Temperature (°C)** >200

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

**Reactivity** Product cures with moisture.

### 10.2. Chemical stability

**Stability** Stable under normal conditions.

### Explosion data

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** None.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

### 10.4. Conditions to avoid

**Conditions to avoid** Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

# SAFETY DATA SHEET

BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY  
Supersedes Date: 08-Apr-2022

Revision date 08-Apr-2022  
Revision Number 1

## 10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

## 10.6. Hazardous decomposition products

Hazardous decomposition products Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### Product Information

**Inhalation** Based on available data, the classification criteria are not met.

**Eye contact** Based on available data, the classification criteria are not met.

**Skin contact** Based on available data, the classification criteria are not met. May cause sensitisation in susceptible persons.

**Ingestion** Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

#### Acute toxicity

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 53,646.90 mg/kg  
ATEmix (dermal) 86,991.40 mg/kg

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone	>5000 mg/kg (Rattus)	-	-
2-Pentandione, O,O',O''-(methylsilylydyne)trioxime	LD50 =1234 mg/kg bw (Rattus)(OECD guideline 425)	LD50 > 2000 mg/kg (Rattus) EU Method B.3	-
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L ( Rattus ) 4 h
3-(Triethoxysilyl) propylamine	LD50 = 1490 mg/kg (Rat, female) EPA OTS 798.1175 LD50 = 2690 mg/kg (Rat, male) EPA OTS 798.1175	LD50 = 4076 mg/kg (Oryctolagus cuniculus) EPA OTS 798.1100	LC50 >144 mg/L (6h) Rat (Vapour)
2-octyl-2H-isothiazol-3-one [OIT]	=125 mg/kg (Rattus)	= 690 mg/kg (Oryctolagus cuniculus)	-

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.



# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
Supersedes Date: 08-Apr-2022

Revision date 08-Apr-2022  
Revision Number 1

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Corrosive

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation** No classification is proposed, based on conclusive negative data. May produce an allergic reaction. OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. May cause sensitisation in susceptible persons.

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Titanium dioxide (13463-67-7)

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse		sensitising

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
---------------	---------------	------	-------------	-----------	----------	----------

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
**Supersedes Date:** 08-Apr-2022

**Revision date** 08-Apr-2022  
**Revision Number** 1

	plants		microorganisms			(long-term)
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmodesmus subspicatus)	CL50 (96h)>10000mg/L (Oncorhynchus mykiss)	-	CE50 (48h) >1000 mg/L Daphnia Magna		
2-Pentandione, O,O',O''-(methylsilylidyne)trioxime 37859-55-5	EC50 (72h) = 88 mg/L (Pseudokirchneriella subcapitata) OECD 201	LC50 (96h) >113 mg/L (Oncorhynchus mykiss) Static (OECD Guideline 203)	-	EC50 (48h) >100 mg/L (Daphnia magna) static (OECD guideline 202)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
3-(Triethoxysilyl) propylamine 919-30-2	EC50 (72h) >1000 mg/L Green algae (desmodesmus subspicatus) (OECD TG 201)	LC50 (96h) >934 mg/L (Brachydanio rerio) (OECD TG 203)	-	EC50 (48h) =331 mg/L Daphnia magna (OECD TG 202)		
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	EC50(72h) = 0.084 mg/L (Scenedesmus subspicatus) (OECD 201)	LC50 (96h) = 0.036 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) =0.42 mg/L (OECD 202)	100	100

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Exposure time	Value	Results
OECD Test No. 309: Aerobic Mineralization in Surface Water - Simulation Biodegradation Test		Half-life 0.6-1.4 d	Readily biodegradable

## 12.3. Bioaccumulative potential

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
Limestone	0.9
2-Pentandione, O,O',O''-(methylsilylidyne)trioxime	1.25
3-(Triethoxysilyl) propylamine	1.7
2-octyl-2H-isothiazol-3-one [OIT]	2.92

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
2-Pentandione, O,O',O''-(methylsilylidyne)trioxime	The substance is not PBT / vPvB
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does not apply

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
Supersedes Date: 08-Apr-2022

Revision date 08-Apr-2022  
Revision Number 1

3-(Triethoxysilyl) propylamine	The substance is not PBT / vPvB
2-octyl-2H-isothiazol-3-one [OIT]	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

## 12.7. Other adverse effects

No information available.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

<b>Waste from residues/unused products</b>	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
<b>Contaminated packaging</b>	Handle contaminated packages in the same way as the product itself.
<b>European Waste Catalogue</b>	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
<b>Other information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## **SECTION 14: Transport information**

**Note:** Keep from freezing.

### Land transport (ADR/RID)

<b>14.1 UN number or ID number</b>	Not regulated
<b>14.2 Proper Shipping Name</b>	Not regulated
<b>14.3 Transport hazard class(es)</b>	Not regulated
<b>14.4 Packing group</b>	Not regulated
<b>14.5 Environmental hazards</b>	Not applicable
<b>14.6 Special Provisions</b>	None

### IMDG

<b>14.1 UN number or ID number</b>	Not regulated
<b>14.2 Proper Shipping Name</b>	Not regulated
<b>14.3 Transport hazard class(es)</b>	Not regulated
<b>14.4 Packing group</b>	Not regulated
<b>14.5 Marine pollutant</b>	NP
<b>14.6 Special Provisions</b>	None
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable

### Air transport (ICAO-TI / IATA-DGR)

<b>14.1 UN number or ID number</b>	Not regulated
<b>14.2 Proper Shipping Name</b>	Not regulated
<b>14.3 Transport hazard class(es)</b>	Not regulated
<b>14.4 Packing group</b>	Not regulated
<b>14.5 Environmental hazards</b>	Not applicable
<b>14.6 Special Provisions</b>	None

## **Section 15: REGULATORY INFORMATION**

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
Supersedes Date: 08-Apr-2022

Revision date 08-Apr-2022  
Revision Number 1

---

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

#### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

#### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

#### **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

#### **Persistent Organic Pollutants**

Not applicable

### National regulations

## 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at  $>10$  tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed  
H302 - Harmful if swallowed  
H311 - Toxic in contact with skin  
H314 - Causes severe skin burns and eye damage  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H319 - Causes serious eye irritation  
H330 - Fatal if inhaled  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects

#### **Legend**

United Kingdom - BE

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
Supersedes Date: 08-Apr-2022

Revision date 08-Apr-2022  
Revision Number 1

---

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

## Key literature references and sources for data

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 08-Apr-2022

## Indication of changes

**Revision note** SDS sections updated: 2, 3, 11, 12, 15.

**Training Advice** No information available

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**