(TOOLSTATION - FLUME) NOISE SILENCER

Page: 1

Compilation date: 17.06.2025

Revision date: 17.06.2025

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: (TOOLSTATION - FLUME) NOISE SILENCER

Product code: AE916

Synonyms: FLUME - AE916

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Specialist water based treatment.

1.3. Details of the supplier of the safety data sheet

Company name: TOOLSTATION LIMITED

Part of Travis Perkins Trading Company

Ryehill House, Northampton, NN5 7UA

Contact: https://www.toolstation.com/contact

1.4. Emergency telephone number

Emergency Contact: https://www.toolstation.com/contact

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Irrit. 2: H319; Skin Irrit. 2: H315

Most important adverse effects: Causes skin irritation. Causes serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H319: Causes serious eye irritation.

Hazard pictograms: GHS07: Exclamation mark



(TOOLSTATION - FLUME) NOISE SILENCER

Page: 2

Signal words: Warning

Precautionary statements: P102: Keep out of reach of children.

P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P302+P352: IF ON SKIN: Wash with plenty of water.

Haz. ingredients (label): Contains:

PHOSPHORIC ACID
SULPHAMIC ACID

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

TRIETHANOLAMINE - REACH registered number(s): 01-2119486482-31-XXXX

EINECS	CAS PBT / WEL		CLP Classification	Percent
203-049-8 102-71-6		Substance with a Community	-	1-10%
		workplace exposure limit.		

SULPHAMIC ACID - REACH registered number(s): 01-2119488633-28-XXXX

226-218-8	5329-14-6	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315;	<1%
			Aquatic Chronic 3: H412	

PHOSPHORIC ACID - REACH registered number(s): 01-2119485924-24

231-633-2	7664-38-2	_	Skin Corr. 1C: H314	<1%
201 000 2	1001002		OKIII OOII: 10:11011	- 1 / 0

Non-classified ingredients:

ETIDRONIC ACID - REACH registered number(s): 01-2119510391-53-xxxx

EINECS	CAS	PBT / WEL CLP Classification		Percent	
- 2809-21-4		-	Met. Corr. 1: H290; Eye Dam. 1: H318;	<1%	
			Acute Tox. 4: H302		

ALKYL DIMETHYL BENZYL AMMONIUM CHLORIDE - REACH registered number(s): 01-2119970550-39-XXXX

939-350-2	68424-85-1	-	Acute Tox. 4: H302; Skin Corr. 1B:	
		H314; Aquatic Acute 1: H400; Aquatic		
			Chronic 2: H411	

Section 4: First aid measures

(TOOLSTATION - FLUME) NOISE SILENCER

Page: 3

4.1. Description of first aid measures

 $\textbf{Skin contact:} \quad \text{Wash immediately with plenty of soap and water.}$

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes. Water based product. Advice relates to dry residues

after water has evaporated.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-

side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding. Warning

relates to a large spillage, not a single bottle.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Single bottle spillage: wash down the drain with a

large amount of water. Wash the spillage site with large amounts of water.

(TOOLSTATION - FLUME) NOISE SILENCER

Page: 4

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

TRIETHANOLAMINE

Workplace exposure limits:

Respirable dust:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m3 (no std.)	-	-	-

PHOSPHORIC ACID

UK	1 mg/m3	2 mg/m3	_	_
J	g,	g,		1

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Barely perceptible odour

Evaporation rate: Slow

(TOOLSTATION - FLUME) NOISE SILENCER

Page: 5

Solubility in water: Highly soluble

Viscosity: Non-viscous

Boiling point/range°C: 100 Melting point/range°C: 0

Flammability limits %: lower: Not applicable. upper: Not applicable.

Flash point°C: Not applicable. Part.coeff. n-octanol/water: No data available.

Autoflammability°C: Not applicable. Vapour pressure: Not applicable.

Relative density: 1.020 pH: 4 - 5

VOC g/I: 0

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Freezing

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

TRIETHANOLAMINE

ORL	RAT	LD50	>2	g/kg
SKN	RBT	LD50	>10	g/kg

(TOOLSTATION - FLUME) NOISE SILENCER

Page: 6

SULPHAMIC ACID

ORAL	RAT	LD50	3160	ma/ka
UNAL	INAI	LD30	3100	ilig/kg

PHOSPHORIC ACID

OBL	RAT	LC50	<2000	ma/ka
ORL	KAI	LUSU	<2000	mg/kg

Non-classified ingredients:

ETIDRONIC ACID

ORL	RAT	LD50	2400	mg/Kg
OIL	11/71	LD30	2400	IIIg/INg

ALKYL DIMETHYL BENZYL AMMONIUM CHLORIDE

DERMAL	RAT	LD50	1560	mg/kg
ORL	RAT	LD50	795	mg/Kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

TRIETHANOLAMINE

FISH	48H EC50	1390	mg/l
FISH	96H LC50	>5000	mg/l

SULPHAMIC ACID

FISH	96H LC50	70.3	mg/l

(TOOLSTATION - FLUME) NOISE SILENCER

Page: 7

ETIDRONIC ACID

RAINBOW TROUT (Oncorhynchus mykiss)	48H EC50	878	mg/l
Oncorhynchus mykiss	96H LC50	300	mg/l

ALKYL DIMETHYL BENZYL AMMONIUM CHLORIDE

DAPHNIA	48H EC50	0.03	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	1.7	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable. The surfactant(s) contained in this preparation complies (comply) with

the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on

detergents.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil. Volatile. Soluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: The product will not be dangerous to the environment when diluted in waste water

systems and may be disposed of as low-hazard chemical waste within the scope of

national and local regulations/permits.

Recovery operations: Not applicable.

Waste code number: 20 01 30

Disposal of packaging: Recycle container where permitted. Disposal of waste containers must be done in

accordance with local and / or national regulations.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

(TOOLSTATION - FLUME) NOISE SILENCER

Page: 8

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

IMPORTANT NOTE:

Risk phases in this section below relate to the INDIVIDUAL COMPONENTS in the

formulation when used at their FULL CONCENTRATIONS, and not at the reduced levels

in the mixed product.

See sections 2 and 3 for the calculated hazard and risk phrases for the blended product.

Phrases used in s.2 and s.3: H290: May be corrosive to metals.

H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product. For professional

and industrial use only.