

MATERIAL SAFETY DATA SHEET

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Identification of substance Precast concrete products

Product description Precast concrete paving, kerbs, channels, block paving, drainage channels, walling

products & specific decorative products marketed under many different range

names

Manufacturer/Supplier Marshalls Mono Ltd, Landscape House, Premier Way, Lowfields Business Park,

Elland, HX5 9HT

Telephone number (01422) 312000 Technical Advisory Services 0370 411 2233

2 HAZARDS IDENTIFICATION

Most important hazards Cutting of hardened product will produce excessive amounts of dust that will

contain respirable Quartz, this may constitute a chronic health hazard

Long term prolonged exposure to high levels of respirable crystalline silica can also

lead to an increased risk of developing silicosis and lung cancer

Any cutting or finishing can also result in particles being projected at high speed

with the consequent risk of injury or damage

3 COMPOSITION/INFORMATION ON INGREDIENTS

Description of the preparation Sand, aggregate, cementitious material, pigments, admixtures and water are

combined and processed to form dense concrete products

4 FIRST AID MEASURES

General advice In all cases of doubt, or when symptoms persist, seek medical attention. Never give

anything by mouth to an unconscious person

Inhalation (Dust) Remove to fresh air and seek medical attention if required

Skin contact Wash skin thoroughly with soap and water or use a proprietary skin cleaner and

apply suitable dressings

Eye contact Contact lenses should be removed. Irrigate copiously with clean, fresh water for at

least 10 minutes, holding the eyelids apart. Obtain medical attention if irritation

persists

Ingestion If accidentally swallowed remove from exposure and seek medical attention if

required

5 FIRE-FIGHTING MEASURES

Suitable extinguishing media Concrete is not flammable and will not facilitate combustion with other materials

6 ACCIDENTIAL RELEASE MEASURES

Personal precaution In the event of dust release, avoid breathing in dust. Wear dust mask/respirator and

goggles

Environmental precaution No danger, but material should be disposed of in accordance with local authority

guidelines

Method for cleaning up No special requirements. Where possible use mechanical aids to reduce the risk of

manual handling injury. Avoid sweeping that creates dust and vacuum dust where

practical

7 HANDLING AND STORAGE

Handling

Technical condition Products are delivered on pallets, shrink-wrapped on specially banded or designed

packs

Safe handling advice The preferred method of off-loading from vehicles is my mechanical means,

ensuring all lift apparatus and vehicles are capable of lifting the product within their working capacity. Care to be taken when placing packs into position avoiding

dropping or banging. Banding MUST NOT be used as a lifting aid

Care should be taken when manually handling products. Good lifting practices should be followed at all times. Mechanical handling devices should be considered

with products over 20kg in weight

Storage

Precaution All products must be stored on a firm level surface and not on slopes or soft uneven

areas. The bottom layer of any non-palleted packs should not be laid directly onto

the ground but placed either on timber or similar bearers, pallets or boards

Storage condition Firm level surface – do not stack packs more than 4 high, however some decorative

products are of irregular shape and an individual assessment should be made at the

time of stacking

Soft, uneven surface – do not stack packs more than 2 high. An individual assessment should be made at the time of stacking as to the suitability of the

ground

Packaging material Before removing shrink-wrapping or banding, ensure that the products are safe and

will not fall over; end supports should be used where necessary

Shrink-wrapping should be cut not torn. Banding must be removed with care and

should be cut with suitable clippers and not broken by hand

Wear suitable protective gloves and eye protection

Packaging could be slippy when wet

It is difficult to cover all situations and whoever is stacking the pallets must assess the risk on how high packs are stacked and their stability

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering measure Use dust extraction if OES is exceeded

Control parameter

Exposure limit Total Inhalable Nuisance Dust 10.0mg/m³

Total Respirable Nuisance Dust 4.omg/m³
Respirable crystalline Silica 0.1omg/m³

All are given as maximum concentrations and expressed as an 8-hour time

weighted average (8hr TWA)

Personal protection equipment

Respiratory protection Dust masks to a suitable BS or EN standard are recommended where operations

may cause inhalation of the product

Hand protection Use suitable gloves

Skin and body protection Safety footwear should be worn to protect against injury from falling precast units

Eye protection Safety goggles or face shield to a suitable BS or EN Standard are recommended

where operations may cause product getting into eyes $% \left\{ \mathbf{r}_{i}^{\mathbf{r}_{i}}\right\} =\mathbf{r}_{i}^{\mathbf{r}_{i}}$

Hygiene measure Wash hands before breaks and after finishing work

9 PHYSICAL AND CHEMICAL PROPERTIES

General information

Appearance Solid

Colour Grey if concrete is unpigmented

Odour Odourless

Important health, safety and environmental information

pH Alkaline >7

Relative density 1.5 to 2.9 (water = 1)

Water solubility 0.1% max. Generally considered insoluble in water

10 STABILITY AND REACTIVITY

Stability Stable

Hardened concrete will react with most acids in a neutralization-type reaction. Heat, spattering and evolution of potentially toxic gases (such as HCl, NO or NO₂) may result depending on the acid involved. Prolonged contact of an acid with the concrete may cause etching or other damage

Hazardous decomposition products None

11 TOXICOLOGICAL INFORMATION

Acute toxicity

Inhalation May cause damage to mucous membranes in nose, throat, lungs and bronchial

system

Skin contact Prolonged contact with wet cement/mixture may cause burns

Eyes contact Risk of serious damage to eyes Ingestion May cause discomfort if swallowed

12 ECOLOGICAL INFORMATION

General information The product components are not classified as environmentally hazardous.

However, this does not exclude the possibility that large or frequent spills can have

a harmful or damaging effect on the environment

13 DISPOSAL CONSIDERATIONS

Waste/unused products Dispose of waste and residues in accordance with local authority requirements Contaminated packaging Shrink-rapping must not be burnt, as toxic fumes are given off such as carbon

monoxide, hydrocarbons and aldehydes

Timber pallets on which products are transported must not be used again for any

other products

Further information Waste should be disposed of in accordance with local and national waste disposal

regulations

TRANSPORT INFORMATION

This product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR, RID)

15 REGULATORY INFORMATION

Symbol Xi - Irritant

R-phrases R₃₇/₃8 – Irritating to respiratory system and skin

R41 – Risk of serious damage to eyes

R₄₃ – May cause sensitization by skin contact

S-phrases S₂₄/₂₅ – Avoid contact with skin and eyes

S₂6 – In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice

S₃₇/₃₉ – Wear suitable gloves and eye/face protection

S₄6 – If swallowed, seek medical advice immediately and show this container or

label

S₅₁ - Use only in well-ventilated areas

S₅6 – Dispose of the material and its container to hazardous or special waste

collection point

S64 – If swallowed, rinse mouth with water, only if the person is conscious

16 OTHER INFORMATION

According legislation Health & Safety at Work etc. Act 1974

Consumer Rights Act 2015

Control of Substances Hazardous to Health Regulations (COSHH) 2002 Control of Substances Hazardous to Health (Amendment) Regulations 2004

Environmental Protection Act 1990

HSE Guidance Note EH40 (Workplace Exposure Limits) Manual Handling Operations Regulations 1992 (as amended)

Chemicals (Hazard Information and Packaging for Supply) Regulations 2009

Important remarks EH40: Workplace Exposure Limits

A step-by-step guide to COSHH Assessment (HS(G)97)

The information and data in this Safety Data Sheet are based on current scientific and technical state of the art and are believed to be accurate at the printing date.

The information refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

History

First edition date 01/07/2007
Previous revision date 01/01/2010
Review date 01/01/2021

Version 2