

Rainwater Compatibility Chart

| Manufacturer | 112mm Half Round | Square Line | Deep Flow | Krown Ogee | 150mm Kommercial |
|------------------|------------------|-------------|-----------|------------|------------------|
| Brett Martin | ✓ | x | ✓ | x | x |
| FloPlast | ✓ | ✓ | ✓ | x | x |
| Freeflow | ✓ | ✓ | ✓ | x | x |
| Gerberit Terrain | x | x | x | x | x |
| Hepworth | ✓ | ✓ | ✓ | x | ✓ |
| Hunter | ✓ | ✓ | ✓ | ✓ | x |
| Marley | ✓ | x | ✓ | x | ✓ |
| Marshall Tufflex | ✓ | ✓ | ✓ | x | x |
| Osma (Wavin) | ✓ | x | ✓ | x | ✓ |
| Polypipe | ✓ | ✓ | ✓ | x | ✓ |

Gutter flow capacity with outlet at the centre of the gutter run

| System | Gutter Level | 1:350 Gradient |
|------------------|-----------------|------------------|
| 112mm Half Round | 1.90 Litres/Sec | 2.43 Litres/Sec |
| Square Line | 2.20 Litres/Sec | 3.03 Litres/Sec |
| Deep Flow | 3.80 Litres/Sec | 5.00 Litres/Sec |
| Krown Ogee | 3.77 Litres/Sec | 4.60 Litres/Sec |
| 150mm Kommercial | 4.60 Litres/Sec | 6.467 Litres/Sec |

Gutter flow capacity with outlet at the end of the gutter

| System | Gutter Level | 1:350 Gradient |
|------------------|-----------------|-----------------|
| 112mm Half Round | 0.95 Litres/Sec | 1.21 Litres/Sec |
| Square Line | 1.10 Litres/Sec | 1.55 Litres/Sec |
| Deep Flow | 2.05 Litres/Sec | 2.56 Litres/Sec |
| Krown Ogee | 1.87 Litres/Sec | 2.29 Litres/Sec |
| 150mm Kommercial | 2.30 Litres/Sec | 3.23 Litres/Sec |

Note:

The above is for guidance only for connection to existing fitted compatible systems.

However, we do not recommend that you mix systems as all manufacturers have slightly different tolerances.