AURES SLIM MULTI





Aures Slim Multi is a great way to supply one or several water outlets (not simultaneously) with instant hot water. Get hot water precisely when needed and in the right amount by simply opening the tap, with no pre-heating time or space necessary to store it.

- / Multi-point model to supply multiple water outlets
- / Flow sensor system initiates instantaneous water heating when a tap is opened
- / Complete safety thanks to its double thermal cut-out
- / Sleek cover of water inlet and outlet pipes
- / Front-facing dial and LED indication for ease of operation
- 4-step dial to set the desired power level option to set at 0, low (4.5kW) medium (5kW), & high (9.5kW)
- / Easy to maintain with frontal access to all internal components
- / Compact size, allows for install in small spaces
- / Elegant aesthetic incorporating premium Italian design

ENERGY RATING






























MULTI DOUBLE SAFETY



	SM 9.5 240V EU
А	178mm
В	135mm
С	304mm
D	45mm
E	98mm

LEGEND

Cold water inlet G 1/2"

O Hot water outlet G 1/2"

TECHNICAL DATA		AURES SLIM MULTI		
Description		9.5kW		
Efficiency				
ERP Rating	-	А		
Electrical Data				
Voltage On Tech Label	V	240		
Ampere	-	39.6		
Frequency	Hz	50/60Hz		
Power & Performance				
Power	kW	9.5		
Step Power	kW	4.5+5		
Phase	=	Mono		
Max Working Temperature	°C	55		
Characteristics				
Max Working Pressure	bar	8		
Safety Valve (Y/N)	=	Υ		
Heating Element	-	Copper		
Inner Tank Type	=	Plastic		
Water Connection Size	inch/BSP	1/2" BSP		
Min Flow Rate	l/min	2.1		
IP Protection Degree	=	IP24		
Tapping Profile	-	XS		
Product Code		3520028		

Temperature differentials

These are the temperature differentials you can expect from the Aures Slim Multi 9.5:

		Power kW			
		4.5	5	9.5	
	3	22°C	24°C	45°C	
Flow rate I/min	4	16°C	18°C	34°C	
	5	13°C	14°C	27°C	

At full power (9.5kW) you can expect to achieve an outlet temperature (at the following flow rates) of:

Flow rate I/min	3	4	5
Summer: Inlet temp @ 20°C	55°C	54°C	47°C
Average: Inlet temp @ 12°C	55°C	46°C	39℃
Winter: Inlet temp @ 5°C	50°C	39°C	32°C

E.g. For a 12°C main water supply @ 4 litres/min, there will be an outlet temperature of 46°C.

UNLIMITED HOT WATER IN AN INSTANT WHEREVER YOU NEED IT

In the interest of our customers, Ariston Thermo UK Ltd is continually developing products to improve both performance and design. We therefore reserve the right to change specification without prior notice. Consumer statutory rights are not affected. The information in this brochure was correct at the time of going to print.

