

# Briton TRUSTED FOR DOOR CLOSERS

WHICH CLOSER IS RIGHT FOR YOUR APPLICATION?



## Low Usage

Suitable for Fire & Non-Fire Doors



### Briton 121CE 39765

Compact overhead closer

- Fixed power size 3
- Certified for Regular, Transom and Parallel arm door applications
- Screw thread armset
- Suitable for doors up to 950mm and 60kg
- Certified and tested to EN 1154 & EN 1634



## Medium Usage

All Closers Suitable for Fire & Non-Fire Doors



### Briton 131 95690

Template adjustable overhead closer

- Adjustable power size EN 2-4
- Certified for Regular, Transom and Parallel arm door applications
- Adjustable soft closing speed & quiet latch action
- Suitable for doors up to 1100mm and 80kg
- Certified and tested to EN 1154 & EN 1634



### Briton 1110 58459

Template adjustable overhead closer

- Template adjustable size EN 2-4
- Certified for Regular, Transom and Parallel arm door applications
- Adjustable soft closing speed & quiet latch action
- Suitable for doors up to 1100mm and 80kg
- Certified and tested to EN 1154 & EN 1634



## High Usage

All Closers Suitable for Fire & Non-Fire Doors



### Briton 2130B 47281

Spring adjustable overhead closer

- Adjustable power size EN 2-6
- Certified for Regular, Transom and Parallel arm door applications
- Backcheck capability
- Self-adhesive fitting template
- Classic cover
- Adjustable soft closing speed & quiet latch action
- Suitable for doors up to 1400mm and 120kg
- Certified and tested to EN 1154 & EN 1634



### Briton 1120B 39765

Spring adjustable overhead closer

- Adjustable power size EN 2-4
- Certified for Regular, Transom and Parallel arm door applications
- Adjustable soft closing speed & quiet latch action
- CE & UKCA marked with backcheck in all applications
- Suitable for doors up to 1100mm and 80kg
- Certified and tested to EN 1154 & EN 1634



### Briton 2003 31698

Fixed power overhead closer

- Fixed power size EN 3
- Certified for Regular, Transom & Parallel arm door applications
- Adjustable soft closing speed & quiet latch action
- Self-adhesive fitting template
- Fire door usage - regular & transom applications only
- Suitable for doors up to 950mm and 60kg
- Certified and tested to EN 1154 & EN 1634



### Briton 2003V 25184

Spring adjustable overhead closer

- Adjustable power size EN 1-4
- Certified for Regular, Transom and Parallel arm door applications
- Adjustable soft closing speed & quiet latch action
- CE and UKCA marked with backcheck in all applications
- Suitable for doors up to 1100mm and 80kg
- Certified and tested to EN 1154 & EN 1634



It's important to select the right door closer for your application.

For fire door usage refer to Certifire certificates for details.



CE Marked to relevant EN Standards



UKCA Marked to relevant EN Standards



Certifire approved.



Fire tested to EN 1164 to achieve a rating on timber and metal doors.



Capable of meeting BS8300 approved Document M requirements.



Tested to ISO 14025 & EN 15804 environmental product declarations.

## Door size chart - EN 1154

EN Closer Size	Recommended Door Sizes	
	Maximum Door Width	Maximum Door Weight
1	750mm	20kg
2	850mm	40kg
3	950mm	60kg
4	1100mm	80kg
5	1250mm	100kg
6	1400mm	120kg
7	1600mm	160kg


**IMPORTANT:** For fire door applications, power size 3 is a minimum requirement.

## Fixing Applications Guide

Most Briton door closers are supplied Tri-pack with the necessary brackets and fixings to enable them to be fitted in any of the applications below.


### Figure 1 Regular fixing\*\*

Closers are door mounted on the pull or opening face of the door.



### Figure 61 is transom mount push\*\*

Closers are transom mounted on the push or closing face of the door.



### Figure 66 parallel fixing application\*\*

Closers are transom mounted on the push or closing face of the door.

