

Briton TRUSTED FOR EXIT DEVICES

WHICH EXIT DEVICE IS RIGHT FOR YOUR APPLICATION?



Briton 378 22644

Push Bar Panic Latch

CERTIFIED TO EN 1125



For Single & Double Rebated Doors

- Certified to EN 1125 and UKCA & CE marked
- Suitable for use on fire & smoke doors up to 1300mm wide
- Site reversible - easy to hand on site
- Rim panic latch with single point latching
- Suitable for single doors and double rebated doors when used in combination with Briton 376 panic bolt and double door strike



Briton 376 19078

Push Bar Panic Bolt

CERTIFIED TO EN 1125



For Single & Double Rebated Doors

- Certified to EN 1125 and UKCA & CE marked
- Suitable for use on fire & smoke doors up to 1300mm wide (extension rods required to achieve maximum height)
- Site reversible - easy to hand on site
- Two-point locking for extra security
- Anti-thrust device, prevents forced latch retraction
- Adjustable top & bottom shoots
- Supplied with easy clean socket
- Suitable for single doors and double rebated doors when used in combination with Briton 378 panic latch and double door strike



Panic Exit Hardware - EN 1125

Panic applications require an operating device that covers the width of the door. Used by members of the public it must provide a safe and effective escape with minimum effort and without prior knowledge of operation.

Typical applications:

- ✓ Shops
- ✓ Schools
- ✓ Hospitals
- ✓ Theatres & Cinemas

Emergency Exit Hardware - EN 179

Emergency applications require only a single point of operation. Used in low occupancy environments, these should only be used by trained personnel and never accessed by the public or people unfamiliar with the escape drill.

Typical applications:

- ✓ Offices
- ✓ Private Flats & Apartments
- ✓ Factories Store/Boiler Rooms
- ✓ Factories



If in doubt, always choose a product to EN 1125

Briton 377 28832

Push Bar Panic for Double Rebated Doors

CERTIFIED TO EN 1125



For Double Rebated Doors

- Certified to EN 1125 and UKCA & CE marked
- Suitable for use on fire & smoke doors up to 2600mm wide (extension rods required to achieve maximum height)
- Site reversible - easy to hand on site
- Three-point locking for extra security
- Anti-thrust device, prevents forced latch retraction
- Comprises of Briton 376 vertical panic bolt, 378 reversible rim panic latch and 378DDS double door strike in one convenient pack
- Adjustable top & bottom shoots



Briton 1438 49030

Push Pad Emergency Latch

CERTIFIED TO EN 179



For Single & Double Rebated Doors

- Certified to EN 179 and UKCA & CE marked
- Pad operated rim latch
- Suitable for use on single doors and the first opening leaf of double rebated doors when used in combination with Briton 372 vertical bolt device and double door strike
- Site reversible for left or right hand
- Can be used with a rim cylinder fitted to the outside of the door



Need Access from Outside?

For Single & Double Doors (fitted to the first opening leaf)

- Lever or knob operated version
- Supplied with 40mm euro profile cylinder as standard (available masterkeyed or keyed alike)
- Self handed or site reversible



1413.LE

1413.KE



Located in a Public Area - Certified to EN 1125.



Located in a Non Public Area - Certified to EN 179.



CE Marked to relevant EN Standards



UKCA Marked to relevant EN Standards



Certifire approved.



Fire tested to EN 1164 to achieve a rating on timber and metal doors.



Tested to ISO 14025 and EN 15804 environmental product declarations.



Level of security.