

PRODUCT DATA SHEET

EVERBUILD® MULTI STICK

Superior high strength grab adhesive based on hybrid polymer technology

PRODUCT DESCRIPTION

EVERBUILD® MULTI STICK, based on hybrid polymer technology, is the ultimate building adhesive, the first hybrid polymer grab adhesive especially created for the Trade, uniquely packed in a plastic 350 ml cartridge. This superior adhesive has the ability to bond virtually anything to everything in both wet and dry conditions, and even underwater or in the rain. With incredible initial grab, high bonding strength, and almost limitless applications and other benefits, no tradesman should be without a tube of this next generation adhesive.

USES

- As a high quality nail replacement adhesive, even to damp surfaces
- Bonding mirrors to most common substrates
- Cladding panels
- Bonding difficult materials
- Any application requiring high performance, durable bonding
- Applications where resistance to chemical spillage is required

CHARACTERISTICS / ADVANTAGES

- Primerless adhesion to most common building substrates, porous and non-porous
- Internal and External use
- Fast curing
- Virtually odourless
- Low dirt pick up
- Excellent break off and tooling
- Waterproof
- Weather resistant
- UV resistant
- Chemical resistant
- Suitable for use with glass, aluminium and PVC

PRODUCT INFORMATION

Packaging	350 ml cartridge
Shelf Life	Use 12 months from date of manufacture.
Storage Conditions	Store in cool dry conditions away from direct sunlight between +5 °C and +25 °C. Storage outside these parameters will dramatically reduce the shelf life.
Colour	White
Density	1.6 - 1.7 g/cm ³

TECHNICAL INFORMATION

Shore A Hardness	60 - 70
Service Temperature	-50 °C to + 80 °C

APPLICATION INFORMATION

Yield	Approx. 12 linear metres for a 6 mm diameter bead.
Sagging	Nil
Ambient Air Temperature	+5 °C to + 35 °C
Curing Time	≥1 mm per 24 hours
Skin Time	20 – 40 mins

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

- Use on overhead applications – Always use in conjunction with mechanical fixings.
- Use in conjunction with mechanical fixings for glass block fitting or large mirrors (>0.5 m² total area).
- For heavy items, provide temporary support until adhesive has cured.
- New plastics, especially PVC, will require light abrasion.
- In areas of high UV some darkening/discolouration may occur. This does not affect the performance.
- Overpaintability: check compatibility with specific paint first before overpainting large areas.
- Do not use on polythene safety-backed mirrors, polypropylene or Teflon.
- Do not use on surfaces that bleed oils or plasticizers.
- Not for use as part of a glazing system.
- Not for use in aquarium manufacture.
- Not for use in conjunction with bitumen or asphalt.
- Yellowing can occur in the dark.
- It is the user's responsibility to determine suitability for use. If in doubt, please contact Technical Services Department for advice.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

- Surfaces must be clean, dry and free from dust, grease, loose material etc.
- Prime dusty surfaces with Everbuild® 501 PVA Bond diluted 1:4 with water and allow to dry.
- Apply using a standard sealant gun, cut tip of cart-

ridge, apply nozzle and cut an opening to suite the required bead size.

APPLICATION METHOD / TOOLS

- Cut the tip of the cartridge taking care not to damage the thread. Fix nozzle, cut aperture to required width and apply with a standard sealant gun.
- For bonding heavy items (plasterboard, worktops, wall panels etc) apply adhesive all the way around the edge of the item (30-50 mm from edge) and cover back with beads of adhesive at 300 mm intervals. Alternatively, apply adhesive direct to battens and press into place. With heavy items, always provide temporary support until the adhesive dries.
- For bonding lightweight items (coving, dado rails, skirting etc) apply adhesive to back of item in one or two continuous beads and press immediately into place.
- Where gap filling is required, mark the areas where there is a large gap and apply a thicker bead to these areas.

CLEANING OF TOOLS

Clean up excess adhesive immediately with a cloth/white spirits.
Cured material should be removed mechanically.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recom-

mendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

Product Data Sheet

**EVERBUILD® MULTI
STICK**

December 2021,
Version 02.01
020513020000000061
3 / 3



BUILDING TRUST



EVERBUILDMULTISTICK-en-GBEVER-(12-2021)-2-1.pdf