

Part Number: LEVK079

Product Description: Fill and Flush valve kit

Approvals: WRAS 1709096

Applied Standard(s): BS EN 997:2018

Material(s): ABS, Brass, Chrome Plated, EPDM, POM,
Rubber, Silicon, Stainless Steel

Approx. Weight (kg): 0.660

Product Dimensions: See specification for individual dimensions

Packaging: Boxed

Product Type: Cistern Fittings Kit

Product Details:

Fill Valve

- Adjustable height from 9" to 13.5".
- 1/2" BSP Thread
- Proprietary pilot technology provides consistent water level at various pressures.
- Wide range of adjustability and valve options for most applications.
- Easy to install
- Proven and reliable quality
- Standard operating pressure: 0.2 Bar (2.6 psi) - 15.85 Bar (230 psi).
- Water level range: 4.0" (102mm) lowest, 11.5" (292 mm) highest
- Critical Level marking: 2" (50mm) from the top
- Recommended torque range: 6Nm to 10Nm (Approx. hand tight plus 1/2 to 3/4 turn)
- Footprint: 97 mm x 72 mm.

Flush Valve

- Dual Flush Option with adjustable full and partial flush volumes - Lever is etched with flush volume indication
- Will suit 1.5" cistern outlet sizes
- 350mm Cable Length
- Cable orientation allows for Top, side or front mounted button
- Lever to replace traditional lever option in cistern
- Internal Overflow with adjustable height
- Quick release lever connection
- Valve body to base twist and release action allows for quick and easy maintenance
- Small Footprint - L 120mm x W 80mm x H 210mm
- Recommended Torque for back nut is 6Nm - 10Nm - (Approx . Hand tight plus up to 3/4 Turn)



For further information about Fluidmaster products please go to:

<https://www.fluidmaster.com/united-kingdom-products/>

Installation Notes:

See installation instructions for full detail

End Of Life Data:

Please recycle all components in accordance with local guidelines/facilities.

Product Warranty: 12 months