

Combi Drill XGT®

HP001GZ01

40V max • 140 Nm • 0 – 2 600 min⁻¹

Rugged, brushless combi drill for heavy-duty screwdriving and drilling

A powerful, brushless drill for screwdriving and drilling with or without hammer action, two power settings. A high maximum torque of 140 / 68 Nm. An ideal choice for jobs that require high power and torque. Integrated LED light. Tool only, battery and charger not included. Tool comes in a Makpac case.



Technical specifications

Voltage XGT	✓
Nominal Battery Voltage	40 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 650 / 2600 min ⁻¹
Max. fastening torque Hard/Soft	140 / 68 Nm
Torque setting	41 / 21
Impacts per Minute (IPM)	0 - 9750 / 39000 min ⁻¹
Max. Drilling Diameter in Wood	76 mm
Max. Drilling Diameter in Masonry	20 mm
Max. Drilling Diameter in Steel	20 mm
Driving Shank	1/2"-20UNF "
Drill Chuck Capacity	1,5 - 13 mm
Sound Power Level (L _{WA})	96 dB(A)
Sound Pressure Level (L _{pA})	85 dB(A)

User benefits

- Jog selector for easy adjustment of mounting torque, visual confirmation of the selected torque on the digital display
- XPT (Extreme Protection Technology) is engineered for improved dust and water resistance for operation in harsh job site conditions
- Battery protection system automatically shuts off power when the battery level is low
- Active Feedback sensing Technology (AFT) stops the engine if the rotation suddenly stops

EAN 0088381894043

Link to product - www.makita.com



Related products

Standard AC

127551-9
Grip Assembly



122576-8
Stopper Pole



346317-0
Belt Hook



784637-8
Screw Bit, Ph2 – S6, 45 Mm, Double



452947-8
Bitholder



251314-2
Truss Head Screw M4*12, Td140D



821551-8
Makpac case (3)



835F93-2
Inner tray (3)



Optional AC

122576-8
Stopper Pole



127551-9
Grip Assembly



346317-0
Belt Hook



452947-8
Bitholder



763252-1
Keyless Drill Chuck



784637-8
Screw Bit, Ph2 – S6, 45 Mm, Double



Other

[User manual](#)

[Parts drawing](#)