TECHNICAL SPECIFICATION



PressToCheck™ A2 P3 Filters

Pack of 2 / BMN740-000-600



DESCRIPTION

PressToCheck™ is the easiest way to face-fit check the seal of your respirator, every time you put it on! The range features HEPA filtration exceeding 99.95%, Low profile design maximising compatibility and low breathing resistance across the range.

F-4123 A2P3 organic gas / vapour + dust replacement encapsulated filters, featuring PressToCheck $^{\text{TM}}$ technology for daily face-fit reassurance.

Winner of the BSIF Product Innovation Award.

OPTIONS

Pack of 2 (BMN740-000-600)

SAFETY STANDARDS

EN 14387





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com







SPECIFICATIONS

Classification

A2P3

Usage

R (Reusable)



Activated Carbon Filter

Yes

Maximum Total Inward Leakage (TIL) 2% when fitted to Force8 Half Mask

Nominal Protection Factor

12 When Fitted To A Force8 Half Mask

UK Assigned Protection Factor

10 When Fitted To A Forec8 Half Mask

9

Type

Press To Check Technology

Metal Free

Yes

Filter Casing Material

ABS



BSI Kitemark

Yes



Filter Type

Organic Vapours, Nusance Odours and Particulate



(D) Resistance to dust clogging

Yes – D marking = passes optional clogging test

Minimum Filtration Efficiency 99.95% For P Rated

Maximum Total Inward Leakage (TIL)

0.05% when fitted to a Force10 Full Face Mask

Nominal Protection Factor

1000 When Fitted To A Force10 Full Face Mask

UK Assigned Protection Factor

20 When Fitted To A Force10 Full Face Mask

Latex free

Yes

Filter Material

Pleated Media & Activated Carbon

Filter Shelf Life 10 Years



Product Weight

231g Per Pair

FEATURES



Increased Product Life

PressToCheck™ encapsulated filters offer ultimate longevity – the durable design makes the filters easy to clean and reuse. Correct cleaning, maintenance and storage increases the useful life of the product.

VIDEOS

- youtu.be/1Y9G8E9kEXQ
- youtu.be/Ecyu_ftPPX4
- youtu.be/-oUSyP9_NsA

DOWNLOADS



doc-force-press-to-check-filter-f-4123.pdf (PDF)







Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





