

Uniclass L621
CI/SfB
/ / / Yq2 / /
October 2018

TECHNICAL INFORMATION

RAPID SET MORTAR

Rapid Setting Mortar Product Data Sheet

A Portland cement based rapid set mortar containing calcium aluminate to give rapid hardening and setting properties:

- For non-structural repair and maintenance where rapid hardening is required, setting manholes, small patch render repairs, repointing.

Blue Circle Rapid Set Mortar is a rapid-setting and hardening Portland cement based mix. At present there is no appropriate British Standard for this product.

Blue Circle Rapid Set Mortar is manufactured under a certified ISO 9001 Quality Management System.



APPLICATIONS

Blue Circle Rapid Set Mortar is for repair and maintenance in building work where rapid setting and rapid hardening properties are beneficial.

Typical uses are as follows:

- Setting manholes
- Repairing rendering and floor screeds
- Work under water table
- Fitting drainage
- Roof repairs.

Due to the rapid setting properties of Blue Circle Rapid Set Mortar, it is recommended that it is placed as soon after mixing as possible, and that mixing time is no longer than that required for thorough mixing.

Normal open time for the ready mix is around 20-30 minutes, depending on weather conditions.

PROPERTIES

- Portland cement based
- Light grey in colour when fully dry
- Contains calcium aluminate to give rapid setting and rapid hardening properties
- Sets soon after placing and gains strength rapidly to allow normal services to be brought back into operation in a working day

AVAILABILITY

Blue Circle Rapid Set Mortar is available in 5kg tubs throughout the United Kingdom.

STORAGE

This product should be stored unopened in cool conditions and should be stacked in a safe and stable manner. May be stored outdoors. Information on the maximum storage period can be found on the tub.

TABLE OF TYPICAL PROPERTIES

(For guidance only, not to be used for specification or compliance purpose)

Open Time	(minutes)	15 to 30
BS EN 1015 Mortar compressive strength		
– 6 hour	(N/mm ²)	4 to 6
– 1 day	(N/mm ²)	10 to 15
– 28 day	(N/mm ²)	30 to 40

CONDITIONS OF USE

- No attempt should be made to alter the set time of Blue Circle Rapid Set Mortar by use of admixtures or inclusion of Portland cement
- To achieve optimum performance from Blue Circle Rapid Set Mortar or other products, it is essential that it is correctly specified and used
- As with other cements in building work, there is no substitute for good practice and workmanship. It is essential to use the correct materials, proportion and mix the materials properly, add the correct amount of water, compact, cure and protect as appropriate
- Do not use when air temperature is below 5C or greater than 30C
- The final finish quality of this material will depend upon the operative having the required skills and a familiarity with the material and its application methods
- Tarmac Cement cannot be held responsible where workmanship has not been carried out in accordance with good practice
- Manual handling should comply with *The Manual Handling Operations Regulations 1992*.

TECHNICAL SUPPORT

Further information and advice on this product and the full range of Tarmac Cement products can be obtained through the contacts listed below.

HEALTH AND SAFETY

Contact between cement powder and body fluids (eg, sweat and eye fluids) may cause irritation, dermatitis or burns. For further information, including control of soluble hexavalent chromium, refer to the appropriate Tarmac Cement Health and Safety Information Sheets.

For further information

Technical helpdesk

Tel: 0845 812 6232

E-mail info-cement@tarmac.com

Customer services & sales

Tel: 0845 812 6300

E-mail customerservice@tarmac.com

Tarmac and the 'circle logo' are registered trademarks. ©2015 Tarmac Trading Limited

The information in this data sheet is accurate at the time of printing, but Tarmac reserves the right to amend details as part of its product development programme. The information given in this technical data sheet is based on our current knowledge and is intended to provide general notes on our products and their uses. Tarmac endeavour to ensure that the information given is accurate, but accept no liability for its use or its suitability for particular application because of the product being used by the third party without our supervision. Any existing intellectual property right must be observed.