

THOR

USER GUIDE - 28013T

by Labgear

32-70"

Anti-theft Heavy Duty Fixed TV Wall Mount


- We have not supplied wall fixings with this product. All walls differ in strength and thickness.
 Consult a qualified installer or seek advice from your local DIY/hardware store on purchasing suitable wall fixings to safely mount the bracket on the type of wall being used.
- Check the components list and images to check there are no missing or defective parts.
- Never exceed the Maximum Weight Capacity.
- Read these instructions carefully before installation. If in any doubt about safely installing this product, contact a professional installer for assistance.
- This product was designed to be installed on wood stud walls and solid concrete/ brick walls. When fixing to walls screws/bolts should be fixed into bricks/stone not into mortar courses.
- Make sure the wall will support the combined load of the equipment and hardware. Also check for hidden wiring or plumbing.
- Make sure that the heads of the screws/ bolts you buy as wall fastenings are the correct size to hold the bracket securely in position.

- Always ensure that all 4 bolts engage well into the VESA threaded apertures on the back of your TV; to at least a depth of 70% of the total depth of the aperture to ensure your TV is attached securely to the TV mount.
- · For larger/heavier TVs we recommend that you ask someone to assist you with lifting and positioning your TV.
- · This product is suitable for indoor use only.
- Improper installation or use of this product can result in product failure, damage or personal injury.
- This product contains small items that could cause choking if swallowed, so keep these items away from children and pets.
- Appropriate safety equipment and proper tools must be used for installation. Always check manufacturer's operating and safety instructions before using tools and other equipment.

UK Distributor: Philex Electronic Ltd., London Road, Bedford, MK42 ONX, U.K.

EU Distributor: Philex Electronic Ireland Ltd., Robwyn House, Corrintra, Castleblayney, Co. Monaghan, A75 YX76, Ireland.

© Philex Electronic Ltd. 2021. Vb1.2




• TV Size range: **32-70**"

· Maximum weight capacity: 45kg

· Mount function: Fixed

· Wall to TV distance: **26mm**

Compatible with VESA sizes:
200 x 200, 300 x 300, 400 x 200, 400 x 400



Measure the distances marked (2) (horizontal) x (1) (vertical) below in mm to find your VESA format.

plays a rectangular shape.


• To check if your TV or monitor is compliant, look at the rear of the display there should be 4 screw/bolt holes in a square pattern or in larger dis-

comply with VESA.

• VEAA comes in a range of sizes depending on the weight and size of the flat screen TV; sizes 50 x 50mm, 75 x 75mm, 100 x 100mm, 200 x 100mm and so on... are standard. Not all flat screen TVs are compliant, contact the TV manufacturer for assistance if your TV does not appear to

between the holes is governed by the VESA standard.

- There are 4 holes on the back of every flat screen TV and the space
 - VEAP is the standard adopted by most TV manufacturers for wall bracket mounting.



Before installation check that you have all the components shown here and that none of them are damaged.




Fig.1

2a. Preparing Wall Fixings - Stud WallsTools required



The wall bracket (a) is attached to the wall using four appropriate screws/bolts as shown in Fig.2. Make sure the screws/bolts are suitable for wood and large enough to support the weight of the TV and bracket (if in doubt ask for advice at your local DIY/hardware store and remember to make sure that the heads of the screws/bolts are the correct size to hold the bracket securely in position).

Mark and drill four holes into the wood as close as possible to the centre of theupright (you can use a stud detector to find stud positions).

To mark the holes, hold the bracket to the wall, using a spirit level to make sure the bracket is level, and mark the centre of each hole, see Fig.1. Drill the four holes and attach the bracket to the wall using the appropriate screws/bolts.




Use the spirit level to ensure bracket is level














3a. Attaching the Adaptor Brackets

(≥70% of depth)





5. Fitting the Locking Bar and Padlock



6. Securing the Adaptor Brackets

