





DOMESTIC

FANS

BATHROOM

Simply Silent[™] LV100TS

4" / 100mm SELV axial bathroom fan with wall fitting kit

Toolstation Product Code 89511

The Simply Silent[™] LV100TS (Low Volt) intermittent extractor fan is designed specifically for safe installation directly in or over the splash area zone 1, offering complete peace of mind. The model is supplied with a 12V SELV transformer, positioned out of reach of any person using the bath or shower. LV100TS has two speeds, selectable at install, and features a wall-fitting kit. The product is suitable for wall, ceiling and window fitting (requires Simply Silent Window Kit - Toolstation Product Code 52015).

LV100TS has an overrun timer which can be set at install between 30s and 30 minutes (the factory set point is 15 minutes). This means that the fan continues to operate for this time once the external switch (for example a lighting circuit) is turned off.


Technical Details

	LV100TS
No. of Speeds	2
Power (W)	5.5 / 11.8
Duct Size (mm)	100
Flow rate (l/s)	15/21
Flow rate (m3/h)	54/76
Noise dB(A)3m	22/34
Specific Fan Power SFP (W/I/s)	0.37 / 0.56
IPX Rating	IPX4
Motor Type	AC
Pullcord	
Timer (30s—30mins)	√
Timer (30s—30mins) Humidistat (50 to 90%)	<u>۷</u>
	<u>√</u> х
Humidistat (50 to 90%)	
Humidistat (50 to 90%) Integral backdraught shutter	x
Humidistat (50 to 90%) Integral backdraught shutter Height (mm)	X 178.5
Humidistat (50 to 90%) Integral backdraught shutter Height (mm) Width (mm)	X 178.5 178.5
Humidistat (50 to 90%) Integral backdraught shutter Height (mm) Width (mm) Depth (mm)	X 178.5 178.5 122.2
Humidistat (50 to 90%) Integral backdraught shutter Height (mm) Width (mm) Depth (mm) Packed Weight (kg)	X 178.5 178.5 122.2 2.1
Humidistat (50 to 90%) Integral backdraught shutter Height (mm) Width (mm) Depth (mm) Packed Weight (kg) Packed Height (mm)	X 178.5 178.5 122.2 2.1 222

Dimensions



178.5m



Simply Silent[™] LV100TS



