



Basin Taps, Bath Taps, Sink Taps


Fitting instructions




43557



68181



92643



65911

Please keep these instructions for future reference.

Contents

Page

1. Tools required

3

2. Parts Supplied

3

3. Specifications

3


4. Installation

4

5. Aftercare


4

Tools required (Tools not supplied)



Parts Supplied

NO.	Description	Qty
1	Tap Body	2
2	Flange	2
3	Sealing Washer	2
4	Anti-Rotational Washer	2
5	Backnuts	2



Specifications

The taps is suitable for use at water supply pressures of 0.1 bar (min.) to 5 bar (max.).


This pressure rating is determined by the manufacturer using soft water under test house conditions and may differ to the retailer's recommendation.

This taps should be installed in compliance with Water Regulations. For further details contact your Local Water Authority.

- (a) Identify all components and check pack contents.
- (b) Turn off water mains supply.

Installation

1. Fit Tap Body (1) to basin/bath/sink, ensuring that the Sealing Washer (3) is fitted between the Flange (2) and the basin/bath/sink.
2. Fit Anti-Rotational Washer (4) and Backnuts (5) to the inlet legs and tighten. **DO NOT OVERTIGHTEN.**
3. Connect to the water supply using suitable plumbing joints.
Note: the Hot tap is fitted to the left-hand side and the Cold is fitted to the right-hand side.
4. Turn on the hot and cold and mains water supply.
Check for leaks immediately. It is always advisable at this stage to flush out the system. To do this, open both valves fully and allow water to flow for approx. 1 minute. This will remove any foreign matter within the installation.
5. Finally turn on all the water heating arrangements.



Aftercare

Whilst modern plating techniques are used in the manufacture of these fittings, the plating will wear if not cleaned properly. The safest way to clean your product is to wipe with a soft damp cloth. Stains can be removed using washing up liquid. All cleaning powders and liquids will damage the surface of your fitting even the non-scratch cleaners.