



Certificate number: 2507748 (1)

Issued 20/08/2025

Expires 20/08/2030

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Methven UK Limited.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Methven UK Limited
3-3a Stone Cross Court
Yew Tree Way
Golborne
Warrington
WA3 3JD
United Kingdom



KUKreg4

Product Certificate

Appendix to Certificate number: 2507748

The following products belong to this certificate

PRODUCT DESCRIPTION Range of deck mounted double hole, single outlet (swivel) combination tap assemblies (chromium plated brass). Incorporating ceramic disc headworks (DLV305B, DLT305B) or non-rising spindle headworks (CR305 BRIDGE, CR305/501 BRIDGE) and single lever (DLV305B, DLT305B) or cross (CR305 BRIDGE, CR305/501 BRIDGE) operating members. ATS3 – Without Production Surveillance.
MODEL(S) DLT305B Lever Action Bridge Sink Mixer DLV305B Lever Action Bridge Sink Mixer With 6" Levers CR305 BRIDGE Coronation Bridge Sink Mixer CR305/501 BRIDGE Coronation Bridge Sink Mixer – Gold
SIZE: ½" BSP (M).
SCOPE: Manufacturer recommended maximum working pressure 10.0 Bar & maximum operating temperature 60°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 60°C.
MARKING DEVA, DTC 59 etched on underside of body.
MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.
BACKFLOW PROTECTION NOTES If this tap or combination tap is installed so that its base is no lower than the spillover level of the receiving vessel a Type AUK3 air gap is achieved. Consider balanced supplies or appropriate backflow protection at the inlets.
ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.

Extra Notes