



Certificate number: 2502702 (1)

Issued 03/02/2025

Expires 03/02/2030

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Norcros Group (Holdings) Limited T/A Abode.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Norcros Group (Holdings) Limited T/A Abode
Unit L
Zenith Park
Whaley Road
Barnsley
United Kingdom



KUKreg4

Product Certificate

Appendix to Certificate number: 2502702

The following products belong to this certificate

PRODUCT DESCRIPTION Range of single hole, single outlet (swivel) combination tap assemblies incorporating quarter turn ceramic disc headworks with single lever operating members. The spout outlet incorporates a plastic aerator. ATS3 – Without Production Surveillance.
MODEL(S) ACT3046 - Chrome ACT3047 – Brushed Nickel ACT3048 – Matt Black ACT3057 – Brushed Brass.
SIZE: Stainless steel braided EPDM lined flexible hose assemblies incorporating ½" BSP (F) captive nut end connections.
SCOPE: Manufacturer recommended maximum working pressure 5.5 Bar & maximum operating temperature 60°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 60°C.
MARKING CAL etched on rear of body.
MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.
BACKFLOW PROTECTION NOTES If this tap or combination tap is installed so that its base is no lower than the spillover level of the receiving vessel a Type AUK3 air gap is achieved. Consider balanced supplies or appropriate backflow protection at the inlets.
ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.

Extra Notes